1 6 APR 1992

f.s. aut.ileen neman ird Architectural Finishes, Inc. Coatings and Resins Croup lol colfax Street, P.O. Box 127 Springgale, PA 15144

Dear ... kennan:

subject: Olympic wood Preservative Clear wra registration no. 7313-0 Your Application Dated April 9, 1992, Alternate Formulation with sun Block, Revised Labeling To Comply with rolpet Registration Standard

The Proposed alternate confidential statement of formula sawmittee th him form 5570-4 and dated north 5, 1992 is acce, table and has been added to the Lin record for this [I would acquation.

the proposed levised lebelling admitted with the appliestion to amend the adaptot resticing product registration under the inderal insecticies, Eungleide and Roderticide Act LE amended is acceptable provided:

- 1. correct the typographic error in the Limited Marranty scattment in the sentence that redus: "bone states so theyou".
- 2. Inst you submit 5 copies of the tinal printed labeling before releasing the product for shipment.

lf these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA. bection ofe). Four release for star ent of the product constitutes acceptance of these conditions.

A stamped copy of the laneling is enclosed for your records.

sincerely yours,

Johnne I. Liller Product danager (23) tungicias-derbicide branch Registration Division (a-75050)

which to take

L. .. I I SUN: DISKETTER UUUUL: U4-10-5%

BEST AVAILABLE COPY

Ve la

Concerd 4-16-9-

FRONT PANEL:

(Left top corner in the raindrops, using a starburst design)
"NOW WITH 5-WAY PROTECTION"

"PRESERVES AND PROTECTS WOOD BEAUTIFULLY"

OLYMPIC (R)

CLEAR WOOD PRESERVATIVE

o REPELS WATER
o MILDEW RESISTANT
o RESISTS SUN DAMAGE
o LINSEED OIL PROTECTION
PLUS (in italics)
o WOOD PRESERVATIVE

One Gallon / 3.78 Liters

ACCRPUID
with COMMENTS
in EPA Letter Dates

16 APR 1992

Under the Federal Insesticide, Functicide, and Rodenticide Act as amended, for the posticide registered under EPA Reg. No. 1/313 - 6

and

Five Gallon / 18.9 Liters

KEEP OUT OF REACH OF CHILDREN (12 pt.)
WARNING! (18 pt.) HARMFUL IF SWALLOWED OR INHALED. COMBUSTIBLE.
See back panel for additional precautionary statements. (12 pt.)

Contains petroleum distillates.
MEETS FED. SPEC TT-W-572B 3.7
EPA Reg. No. 7313-6 EPA Est. No. 7313-WA-1, 7313-IL-1, 7313-KY-1

FEST AVAILABLE COPY

LEFT SIDE PANEL

LIMITED WARRANTY

OLYMPIC warrants your satisfaction with the application, appearance and performance properties of this product if it is properly applied to a properly prepared surface in accordance with label directions. OLYMPIC MAKES NO OTHER EXPRESS IN THE EVENT THE PRODUCT PAILS TO CONFORM TO THIS WARRANTIES. WARRANTY, OLYMPIC, AS ITS SOLE LIABILITY AND IN LIEU OF ANY DIRECT OR INDIRECT, INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES, WILL, AT YOUR OPTION, FURNISH REPLACEMENT PRODUCT OR REFUND THE PURCHASE PRICE - LABOR OR COSTS OF LABOR FOR THE APPLICATION OF ANY PRODUCT SPECIFICALLY ARE EXCLUDED. You must supply proof of This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. Some states do not allow the exclusion or limitation of incidental of Vconsequential damages, so the above limitation or exclusion may not apply to you. To make a claim under this warranty contact the store where you purchased the product or: OLYMPIC STAINS, One PPG Place, Pittsburgh, PA 15272.

RIGHT SIDE PANEL

For 51787 imprints:

UPC Code: One Gallon: 7 15195 17871 6

Five Gallon: 7 15195 17875 4

For 55587 imprints:

MAXIMUM VOC = 350 g/l (2.92 lbs/gal)

Calc. VOC = 332 g/l (2.77 lbs/gal)

UPC Code: One Gallon: 7 15195 55871 6

Five Gallon: 7 15195 55875 4

DIST. BY AND (C) 1990
PPG ARCHITECTURAL FINISHES, INC.
ONE PPG PLACE
PITTSBURGH, PA 15272
(412) 434-3131
MADE IN U.S.A.

BACK PANEL

NOTE: The following label warning should appear in a box with rounded corners at the top of the back panel.

(12 pt.) PRECAUTIONARY STATEMENTS -- HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING (18 pt)

(All headings in 12 pt. type)

Causes substantial but temporary eye injury. May cause an allergic skin reaction. Harmful if swallowed or inhaled. Do not get in eyes, on skin or on clothing. Avoid breathing dust or liquid aerosols. Wear goggles or face shield when handling. Wash thoroughly with soap and water after handling. Remove contaminated clothing and separately launder clothing before reuse.

ENVIRONMENTAL HAZARDS: This product is highly toxic to fish. Keep out of lakes, ponds or streams. Do not contaminate water when disposing of equipment washwaters.

PHYSICAL/CHEMICAL HAZARDS: Combustible. Keep away from heat, sparks or flame. Use with force ventilation. Do not take internally. Close container after each use.

IMPORTANT: Spray equipment must be handled with due care and in accordance with manufacturer's recommendations. Spraying of any material can be hazardous. Wear respirator, eye protection, and protective clothing.

STATEMENT OF PRACTICAL TREATMENT

IF IN EYES: Flush eyes with plenty of water. Call a physician.

IF SWALLOWED: Promptly drink a large quantity of milk, egg whites, gelatin solution, or, if these are not available, drink large quantities of water. Do not drink alcohol. Call a physician immediately.

IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. (-et meuical attention.

For Emergency Medical and Spill Control Information, (304) 843-1300.

BEST AVAILABLE COPY

OLYMPIC (R) CLEAR WOOD PRESERVATIVE

- o Protects Against Costly Water Damage.
- o Protects Against Harmful Sun Damage.
 - o Fights Unsightly Mildew Growth.
- o Linsee! Oil Penetrates Deep To Strengthen Wood Fibers.
- o Preserves Wood While Helping To Maintain Its Natural Beauty

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Apply this product only as specified on this label. Wear goggles or face shield when handling. Remove contaminated clothing and separately launder clothing before reuse. Wash thoroughly with soap and water after handling.

OLYMPIC (R) CLEAR WOOD PRESERVATIVE is a penetrating linseed oil base, water repellent wood preservative. It gives wood protection from rot, decay, mildew, ultra violet light, and moisture damage. Recommended only for EXTERIOR above ground use, it also adds these protective qualities when used under finish coats, resulting in longer life for the wood and the finish. It may also be used on pressure treated wood to protect the wood from water damage, mildew and deterioration due to ultra violet sunlight. It exceeds the Federal specification for water repellency, TT-W-572B, paragraph 3.7.

CLEAR WOOD PRESERVATIVE is recommended on exterior bare wood surfaces which may be exposed to attack by wood rot, mildew or excess moisture. Use on structural lumber, beams, timbers, sills, millwork and roofs. To maintain wood preservation properties, reapplications are recommended every 2 to 4 years.

•

When used prior to painting or staining, allow to dry thoroughly (at least 24 to 48 hours) before applying OLYMPIC(R) Stain or PrimecoatTM. Applications of oil base top coats may result in a higher gloss in some areas which will normally become more uniform with weathering.

Surfaces treated with CLEAR WOOD PRESERVATIVE will be protected from moisture damage, mildew and rot, but will "weather" naturally. Depending on the exposure and the type of wood, this weathering will include a gradual graying. To protect and beautify with color, use one of OLYMPIC'S(R) Semi-Transparent or Solid Color Stains. For severe exposure to wood rot, "pressure treated wood" offers maximum protection.



7 12 7

PREPARATION

SURFACE PREPARATION: Proper surface preparation is essential for Olympic Stain's limited warranty to apply. Surfaces must be clean, dry and free of mildew. Rinse thoroughly and allow to dry before application.

MILDEW: Remove and inhibit regrowth of mildew by using MILDEW CHECK(R) Multi-Purpose Wash by OLYMPIC STAIN.

APPLICATION

Mix thoroughly prior to use. May be applied with a natural bristle brush, spray or by dipping. Use only one thin coat. Thoroughly treat ends and edges of boards. DO NOT THIN.

APPROXIMATE COVERAGE: Depending on texture, porosity and dryness of wood: 150 to 250 square feet per gallon.

TEMPERATURE RECOMMENDATIONS: Avoid application to a hot surface in direct sunlight. Do not apply when the air, coating or surface temperature is below $50^{\circ}F$ ($10^{\circ}C$).

DRYING: CLEAR WOOD PRESERVATIVE will require 24 to 48 hours to dry under ideal conditions.

CLEANUP: Clean brushes and other tools with mineral spirits.

EXTRACTIVE BLEEDING: Some woods contain water-soluble colorings or extractives that tend to "bleed" to the surface. This bleeding may be unsightly but is not damaging to the finish. If it has occurred, allow the coating to dry, then wash with a mild detergent solution and rinse with clear water. For stubborn stains, a second solution of 50% alcohol and 50% water may be necessary.

STORAGE AND DISPOSAL: Securely wrap original container in several layers of newpaper and discard in trash. Do not reuse container. Rinse thoroughly before discarding in trash.

FOR ADDITIONAL INFORMATION - ASK YOUR DEALER OR REFER TO THE OLYMPIC INFORMATION MANUAL.

Label Date Code: (09292)

1731 1731