

09 JUN 1992

Ms. Kathleen Kennan
PPG Architectural Finishes, Inc.
Coatings and Resins Group
151 Colfax Street, P.O. Box 127
Springdale, PA 15144

Dear Ms. Kennan:

Subject: Olypic® Wood Preservative Clear
EPA Registration No. 7313-6
Your Application Dated May 6, 1992, Amendment
of Physical/Chemical Hazards Statement To
Include Spontaneous Combustion Warnings and
Prevention

The proposed amendment to revise the Physical/Chemical Hazards statement to include warnings and prevention measures against potential spontaneous combustion of combustible materials contaminated from overspray or liquid residues of the subject pesticide product has been reviewed and is acceptable under the Federal Insecticide, Fungicide and Rodenticide Act as amended provided that you:

- o submit 5 copies of the final printed labeling before releasing the product for shipment.

If this condition is not complied with, the registration will be subject to cancellation in accordance with FIFRA, Section 6(e). Your release for shipment of the product constitutes acceptance of this condition.

A stamped copy of the labeling is enclosed for your records.

Sincerely yours,

Joanne L. Miller
Product Manager (23)
Fungicide-herbicide Branch
Registration Division (A-7505C)

Enclosure

E.Wilson:Diskette#000001:04-16-92

BEST AVAILABLE COPY

NAC 1000 6-5-92
Eugene L. Nelson

FRONT PANEL:

(Left top corner in the raindrops, using a starburst design)
"NOW WITH 5-WAY PROTECTION"

"PRESERVES AND PROTECTS WOOD BEAUTIFULLY"

OLYMPIC (R)

CLEAR
WOOD
PRESERVATIVE

- o REPELS WATER
- o MILDEW RESISTANT
- o RESISTS SUN DAMAGE
- o LINSEED OIL PROTECTION
PLUS (in italics)
- o WOOD PRESERVATIVE

One Gallon / 3.78 Liters

and

Five Gallon / 18.9 Liters

KEEP OUT OF REACH OF CHILDREN (12 pt.)
WARNING! (18 pt.) HARMFUL IF SWALLOWED OR INHALED. COMBUSTIBLE.
See back panel for additional precautionary statements. (12 pt.)

ACTIVE INGREDIENTS

Bis (tributyltin) oxide.....	0.50%
Folpet [N-(trichloromethylthio) phthalimide].....	0.50%
INERT INGREDIENTS.....	99.00%

Contains petroleum distillates.

MEETS FED. SPEC TT-W-572B 3.7

EPA Reg. No. 7313-6 EPA Est. No. 7313-WA-1, 7313-IL-1, 7313-KY-1

ACCEPTED
with COMMENTS
In EPA Letter Dated:

09 JUN 1992

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
as amended, for the pesticide
registered under EPA Reg. No.

7313-6

LEFT SIDE PANEL

LIMITED WARRANTY

OLYMPIC warrants your satisfaction with the application, appearance and performance properties of this product if it is properly applied to a properly prepared surface in accordance with label directions. OLYMPIC MAKES NO OTHER EXPRESS WARRANTIES. IN THE EVENT THE PRODUCT FAILS TO CONFORM TO THIS WARRANTY, OLYMPIC, AS ITS SOLE LIABILITY AND IN LIEU OF ANY DIRECT OR INDIRECT, INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES, WILL, AT YOUR OPTION, FURNISH REPLACEMENT PRODUCT OR REFUND THE PURCHASE PRICE - LABOR OR COSTS OF LABOR FOR THE APPLICATION OF ANY PRODUCT SPECIFICALLY ARE EXCLUDED. You must supply proof of purchase. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. To make a claim under this warranty contact the store where you purchased the product or: OLYMPIC STAINS, One PPG Place, Pittsburgh, PA 15272.

4 8 7

RIGHT SIDE PANEL

For 51787 imprints:

UPC Code: One Gallon: 7 15195 17871 6
Five Gallon: 7 15195 17875 4

For 55587 imprints:

MAXIMUM VOC = 350 g/l (2.92 lbs/gal)

Calc. VOC = 332 g/l (2.77 lbs/gal)

UPC Code: One Gallon: 7 15195 55871 6
Five Gallon: 7 15195 55875 4

DIST. BY AND (C) 1990
PPG ARCHITECTURAL FINISHES, INC.
ONE PPG PLACE
PITTSBURGH, PA 15272
(412) 434-3131
MADE IN U.S.A.

BACK PANEL

NOTE: The following label warning should appear in a box with rounded corners at the top of the back panel.

(12 pt.) PRECAUTIONARY STATEMENTS -- HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING (18 pt)

(All headings in 12 pt. type)

Causes substantial but temporary eye injury. May cause an allergic skin reaction. Harmful if swallowed or inhaled. Do not get in eyes, on skin or on clothing. Avoid breathing dust or liquid aerosols. Wear goggles or face shield when handling. Wash thoroughly with soap and water after handling. Remove contaminated clothing and separately launder clothing before reuse.

ENVIRONMENTAL HAZARDS: This product is highly toxic to fish. Keep out of lakes, ponds or streams. Do not contaminate water when disposing of equipment washwaters.

PHYSICAL/CHEMICAL HAZARDS: Combustible. Keep away from heat, sparks or flame. Use with forced ventilation. Do not take internally. Close container after each use. Combustible materials contaminated with overspray or liquid residues of this product may undergo spontaneous combustion. To minimize the potential for spontaneous combustion, soak contaminated materials with water or place them in a closed metal container away from buildings and other combustible materials.

IMPORTANT: Spray equipment must be handled with due care and in accordance with manufacturer's recommendations. Spraying of any material can be hazardous. Wear respirator, eye protection, and protective clothing.

STATEMENT OF PRACTICAL TREATMENT

IF IN EYES: Flush eyes with plenty of water. Call a physician.

IF SWALLOWED: Promptly drink a large quantity of milk, egg whites, gelatin solution, or, if these are not available, drink large quantities of water. Do not drink alcohol. Call a physician immediately.

IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

For Emergency Medical and Spill Control Information, (304) 843-1300.

BEST AVAILABLE COPY

OLYMPIC (R) CLEAR WOOD PRESERVATIVE

- o Protects Against Costly Water Damage.
- o Protects Against Harmful Sun Damage.
- o Fights Unsightly Mildew Growth.
- o Linseed Oil Penetrates Deep To Strengthen Wood Fibers.
- o Preserves Wood While Helping To Maintain Its Natural Beauty

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Apply this product only as specified on this label. Wear goggles or face shield when handling. Remove contaminated clothing and separately launder clothing before reuse. Wash thoroughly with soap and water after handling.

OLYMPIC (R) CLEAR WOOD PRESERVATIVE is a penetrating linseed oil base, water repellent wood preservative. It gives wood protection from rot, decay, mildew, ultra violet light, and moisture damage. Recommended only for EXTERIOR above ground use, it also adds these protective qualities when used under finish coats, resulting in longer life for the wood and the finish. It may also be used on pressure treated wood to protect the wood from water damage, mildew and deterioration due to ultra violet sunlight. It exceeds the Federal specification for water repellency, TT-W-572B, paragraph 3.7.

CLEAR WOOD PRESERVATIVE is recommended on exterior bare wood surfaces which may be exposed to attack by wood rot, mildew or excess moisture. Use on structural lumber, beams, timbers, sills, millwork and roofs. To maintain wood preservation properties, reapplications are recommended every 2 to 4 years.

When used prior to painting or staining, allow to dry thoroughly (at least 24 to 48 hours) before applying OLYMPIC(R) Stain or Primecoat™. Applications of oil base top coats may result in a higher gloss in some areas which will normally become more uniform with weathering.

Surfaces treated with CLEAR WOOD PRESERVATIVE will be protected from moisture damage, mildew and rot, but will "weather" naturally. Depending on the exposure and the type of wood, this weathering will include a gradual graying. To protect and beautify with color, use one of OLYMPIC'S(R) Semi-Transparent or Solid Color Stains. For severe exposure to wood rot, "pressure treated wood" offers maximum protection.

BEST AVAILABLE COPY

PREPARATION

SURFACE PREPARATION: Proper surface preparation is essential for Olympic Stain's limited warranty to apply. Surfaces must be clean, dry and free of mildew. Rinse thoroughly and allow to dry before application.

MILDEW: Remove and inhibit regrowth of mildew by using MILDEW CHECK(R) Multi-Purpose Wash by OLYMPIC STAIN.

APPLICATION

Mix thoroughly prior to use. May be applied with a natural bristle brush, spray or by dipping. Use only one thin coat. Thoroughly treat ends and edges of boards. DO NOT THIN.

APPROXIMATE COVERAGE: Depending on texture, porosity and dryness of wood: 150 to 250 square feet per gallon.

TEMPERATURE RECOMMENDATIONS: Avoid application to a hot surface in direct sunlight. Do not apply when the air, coating or surface temperature is below 50°F (10°C).

DRYING: CLEAR WOOD PRESERVATIVE will require 24 to 48 hours to dry under ideal conditions.

CLEANUP: Clean brushes and other tools with mineral spirits.

EXTRACTIVE BLEEDING: Some woods contain water-soluble colorings or extractives that tend to "bleed" to the surface. This bleeding may be unsightly but is not damaging to the finish. If it has occurred, allow the coating to dry, then wash with a mild detergent solution and rinse with clear water. For stubborn stains, a second solution of 50% alcohol and 50% water may be necessary.

STORAGE AND DISPOSAL: Securely wrap original container in several layers of newspaper and discard in trash. Do not reuse container. Rinse thoroughly before discarding in trash.

FOR ADDITIONAL INFORMATION - ASK YOUR DEALER OR REFER TO THE OLYMPIC INFORMATION MANUAL.

Label Date Code: (09292)