OCT 2 1 2004

PPG Industries, Inc. One PPG Place - 8 North Pittsburgh, PA 15272

Attention: Donna L. Butler

Regulatory Compliance Specialist

Subject: Clear Wood Preservative EPA Registration No. 7313-6

Your Notification Dated September 21, 2004

This will acknowledge receipt of your notification for the following additional brand name, submitted under the provisions of FIFRA Section 3(c)(9). Based on a review of the submitted material, the following comments apply.

### Additional Brand Name

"Weatherscreen Clear Wood Preservative"

The notification is in compliance with PR Notice 98-10 and is acceptable. This information has been added to your file.

If you have any questions concerning this letter, please contact Karen M. Leavy-Munk at (703) 308-6237.

Sincerely

Marshall Swindell

Product Manager (33)

Regulatory Management Branch 1 Antimorobials Division (7510C)

CONCURRENCES									
SYMBOL									
SURNAME					]	}			
DATE	.,	************							

235

	Form App	roved. OMB No.	2070-00	80. Approval expires 2-28-9			
SEPA Environmental Protect Washington, DC 20	tion Agency	Registra Amend  Other		OPP Identifier Number			
Applicat	tion for Pesticide - Sect	ion I					
1. Company/Product Number 7313-6	2. EPA Product Manager Swindell			3. Proposed Classification  None Restricted			
4. Company/Product (Name) Olympic Clear Wood Preservative	PM# 33	PM#					
5. Name and Address of Applicant (Include ZIP Code) PPG Industries, Inc. One PPG Place - 8 North Pittsburgh, PA 15272  Check if this is a new address	6. Expedited Reveiw. In accordance with FIFRA Section 3(c)(3) (b)(i), my product is similar or identical in composition and labeling to:  EPA Reg. No.  Product Name						
	Section - II	·					
Amendment - Explain below.  Resubmission in response to Agency letter dated  Notification - Explain below.  Explanation: Use additional page(s) if necessary. (For section Per PR Notice 98-10, this is a notification to EPA that PPG is additional Clear Wood Preservative, Reg. No. 7313-6. This notification is condition of the changes have been made to the labeling or the confident 1001 to willfully make any false statement to EPA. I further under 152.46, this product may be in violation of FIFRA and I may be su	Agency lette "Me Too" A  Other - Explaining the alternate brand name of Weather and the provisions of PR Notatial statement of formula of this products of that if this notification is not consistent with the provisions of PR Notification is not consistent with the provisions of PR Notification is not consistent with the provisions of PR Notification is not consistent with the provision with the p	pplication.  sin below.  sitherscreen Clear lotice 98-10 and Euct. I understand insistent with the trees.	Wood Pres PA regula that it is a erms of PF	tions at 40 CFR 152.46, and violation of 18 U.S.C. Sec. R Notice 98-10 and 40 CFR			
Material This Product Will Be Packaged In:	Section - III						
Child-Resistant Packaging  Yes  Yes  Yes	Water Soluble Packaging 2. Type of 6			Container Metal Plastic			
Certification must be submitted No No. per Unit Packaging wgt. No. per container	If "Yes" No. per Package wgt container	Glass Paper Other (Specify)					
Label Container  6. Manner in Which Label is Affixed to Product Litho	ograph Other	Other					
Stend	r glued ciled						
	Section - IV						
1. Contact Point   (Complete items directly below for identification)	ion of individual to be contacted, if	necessery, to pr	ocess this	application			
Name Donna L. Butler				hone No. (Include Area Code) 134-2887			
Certific			•	6. Date Application Reneived			
I certify that the statements I have made on this form and I acknowledge that any knowlinglly false or misleading stated both under applicable law.		or imprisonmen	t Cr	(Stamped)			
I certify that the statements I have made on this form and I acknowledge that any knowlinglly false or misleading st		or imprisonmen		(Stamped)			





### **PPG** Industries

PPG Industries, Inc. One PPG Place - 8 North Pittsburgh, PA 15272 USA

Donna L. Butler Regulatory Compliance Specialist Product Stewardship Environment, Health & Safety Phone: 1-412-434-2887 Fax: 1-412-434-2014 E-mail: dbutler@ppg.com

September 21, 2004

Document Processing Desk (NOTIF)
Office of Pesticide Programs (7504C)
U.S. Environmental Protection Agency
Room 266A, Crystal Mall #2
1801 South Bell Street
Arlington, VA 22202-4501

ATTN: Marshall Swindell, PM 33, AD

RE: EPA Reg. No. 7313-6, Clear Wood Preservative, Addition of Atternate Brand Name

Dear Mr. Swindell:

Per PR Notice 98-10, this is a notification to EPA that PPG is adding the alternate brand name of **Weatherscreen Clear Wood Preservative** under the Olympic Clear Wood Preservative, EPA Reg. No. 7313-6. Attached are a completed EPA Form 8570-1, Application for Pesticide Amendment, and a copy of the label for your review.

This notification is consistent with the provisions of PR Notice 98-10 and EPA regulations at 40 CFR 152.46, and no other changes have been made to the labeling or the confidential statement of formula of this product. I understand that it is a violation of 18 U.S.C. Sec. 1001 to willfully make any false statement to EPA. I further understand that if this notification is not consistent with the terms of PR Notice 98-10 and 40 CFR 152.46, this product may be in violation of FIFRA and I may be subject to enforcement action and penalties under sections 12 and 14 of FIFRA.

If you have any questions, please call.

Somal Butles

Very truly yours,

Donna L. Butler

Attachments

NATER SUPPLIED

## Protects Wood Beautifully

# WEATHERSCREEN

# Clear Wood Preservative

The 5-Way Wood Protector

- 1. Repels Water
- 2. Resists Sun Damage
- 3. Mildew Resistant
- 4. Penetrating Linseed Oil
- 5. Fights Rot & Decay

### LIMITED WARRANTY

PPG Architectural Finishes, Inc. warrants your satisfaction with the application, appearance and performance properties of this product if it is properly applied to a properly prepared surface in accordance with label directions. PPG ARCHITECTURAL FINISHES, INC. MAKES NO OTHER EXPRESS WARRANTIES. IN THE **EVENT THE PRODUCT FAILS TO CONFORM TO THIS** WARRANTY, PPG ARCHITECTURAL FINISHES. INC. AS ITS SOLE LIABILITY AND IN LIEU OF ANY DIRECT OR INDIRECT. INCIDENTAL, SPECIAL OR CONSE-QUENTIAL DAMAGES. WILL, AT YOUR OPTION, FURNISH REPLACEMENT PRODUCT OR REFUND THE PURCHASE PRICE — LABOR OR COSTS OF LABOR FOR THE APPLICATION OF ANY PRODUCT SPECIFI-CALLY ARE EXCLUDED. You must supply proof of purchase. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. To make a claim under this warrently contact the store where you purchased the product or: PPG Architectural Finishes, Inc., One PPG Place, Pittsburgh, PA 15272.





### PRECAUTIONARY STATEMENTS — HAZARDS TO HUMANS AND DOMESTIC ANIMALS WARNING!

Causes substantial, but temporary, eye injury. May cause an allergic skin reaction. Harmful if swallowed or inhaled. Do not get in eyes, on skin, or on cluthing. Avoid breathing dust or liquid aerosols. Wear gaggles or face shield when handling. Wash thoroughly with soap and water after handling. Remove contaminated clothing and separatel, launder clothing before reuse.

**ENVIRONMENTAL HAZARDS:** This pesticide is highly toxic to fish. For terrestrial uses, do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment washwaters.

PHYSICAL/CHEMICAL HAZARDS: Combustible. Keep away from heat, sparks or flame. Use with forced ventilation. Do not take internally, Close container after each use. Combustible materials contaminated with overspray or liquid residues of this product may undergo spontaneous combustion. To minimize the outential for spontaneous combustion, soak contaminated materials with water or place them in a closed metal container away from buildings and other combustible materials.

IMPORTANT: Spray equipment must be handled with due care and in accordance with manufacturer's recommendations. Spraying of any material can be hazardous. Wear respirator, eye protection, and protective clothing.

STATEMENT OF PRACTICAL TREATMENT

IF IN EYES: Flush eyes with plenty of water. Call a physician. IF SWALLOWED: Promptly drink a large quantity of milk, egg whites, gelatin solution, or, if these are not available, drink large quantities of water. Do not drink alcohol. Call a physician immediately. IF ON SKIN: Wash with plenty of soap and water. Get medical attention if irritation persists. IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention. For Emergency Medical and Spill Control Information. (412) 434-4515.



### WEATHERSCREEN"

### **Clear Wood Preservative**

Provides a clear finish to protect the natural beauty of your wood while allowing it to weather gray naturally.

Premium penetrating Linseed Oil and a wood preservative protects your wood from rot and decay.

#### DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling. Apply this product only as specified on this label. Wear gaggles or face shield when handling. Remove contaminated dathing and separately launder dothing before reuse. Wash thoroughly with soop and water after handling.

WEATHERSCREEN Clear Wood Preservotive is a penetrating linseed oil base, water repellent wood preservative. It gives wood protection from rat, decay, mildew, ultra violet light, and moisture damage. Recommended only for EXTERIOR above ground use, it also adds these protective qualities when used under finish coats, resulting in langer life for the wood and the linish. It may also be used on pressure treated wood to protect the wood from water damage, mildew and deterioration due to ultra violet sunlight. It exceeds the Federal specification for water repellency, TT-W-572B, poragraph 3.7.

WEATHERSCREEN Clear Wood Preservative is recommended on exterior bare wood surfaces which may be exposed to attack by wood rot, mildew or excess moisture. Use on structural lumber, beams, timbers, sills, millwork and roofs. To maintain wood preservation properties, reapplications are recommended every 2 to 4 years. When used prior to painting ar staining, allow to dry thoroughly at least 24 to 48 hours) before applying WEATHERSCREEN Stain. Applications of oil base top coals may result in a higher gloss in some areas which will normally become more uniform with weathering.

Surfaces treated with WEATHERSCREEN Clear Wood Preservative will be protected from maisture damage, mildew and rot, but will "weather" naturally. Depending on the exposure and the type of wood, this weathering will include a gradual graying. To protect and beautify with color, use one of WEATHERSCREEN Semi-Transparent or Solid Color Stains. For severe exposure to wood rot, "pressure treated wood" offers maximum protection.

### PREPARATION

SURFACE PREPARATION: Proper surface preparation is essential for PPG Architectural Finishes, Inc.'s limited warranty to apply. Surfaces must be dean, dry and free of mildew. Rime thoroughly and allow to dry before application.

MILDEW: Remove mildew by washing with a mixture of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly.

#### APPLICATION

Mix thoroughly prior to use. May be applied with a natural bristle brush, spray or by dipping. Use only one thin coat. Thoroughly treat ends and edges of boards. DO NOT THIN.

APPROXIMATE COVERAGE: Depending on texture, porosity and dryness of wood: 150 to 250 square feet (13.9 to 23.2 square meters) per gallon (3.78 liters).

TEMPERATURE RECOMMENDATIONS: Avoid application to a hot surface in direct sunlight. Do not apply when the air, coating or surface temperature is below 50°F (10°C).

DRYING: WEATHERSCREEN Clear Wood Preservative will require 24 to 48 hours to dry under ideal conditions.

CLEANUP: Clean brushes and other tools with mineral spirits. DANGER — RAGS, STEEL WOOL OR WASTE SOAKED WITH WEATHERSCREEN CLEAR WOOD PRESERVATIVE MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER. Place closed metal container away from buildings and other combustible materials.

**EXTRACTIVE BLEEDING:** Some woods contain water-soluble colorings or extractives that tend to "bleed" to the surface. This bleeding may be unsightly but is not damaging to the finish. If it has occurred, allow the coating to dry, then wash with a mild detergent solution and rinse with clear water. For stubbarn stains, a second solution of 50% alcohol and 50% water may be necessary.

STORAGE AND DISPOSAL: Securely wrop original container in several layers of newspaper and discard in trash. Do not reuse container. Rinse thoroughly before discarding in trash.

NOTICE: THIS PRODUCT CONTAINS (HEMICALIS) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND/OR BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

Calc, VOC = 548 g/L (4.57 lbs/gal).

5 95