

### STORAGE AND DISPOSAL

Do not reuse container. Securely wrap original container in several layers of newspaper and discard in trash.

### PROTECT PRODUCT FROM FREEZING

### PRECAUTIONARY STATEMENTS

### HAZARDS TO HUMANS AND DOMESTIC ANIMALS

### CAUTION

### STATEMENT OF PRACTICAL TREATMENT

Harmful if swallowed or absorbed through skin. Avoid contact with eyes, on skin or on clothing. Wash thoroughly after handling.

IF SWALLOWED, Do not induce vomiting. CALL PHYSICIAN IMMEDIATELY — IF ABSORBED THROUGH SKIN, Wash thoroughly with soap and water.—IF IN EYES, Flush with plenty of water and get immediate medical attention.—CONTAMINATED CLOTHING should be removed and washed thoroughly before reusing.

### ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on the label.

### PHYSICAL OR CHEMICAL HAZARDS

Use only with adequate ventilation: Close container after each use.



2634

**WOOD MAX**  
**MAXIMUM PROTECTION**

**CLEAR WOOD PRESERVATIVE**

**KEEP OUT OF REACH OF CHILDREN**  
**CAUTION**  
 SEE OTHER PRECAUTIONARY STATEMENTS ON SIDE PANEL

**ACTIVE INGREDIENT:**  
 Zinc naphthenate\* ..... 15.7%  
**INERT INGREDIENTS** ..... 84.3%  
**TOTAL** ..... 100.0%  
 \*(Equivalent to 2% Zinc Metal)  
 Product Weight Per Gallon 8.3 lbs.

**ACCEPTED**  
 MAR 5 1987  
 Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 7342-3

EPA Reg. No. 7342-3

EPA Est. No. 07342MD01

**NET CONTENTS 5 GALLONS**

**THE WARNER-GRAHAM CO.**  
 COCKEYSVILLE, MARYLAND 21030

7342-3

PM21 1061

### WATER REPELLANT PAINTABLE

WOOD MAX is a non-flammable preservative that protects wood against attack by termites, fungus, mold, mildew, rot and decay. Provides positive protection against dimensional change and warping. Can be painted over. For interior or exterior use. Can be applied to wet or green wood.

### USES

WOOD MAX is recommended for use on all wood and wood products such as mill-work, plywood, decks, shingles, siding, fencing, outdoor furniture, structural timbers, spars, docks, piers, posts and pilings. Can also be used on nursery lumber, slats and crates. Use as a first coat prior to painting or varnishing.

### DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Do not use on wood intended for food, feed, potable water, livestock or dairy animals contact surfaces. Stir before using. SURFACE PREPARATION: Surface to be treated should be clean and free of dirt, bark, wax, grease and mildew. Wood does not have to be dry.

APPLICATION: Apply by brush, roller, spray or dipping. Total immersion is best wherever possible. Wood in ground contact should be dipped for a minimum of 5 minutes. Large timbers, poles, etc. should be immersed in WOOD MAX for 12 to 48 hours. Where immersion is not possible a second coat is highly recommended. Side or end grains should be coated 2 or 3 times for full protection. Recoat within 1-2 hours. Allow WOOD MAX to dry 24-48 hours prior to painting or varnishing. Use WOOD MAX as it comes from the container. Appearance in the container is opaque but WOOD MAX dries to a clear flat finish. Do not use when temperature is below 40°F.

COVERAGE: 100 to 300 square feet depending on porosity of the wood and the method of application.

CLEAN-UP: Clean brushes and equipment with soapy water.