FRONT PANEL

file faclet

AQUA CHEMTM
Balanced for Clean Pools

STABILIZED CARTRIDGE

FOR LONG LASTING CHLORINATION TYPE "E"

FITS E-Z CHLOR(R) AND SUN AUTOMATIC CHLORINATORS

ACTIVE INGREDIENT:	Trichloro-S-Triazinetrione	99.0%

*Available Chlorine		

KEEP OUT OF REACH OF CHILDREN

DANGER: Highly Corrosive.
Read Additional Precautions and First Aid on Back Panel

NET WT. 4 LB.

STABILIZED CHLORINATOR

NOTE: Label Code, 60-L2520, 9/90

MOTIFICATION NOT REVIEWED 1990

5/29/90

0010

BACK PANEL (Column 1)

PRODUCT DESCRIPTION: Aqua ChemTM Stabilized Cartridge, Type "E" is an easy and economical way to regulate the chlorine that sanitizes your pool. A built-in stabilizer helps reduce chlorine loss from sunlight and other factors. When used as directed, the cartridge automatically releases the correct amount of chlorine in a constant flow. This reduces the growth of harmful algae and micro-organisms in your pool for several weeks. If used regularly, no additional stabilizer is needed. May be used as a refill for automatic chlorinating systems using the Type "E" refill cartridge.

IMPORTANT NOTES

1. Do not completely submerge cartridge or allow vent holes to become clogged. Chlorine gas may build up and could cause a violent explosion. 2. Do not attempt to open or refill this cartridge.

3. Superchlorination to eliminate harmful algae and micro-organisms should be done every 2-4 weeks or at least each time a chlorinating cartridge is replaced. For this purpose, use Aqua Chem Shock Treatment or Liquid Chlorinizor, following label directions. During superchlorination, remove chlorinating cartridge from pool. Place it back in pool when the process is completed.

DIRECTIONS FOR USE

It is a violation of federal law to use this product in any manner inconsistent with its labeling.

BEFORE YOU BEGIN

- Make sure all pool equipment is working properly, including pump, filter, skimmer and heater.
- 2. For use in automatic chlorinating systems, follow equipment manufacturer's directions for installation of the Type "E" cartridge.
- 3. For use as a floating chlorinator, start by making sure water has been treated with a stabilizer to retard chlorine loss. For water with unstabilized chlorine, add Aqua Chem Stabilizer once following label directions.

BACK PANEL (Column 1) (Cont.)

- 4. Check residual chlorine level with an Aqua Chem Test Kit.
 Desirable range is 1.0-1.5 parts per million of water (ppm). If
 necessary, add Aqua Chem Stabilized Granules or Aqua Chem Liquid
 Chlorinizor according to directions till water reaches desired
 level. Note: Use of the Floating Cartridge for this purpose
 will rapidly deplete contents. Use for maintenance of chlorine
 levels only.
- 5. Also check water pH (acidity/alkalinity balance) with an Aqua Chem Test Kit. Water pH should be 7.2-7.6. If not, adjust by adding Aqua Chem pH Decreaser to lower pH, or Aqua Chem pH Add to raise pH. Be sure to follow product directions.

NOW USE AQUA CHEM STABILIZED CARTRIDGE, TYPE "E"

1. Punch out numbered hole in cartridge corresponding to pool size as indicated below. Use a large nail, sharp knife or similar tool for this purpose. Place cartridge on a solid surface and work carefully to avoid injury.

Pool Ca	apa	aÇ.	it	y :	In	G	al	lo	ns													(Ope	en	He) 16)]	Nui	nbe	er:
10,000	•	•	•	•	•	•	٠	•	•	•	•	•	•	•	•	•	•	•	•	•	٠	•	•	•	•	•	•	•	•	. 1
20,000		•	•	•	•	٠	•			•	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•	•	•	. 2
30,000		•	•	•	•			•	•	•	•	•	•	•	•	•	•			•	•	•	•	•	•	•	•	•	•	. 3
40,000	•	•	•	•	•	•	•	•	•	•		٠	•	•	•	•	•		•	•	•	•	•	•	•	•	•	•	•	. 4
50,000	•	•			•	•	•		•		•	•	•	•	•	•	•	•		•	•	•	•	•	•			•	•	. 5
60,000	•	•			•		•		•			•	٠	•	•	•	•		•	•		•	٠	•	•	•		•		. 6

- For pools of intermediate size, open hole for next larger capacity. (Example: For 25,000 gallon pool, open hole number 3.) For pools larger than 60,000 gallons, use 2 (or more) cartridges and divide the number of holes to be opened equally among them. (Example: For 80,000 gallon pool, use 2 cartridges and open hole #4 on each.)
- 3. Place cartridge (or cartridges) in center of the pool and wait for 24 hours. Then check chlorine level with Aqua Chem Test Kit. Correct range should be 1.0-1.5 ppm. If residual level is above 1.5 ppm, wait 24 hours and recheck. Do not use pool until residual level is below 3.0 ppm.

If you are unsure of the pool capacity, use the following chart to calculate volume.

HOW TO CALCULATE POOL CAPACITY

Shape of pool	Gallons of water
Rectangular	Average depth x average léngth
	x average width x 7.5
Circular	Diameter x diameter x average
	depth x 5.9
Oval with straight sides	Full width x full length x
-	average depth x 6.7
Irregular	Consult pool builder



PRECAUTIONARY STATEMENT: HAZARDS TO HUMAN AND DOMESTIC ANIMALS DANGER: Highly corrosive. Causes skin and eye damage. May be fatal if swallowed. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Irritating to nose and throat. Avoid breathing dust. Remove and wash contaminated clothing before reuse.

STATEMENT OF PRACTICAL TREATMENT (FIRST AID): IF SWALLOWED: Feed victim bread soaked in milk, followed by olive oil and cooking oil. Call a physician immediately. IF ON SKIN: Brush off excess chemical and flush skin with water for at least 15 minutes. If irritation persists, get medical attention. IF IN EYES: Flush with cold water for at least 15 minutes. Get medical attention. NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

IN THE EVENT OF A MEDICAL EMERGENCY CALL COLLECT: 1-303-623-5716

ENVIRONMENTAL HAZARDS: This product is toxic to fish. Do not discharge into lakes, streams, ponds, or public waters unless in accordance with an NPDES Permit. For guidance, contact the regional office of EPA.

PHYSICAL AND CHEMICAL HAZARDS/STRONG OXIDIZING AGENT: Mix this product with water only. Use only clean, dry utensils. Do not completely submerge cartridge or allow holes to become clogged. If either occurs, chlorine gas may become trapped and cause a violent explosion. Do not attempt to open or refill this cartridge. Contamination of cartridge contents with moisture, organic matter or other chemicals may start a chemical reaction, generating heat, liberating hazardous gases, and possibly causing fire or explosion. If cartridge becomes contaminated or product becomes decomposed, do not reseal. Isolate container outdoors. Flood cartridge with large volumes of water, and keep animals and humans away from water flow path.

STORAGE AND DISPOSAL: Keep this product in tightly closed original container, when not in use. Store in a locked, cool, dry, well-ventilated area way from heat or open flame. In case of decomposition, isolate container (if possible) and flood area with large amounts of water to dissolve all materials before discarding this container. Do not reuse empty container but place in trash collection. Do not contaminate food or feed by storage, or disposal, or cleaning of equipment.

If you have any questions or comments about Aqua Chem Products or their use, please call us toll free. In the continental U.S. Call 1-800-252-POOL. Ask for your free pool care booklet.

EPA REG NO 7368-70 EPA EST NO 7368-CA-1

(UPC CODE)

(C) 1987 GROW GROUP, INC. ALL RIGHTS RESERVED (LABEL CODE) AQUA CHEM IS A TRADEMARK OF GROW GROUP, INC.

Grow Group, Inc. 2501 Malt Avenue City of Commerce, CA 90040