

JAN 11 1988

Jasco Chemical Corporation
P. O. Drawer J
Mountain View, CA 94042

Dear Mr. Thomas:

Subject: Jasco Termin-8-Wood Preservative Green
Jasco Termin-8-Wood Preservative Black
EPA Registration No. 7424-1
Your submissions dated August 16 and September 21, 1988

The labeling and other information you submitted in connection with the subject pesticide registration under the Federal Insecticide, Fungicide, and Rodenticide Act, is acceptable provided you make the following label change(s).

1. Expand the "First Aid" section of the label to include appropriate first aid instructions in the event of skin and inhalation exposures.
2. Under the "Environmental Hazards" heading, revise the water contamination statement (last sentence) to read as follows: "Do not contaminate water when disposing of equipment washwaters."

Stamped copies of each label are enclosed for your record. Submit five(5) copies of each final printed label.

Enclosure

Sincerely yours,

for Lois A. Rossi ^{LR}
Product Manager (21)
Fungicide-Herbicide Branch
Registration Division (TS-767C)

2 of 3

ACCEPTED
WITH COMMENTS
in EPA Letter Dated:

01/11/89

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
as amended, for the pesticide
registered under EPA Reg. No.

7424-1

- USES:**
- BOATS/DOCKS
 - DOORS
 - WINDOWS
 - FRAMES
 - SHINGLES
 - SHAKES
 - STAIRS
 - SILLS
 - PORCHES
 - FENCES
 - POSTS
 - FLOORING
 - PATIO FURNITURE
 - PLYWOOD
 - PRESSURE-TREATED WOOD

JASCO

TERMIN-8

WOOD PRESERVATIVE

GREEN

Seals Wood

Repels Water

ACTIVE INGREDIENTS:	
COPPER NAPHTHENATE (Equivalent to metallic copper 2%)	25.00%
INERT INGREDIENT	75.00%
TOTAL	100.00%

KILLS TERMITES & WOOD EATING INSECTS **PREVENTS ROT FUNGI AND MOLD**

CONTROLS WARPING AND SWELLING

USE ABOVE OR BELOW GROUND

1 GALLON 3.78 LITERS

EPA REG NO 7424-1 EPA EST 7424 CA 1

KEEP OUT OF REACH OF CHILDREN

WARNING

See precautions on back panel

WARRANTY: Our only obligation shall be to replace or pay for any material proved defective. Beyond the purchase price of materials supplied by us, we assume no liability for damages of any kind including consequential and the user accepts the product "as is" and without warranties, express or implied. The suitability of the product for an intended use shall be solely up to the user. For specialized applications, consult your local representative.

PRECAUTIONS/HUMAN

WARNING! Harmful if swallowed, inhaled, or absorbed. Do not take internally. Use only in well-ventilated areas. Avoid breathing dust or fumes. Wash thoroughly after handling, and clothes separately. IF IN EYES, flush with water for 15 minutes. IF ON SKIN, wash with soap and water. IF ON CLOTHING, remove and wash separately. IF ON FLOOR, sweep up and dispose of in a water-filled container.

It is in violation of Federal labeling.

Paint, varnish, wax or Termin-8. All around evidence of decay to control must be normally dry. ABOVE-GROUND WOOD is not possible, apply 2 or 3 coats. BELOW-GROUND WOOD ground level; if not possible, apply 2 or 3 coats. PRESSURE-TREATED WOOD sanding or boring process. COVERAGE: 100 - 300 sq ft per gallon. PRIMER: Ideal as an undercoat or other coating on light-colored paints. CLEAN-UP: Use paint thinner.

STORAGE AND DISPOSAL: Store at temperature above 40°F or is leaking, remove from service, then pick up and dispose of in a water-filled container. Do not reuse empty paper and discard in a water-filled container.

NON-PH

JASCO
MOUNTAIN VIEW



303

ACCEPTED
with COMMENTS
in EPA Letter Dated:

01/11/89

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
as amended, for the pesticide
registered under EPA Reg. No.
74-24-1

- USES:**
- BOATS/DOCKS
 - DOORS
 - WINDOWS
 - FRAMES
 - SHINGLES
 - SHAKES
 - STAIRS
 - SILLS
 - PORCHES
 - FENCES
 - POSTS
 - FLOORING
 - PATIO FURNITURE
 - PLYWOOD
 - PRESSURE-TREATED WOOD

JASCO

TERMIN-8

WOOD PRESERVATIVE

BLACK

Seals
Wood

Repels
Water

ACTIVE INGREDIENTS:

COPPER NAPHTHENATE (Equivalent to metallic copper 2%)	25.00%
INERT INGREDIENT	75.00%
TOTAL	100.00%

KILLS TERMITES & WOOD EATING INSECTS

PREVENTS ROT FUNGI AND MOLD

CONTROLS WARPING AND SWELLING

USE ABOVE OR BELOW GROUND

1 GALLON 3.78 LITERS

EPA REG NO 7424.1 EPA EST 7424.CA.1

KEEP OUT OF REACH OF CHILDREN

WARNING

See precautions on back panel

WARRANTY: Our only obligation shall be to replace or pay for any material proved defective. Beyond the purchase price of materials supplied by us, we assume no liability for damages of any kind including consequential and the user accepts the product "as is" and without warranties, express or implied. The suitability of the product for an intended use shall be solely up to the user. For specialized applications, consult your local representative.

JASCO TERMIN-8

PRECAUTIONARY STATEMENTS & HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING: Harmful if swallowed. Causes eye and skin irritation. Avoid contact with skin, eyes and clothing. Do not take internally. Avoid risk of vapors or spray mist. Use only in well-ventilated areas. Wash thoroughly with soap and water after handling, and clothes before re-use. Close container after each use.

FIRST AID — IF SWALLOWED: do not induce vomiting. Call physician immediately. **IF IN EYES:** flush with plenty of water, if irritation persists, get medical attention.

ENVIRONMENTAL HAZARDS — This product is toxic to fish. Do not apply directly to water or wetlands. Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL AND CHEMICAL HAZARDS — COMBUSTIBLE! Do not store near heat or open flame. To avoid spontaneous combustion, discard oily rags in a water-filled container.

DIRECTIONS FOR USE

It is in violation of Federal law to use this product in a manner inconsistent with its labeling.

DIP - SPRAY - BRUSH - ROLL

Paint, varnish, wax or other films and all bark must be removed before applying Termin-8. All unbound wood should be removed at least 2 feet beyond any visible evidence of decay to control termites, carpenter ants and powder-post beetles. Wood must be normally dry.

ABOVE-GROUND WOOD: Soak wood for at least 3 minutes for best results. If this is not possible, apply 2 coats by brush, roller or low-pressure spray. Cover all surfaces.

BELOW-GROUND WOOD: Soak wood for 12 to 24 hours covering 6 inches above ground level; if not possible, apply 2 heavy coats within 10 minutes of each other.

PRESSURE-TREATED WOOD: Apply a generous coat to exposed surfaces from cutting, sanding or boring pressure-treated wood.

COVERAGE: 100 - 300 square feet, depending on the porosity and surface roughness. 7 gallons per 1000 board feet for open-tank treatment.

PRIMER: Ideal as an undercoating. Allow 24 hrs. drying time before finishing with paint or other coating material. Termin-8 may show through the first coat of some light-colored paints.

CLEAN-UP: Use paint thinner or mineral spirits.

STORAGE AND DISPOSAL

Store at temperature between 40°F and 100°F. If the product has been spilled or is leaking, remove source of spill or leak. Recover free liquid. Spread absorbent, then pick up and place in containers. Where applicable, wash area with detergent and water. Store product only in the original container. Keep container closed when not in use.

Do not reuse empty container. Securely wrap original in several layers of newspaper and discard in the trash.

NON-PHOTOCHEMICALLY REACTIVE V.O.C. 368 g/L

JASCO CHEMICAL CORP.
MOUNTAIN VIEW, CA 94042 SANTA ANA, CA 92703