

DIRECTIONS

All wood to be treated should be dry, clean, free from previous finishes and the framing or cutting completed before applying ZPW. All unsound wood should be removed at least 2 feet beyond any visible evidence of decay. Best results can be obtained by soaking the wood for five minutes per inch of wood thickness. When this is not possible at least 2 coats should be applied by brush or low pressure flood spray. The second coat must be applied before the first coat is dry, and all surfaces should be covered with particular attention paid to side and end grains. Fence posts, poles, four timbers and wooden members should be free of dirt, dry and well seasoned. The portion to be buried should be soaked 48 hours to be an effective wood preservative against decay — 24 hours for wood in contact with soil. Avoid spray drift. Fish nets, rope, canvas, burlap or twine should be dipped in ZPW to thoroughly saturate the fibers.

SEMI-TRANSPARENT STAINS: This product can be mixed with up to 6 ozs. of universal tinting color to one gallon ZPW which will produce a water repellent wood preservative semi-transparent stain.

COVERAGE: Approximately seven gallons per 1000 board feet for open tank treatment depending on wood hardness. Approximately 150 square feet per gallon by brush or spray. Wood must be odor-free and dried 24-48 hours before paint can be applied.

CLEAN-UP: Use warm soapy water for brushes, spray equipment, etc. Do not contaminate water when disposing of equipment wash-water.

**Buyer assumes all risks of use, handling or storage when such use, handling or storage is not in strict accordance with label.

THIS PRODUCT CONTAINS A MAXIMUM OF 260 µL V.O.C.

JASCO CHEMICAL CORP.
MOUNTAIN VIEW, CA 94042 • SANTA ANA, CA 92701

JASCO®

ZPW

WOOD

PRESERVATIVE

0931

INTERIOR
EXTERIOR

ABOVE OR
BELOW GROUND

CLEAR • TINTABLE • PAINTABLE • WATER REPELLENT

PROTECTS AGAINST ROT, TERMITES, WARPING, SWELLING

1 GALLON 3.785 LITERS

ACTIVE INGREDIENTS:
Zinc Naphthenate 15.75%
Inert Ingredients 84.25%
100.00%

*Equivalent to 2% as Zinc Metal

EPA REG. NO. 7424-9
EPA EST. 7424-CA-2

WARNING! KEEP OUT OF REACH OF CHILDREN
See Additional Precautions And
First Aid Statement On Back Panel.

BEST AVAILABLE COPY

JASCO ZPW
Colorless but Tintable
WOOD PRESERVATIVE
Protects paint from moisture. Ideal as an undercoating.
Stops wood rot fungi and mold.
Kills Termites Carpenter Ants Wood Boring Beetles.
WATER REPELLENT
Protects wood from warping, swelling, shrinking,
grain raising and checking.
FOR INTERIOR AND EXTERIOR USE
Decks, doors, windows & frames, shingles, siding,
fences, sill, stairs, porches, structural lumber, roofs
(net composition)

CONTAINS ZINC NAPHTHENATE

WARNING! May be harmful or fatal if swallowed or absorbed through skin. Causes skin irritation. Do not get in eyes, on skin or on clothing. Do not breathe vapor or spray mist. Use only with adequate ventilation. Wear protective clothing and rubber gloves when handling freshly treated lumber. Wash thoroughly after handling. Avoid contamination of food or feedstuffs. Not harmful to animals or plant life except African Violets. Use good ventilation.

FIRST AID: If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY! Avoid alcohol. Never give anything by mouth to an unconscious person.

In case of contact, wash skin with soap and water. For eyes, flush with water for at least 15 minutes and get medical attention. Remove and wash contaminated clothing before re-use.

ENVIRONMENTAL HAZARDS: This product is toxic to fish. Keep out of any body of water. Do not contaminate water when disposing of equipment washwaters. Apply this product only as specified on this label. Open dumping is prohibited.

DISPOSAL: Do not re-use empty container. Wrap container and put in trash collection.

ACCEPTED
APR 11 1989
Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
registered under
EPA Reg. No. 7424-9