

JASCO®

EXTERIOR
ONLY

ZPW

ABOVE OR
BELOW GROUND

CLEAR WOOD PRESERVATIVE


0931

ACTIVE INGREDIENTS:
Naphthenate 15.75%
Ingredients 84.25%
100.00%

Equivalent to 2% as Zinc Metal

TINTABLE - PAINTABLE - WATER REPELLENT
PROTECTS AGAINST ROT, TERMITES, WARPING, SWELLING

1 GALLON - 3.785 LITERS



EPA REG. NO. 7424-9
EPA EST. 7424-CA-2

WARNING! KEEP OUT OF REACH OF CHILDREN
See Additional Precautions And
First Aid Statement On Back Panel.

ACCEPTED
DEC 23 1998
Under the Federal Insecticide, Fungicide, and
Rodenticide Act as amended, for the
pesticide, registered under
EPA Reg. No. 7424-9

7424-9

12/23/1998

12

JASCO ZPW
Colorless but Tintable

WOOD PRESERVATIVE

Protects paint from moisture Ideal as an undercoating
Stops wood rot fungi and mildew
Kills Termites Carpenter Ants Wood Boring Beetles

WATER REPELLENT

Protects wood from warping, swelling, shrinking,
grain raising and checking

FOR EXTERIOR USE ONLY

Decks, doors, windows & frames, shingles, siding, fences, sills
stairs, porches, structural lumber, roofs (not composition)

WARNING- Causes substantial burt temporary eye injury. Harmful or fatal if swallowed or absorbed through the skin. Do not get in eyes, on skin or on clothing. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse. Avoid breathing spray mists or vapors. Wear goggles or face shield and rubber gloves when handling ZPW. DO NOT breathe vapors during brush, roll, spray and dip applications. Wear a NIOSH/MSHA approved respirator for continued use of this product or for frequent use of this product. In case of questions, emergencies or accidents involving this product, call Chemtrec at 1-800-424-9300. Application of this product may produce strong, lingering, unpleasant odor. **FIRST AID-STATEMENT OF PRACTICAL TREATMENT**
IF IN EYES Immediately flush with large quantity of water and get medical treatment. **IF ON SKIN** Flush with water. Remove and wash contaminated clothing before reuse. **IF SWALLOWED** Do not induce vomiting. **CALL A DOCTOR.**

ENVIRONMENTAL HAZARDS- This product is toxic to fish. Do not apply directly to water or the areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water by cleaning of equipment or disposal of wastes. **PHYSICAL AND CHEMICAL HAZARDS-** Do not use or store near heat or open flame. Close container after each use.

STORAGE AND DISPOSAL-PROHIBITIONS Do not contaminate water, food or feed by storage or disposal. **PESTICIDE DISPOSAL** Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility. **CONTAINER DISPOSAL** US Quart/1 Gallon Containers. Do not reuse empty container. Securely wrap original container in several layers of newspaper and discard in trash. **GENERAL** Consult Federal, State or local disposal authorities for approved alternative procedures.

DIRECTIONS

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

All wood to be treated should be dry, clean, free from previous finishes and the framing or cutting completed before applying JASCO ZPW. All unsound wood should be removed at least 2 feet beyond any visible evidence of decay. Best results can be obtained by soaking the wood for five minutes per inch of wood thickness. When this is not possible at least 2 coats should be applied by brush or low-pressure flood spray. The second coat must be applied before the first coat is dry, and all surfaces should be covered with particular attention paid to side and end grains. Fence posts, poles, foundation timbers and heavy wooden members should be free of bark, dry and well-seasoned. The portion to be buried should be soaked 48 hours to be an effective wood preservative against decay — 24 hours for wood in contact with soil. Avoid spray drift. Fish nets, rope, canvas, burlap or twine should be dipped in JASCO ZPW to thoroughly saturate the fibers.

SEMI-TRANSPARENT STAINS: This product can be mixed with up to 6 ozs. of universal tinting color to one gallon ZPW which will produce a water repellent wood preservative semi-transparent stain.

COVERAGE: Approximately seven gallons per 1000 board feet for open tank treatment depending on wood hardness. Approximately 150 square feet per gallon by brush or spray. Wood must be odor-free and dried 24-48 hours before paint can be applied.

CLEANUP: Use warm soapy water for brushes, spray equipment, etc. Do not contaminate water when disposing of equipment wash-water.

Buyer assumes all risks of use, handling or storage when such use, handling or storage is not in strict accordance with label.

THIS PRODUCT CONTAINS A MAXIMUM OF 260 g/L V.O.C.

ACCEPTED

DEC 23 1998

Under the Federal Insecticide, Fungicide, and
Rodenticide Act as amended, for the
pesticide, registered under
EPA Reg. No. 17424-9

JASCO CHEMICAL CORP.

MOUNTAIN VIEW, CA 94042 • SANTA ANA, CA 92701

2/2