



**A COPPER SHIELD  
AGAINST TERMITES!**

207-3

# JASCO Copper-Tek 6

## WATER REDUCIBLE

**Stains Green or Paint Over It!**

JASCO Copper-Tek 6 conforms to FEDERAL SPECIFICATION TT-W-572, Type II, Composition "C" when reduced.

### SEALS AND PRESERVES WOOD

Stops rot • Kills termites and wood eating insects

### WATER REPELLENT

Protects wood from warping, swelling, shrinking, grain raising and checking.

### PRIMER

Ideal as an undercoating. Protects wood surfaces from mildew growth. Harmless to plants and humans when dry. May be used in green houses or flower boxes. Allow a minimum of twenty-four hours drying time before finishing with paint or other coating material. Copper-Tek 6 may show through the first coat of some light paints.

### DIRECTIONS

#### Dip - Brush - Spray

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

No protective clothing is necessary unless the user is allergic to Petroleum Distillates. Mix 1 gallon Copper-Tek 6 with 2 gallons water to give 2% metallic copper. Apply to wood that is bare and free from paint, varnish, wax, bark or other films.

Best results can be obtained by soaking the wood for at least three minutes, per inch thickness, but when this is not possible at least 2 coats should be applied by either brush or spray. All surfaces should be covered with particular attention paid to end grain and joints.

For fence posts and other wood to be used in contact with the ground, if possible, apply by soaking for 12-48 hours, covering four to six inches above ground contact; if not, two heavy brush coats within 10 minutes of each other are recommended. The wood must be clean and dry before treatment. After treatment, allow the wood to dry completely before allowing contact with the ground.

All newly exposed surfaces resulting from cutting, sanding or boring of treated wood should be treated by applying one generous coat of Copper-Tek 6 and water mixture.

**COVERAGE:** Approximately seven gallons per 1,000 board feet for open tank treatment depending on wood hardness; approximately 150 to 200 square feet per gallon by spray or brush.

**CLEAN UP:** Use warm soapy water for brushes, spray equipment, etc.

### WARRANTY STATEMENT

\*\* Buyer assumes all risks of use, handling or storage when such use, handling or storage is not in strict accordance with label

**KEEP OUT OF THE REACH OF CHILDREN**

**1 GALLON 3.78 Liters**

**JASCO CHEMICAL CORP.**  
MOUNTAIN VIEW, CALIFORNIA 94042

# JASCO Copper-Tek 6

## WATER REDUCIBLE

Stains Green or Paint Over It!

JASCO Copper-Tek 6 conforms to FEDERAL SPECIFICATION TT-W-572, Type II Composition "C" when reduced.

### SEALS AND PRESERVES WOOD

Stops rot • Kills termites and wood eating insects

### WATER REPELLENT

Protects wood from warping, swelling, shrinking, grain raising and checking

### PRIMER

Ideal as an undercoating. Protects wood surfaces from mildew growth. Harmless to plants and humans when dry. May be used in green houses or flower boxes. Allow a minimum of twenty-four hours drying time before finishing with paint or other coating material. Copper-Tek 6 may show through the first coat of some light paints.

### DIRECTIONS

#### Dip - Brush - Spray

It is a violation of Federal law to use this product in a manner inconsistent with its labeling

For protective clothing is necessary unless the user is allergic to Petroleum Distillates. Mix 1 gallon Copper-Tek 6 with 2 gallons water to give 2% metallic copper. Apply to wood that is bare and free from paint, varnish, wax, mark or other films.

Best results can be obtained by soaking the wood for at least three minutes, per inch thickness, but when this is not possible at least 2 coats should be applied by either brush or spray. All surfaces should be covered with particular attention paid to end grain and joints.

For fence posts and other wood to be used in contact with the ground, if possible, apply by soaking for 12-48 hours, covering four to six inches above ground contact; if not, two heavy brush coats within 10 minutes of each other are recommended. The wood must be clean and dry before treatment. After treatment, allow the wood to dry completely before allowing contact with the ground.

On newly exposed surfaces resulting from cutting, sanding or boring of painted wood should be treated by applying one generous coat of Copper-Tek 6 and water mixture.

**COVERAGE:** Approximately seven gallons per 1,000 board feet for open end treatment depending on wood hardness; approximately 150 to 200 square feet per gallon by spray or brush.

**LEAN UP:** Use warm soapy water for brushes, spray equipment, etc

### WARRANTY STATEMENT

\* Buyer assumes all risks of use, handling or storage when such use, handling or storage is not in strict accordance with label.

**KEEP OUT OF THE REACH OF CHILDREN**

1 GALLON 3.78 Liters

# JASCO

## Copper-Tek 6

## WOOD

## PRESERVATIVE

Protects paint from moisture. Ideal as an undercoating. Stops wood rot fungi and mildew. Kills Termites.

### WATER REPELLENT

Protects wood from warping, swelling, shrinking, grain raising and checking.

### FOR INTERIOR OR EXTERIOR USE

Decks, doors, windows & frames, shingles, siding, fences, sills, stairs, porches, structural lumber, roofs (not composition), green houses. "Note: The treatment of interior use wood for control of wood rot fungi is only necessary for wood which is subject of frequent and/or prolonged wetting (e.g., condensation, rain seepage)."

### PRECAUTIONARY STATEMENTS

Hazards to Humans and Domestic Animals.  
**WARNING!** May be harmful or fatal if swallowed, inhaled or absorbed through skin. Causes skin irritation. Do not get in eyes, on skin, or on clothing. Do not breathe vapor or spray mist. Wear protective clothing and rubber gloves when handling freshly treated lumber. Wash thoroughly after handling. Avoid contamination of feed or foodstuffs.

**FIRST AID:** If swallowed, do not induce vomiting. CALL PHYSICIAN, IMMEDIATELY! Avoid alcohol. Never give anything by mouth to an unconscious person.

In case of contact, wash skin with soap and water. For eyes, flush with water for at least 15 minutes and get medical attention. Remove and wash contaminated clothing before reuse.

**ENVIRONMENTAL HAZARDS:** This product is toxic to fish. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label. Keep container closed when not in use. Open dumping is prohibited.

### PHYSICAL AND CHEMICAL HAZARDS

**COMBUSTIBLE:** Contains Petroleum Distillates. Keep away from heat, sparks or open flame. Use with adequate ventilation.

### STORAGE AND DISPOSAL

Do not re-use empty container. Wrap container and put in trash collection.

# JASCO CHEMICAL CORP.

MOUNTAIN VIEW, CALIFORNIA 94042