

BLACK JACK

5% PENTA — WATER REPELLANT

WOOD PRESERVING COMPOUND

USDA Registration No. 7500-1

APPROVED
FEB 2, 1970
7500-1
FEDERAL REGISTER
PUBLISHED WEEKLY
U.S. GOVERNMENT PRINTING OFFICE

7500-1
Comments

ACCEPTED WITH COMMENTS

BLACK JACK

PENTA WATER REPELLANT

WOOD PRESERVING COMPOUND

USDA Registration No. 7500-1

Active Ingredients	84%
Pentachlorophenol	4.4%
Other Chlorophenols	0.6%
Mineral Spirits	79.0%
Inert Ingredients	16%

WARNING

Harmful if swallowed or absorbed through skin! Causes skin irritation! Do not breathe vapor or spray mist. Do not get in eyes, on skin or on clothing. Wash thoroughly with soap and warm water after handling. KEEP AWAY FROM CHILDREN. Keep away from heat and open flame. Keep container closed when not in use.

DESCRIPTION

This solution is effective for preventing the destruction of wood due to mold, fungi, or insects. Protects wood against swelling, warping and checking due to rapid change in moisture content. When properly applied, the wood retains a natural appearance with a minimum of discoloration. Especially designed for treating mill work, doors, window-frames and similar construction. May be painted over but need not be.

DIRECTIONS

Shake well or stir contents before using. Apply two or more brush coats or dip a minimum of three minutes all wood that is to be in contact with the soil. Wood to be treated must be dry, free from bark and clean. Will penetrate best at temperatures over 70° F. If wood is cut after applying this preservative, the fresh cut surface should be treated for maximum protection. Permit treated material to dry at least one hour before handling or painting.

Distributed by **HANDI PRODUCTS COMPANY**— P.O. Box 1955, Cleveland, Ohio 44105

Net Contents:

BLACK JACK

FORMULA 454

CREOSOTE WOOD PRESERVER

USDA Registration No. 7500-2

ACCEPTED

May 28, 1971

7500-2

Comment

ACCEPTED WITH COMMENTS