

BLACK JACK

FORMULA 454

CREOSOTE WOOD PRESERVER

USDA Registration No. 79004-2

NET CONTENTS

Active Ingredient

100%

ONE U.S. GALLON

AWPA #1 Creosote Oil 100%

DESCRIPTION

This Wood Preserver is AWPA #1 Creosote Oil. Use it full strength, or for applications that are not severe, may be thinned up to 50% with fuel oil or kerosene. This Wood Preserver is particularly well suited for fence posts, bridge timbers, foundation timbers, pilings and other similar surfaces that are not to be painted over. Surfaces treated with this Wood Preserver are protected against fungi, termites, other wood destroying pests, and rot.

WARNING - KEEP OUT OF REACH OF CHILDREN

MAY BE FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN.

Avoid contact with the skin. Wash thoroughly after handling. Avoid prolonged breathing of the vapor. Keep away from heat and open flame. Keep container closed when not in use.

DIRECTIONS

Shake or stir to mix contents before using. If there are crystals in the bottom of the container, bring to room temperature and stir. Crystals will redissolve. Posts and timbers to be treated must be free of bark, clean and dry. Heavy timbers should be soaked 24 to 48 hours, for best results. Posts should be soaked for 12 to 24 hours, depending on seasoning of wood. If applied with a paint brush, apply at least two flood coats. This Wood Preserver dries in about 24 hours.

BJ-5893-20-F

Distributed by HANDI PRODUCTS COMPANY — P.O. Box 1955, Cleveland, Ohio 44106

Printed in U.S.A.

DESCRIPTION

This Wood Preserving Compound combines Copper Naphthenate, which is toxic to nearly all known decay-causing fungi, with Pentachlorophenol which is toxic to fungi not affected by Copper Naphthenate. This compound does not crystalize on the surface of the wood. It will not leach out; it forms an insoluble soap which acts as a water repellent. Protects against termites. Gives reliable protection to woods, cordage and fabric. It is toxic to plants, shrubs and grasses.

DIRECTIONS

Shake well or stir thoroughly to mix contents before using. Apply two or more liberal brush coats or dip for a minimum of three minutes on all wood which is to be in contact with the soil. Fence posts, poles, foundation timbers and heavy wooden members should be free of bark, dry and well-seasoned and immersed in the product for a period of 12 to 48 hours to be an effective wood preserver. Best penetration into the material to be treated is obtained at temperatures above 70°F. and by dipping. Permit treated material to dry at least one hour before handling, and permit to dry at least 72 hours before painting. Fabrics or cordage unroll and apply sufficient compound to wet through — by dipping, time varies with material — by brush or spray flood compound onto surface.

BJ-5875-20-W

BLACK JACK

COPPER NAPHTHENATE (with Pentachlorophenol)

WOOD PRESERVING COMPOUND

EPA Reg. No. 7500-3

WARNING

Harmful if swallowed or absorbed through skin! Causes skin irritation! Do not breathe vapor or spray mist. Do not get in eyes, on skin or clothing. Wash thoroughly with soap and warm water after handling. KEEP AWAY FROM CHILDREN. Keep away from heat and open flame. Keep container closed when not in use.

Wear protective clothing and rubber gloves when handling the freshly treated lumber.

ED

PESTICIDE
ACT
REGISTER

This product is toxic to fish and wildlife. Keep out of lakes, streams, or ponds. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

Do not reuse empty container. Destroy it by perforating or crushing. Bury or discard in a safe place away from water supplies. Drums may be reconditioned by drum supplier.