

## DIRECTIONS

Use HANDI-COPP just as it is and DO NOT thin for any type of application. Shake well or stir thoroughly before using.

On wood, all previous paint and rotted wood should be removed and the surface cleaned of loose particles and rust. Make brush applications as liberal as necessary to obtain good penetration. Two liberal coats are ~~recommended~~ *recommended* on wood that is to contact the ground. For dip treatment, soaking time depends on type of wood and its thickness. Approximately 30 minutes soaking is recommended for wood not more than 1" thick. For heavy timbers overnight soaking is recommended.

Fabrics and cordage unroll and apply sufficient compound to wet through — by dipping, time varies with material -- by brush or spray flood compound onto surface.

## IMPORTANT

If the surface treated with HANDI-COPP is to be painted over, allow at least 48 hours for drying before applying top coats. There might be a slight discoloration on the first coat where white and light tints are used but this will disappear after the second coat is applied, provided the wood is thoroughly seasoned and dry.

HANDI-PRODUCTS CO.  
P. O. Box 1955  
Cleveland 6, Ohio

Excellent Preventative for  
**TERMITES - WOOD ROT**  
Also used on canvas and rope

Harmful If Taken Internally

**CAUTION!**

**KEEP OUT OF REACH OF CHILDREN**

*A Quality Product*  
*of the*  
**handi-family**

ANALYSIS  
Active Ingredients:  
Copper Napthenate ..... 12.5%  
Petroleum Distillate ..... 87.5%  
(Copper as metal 1%) 100%

## WARNING

Harmful if swallowed or absorbed through skin! Causes skin irritation! Do not breathe vapor or spray mist. Do not get in eyes, on skin, or on clothing. Wash thoroughly with soap and warm water after handling. **KEEP AWAY FROM CHILDREN.** Keep away from heat and open flame. Keep container closed when not in use.

## GIVES LASTING PROTECTION

On wood, Canvas and Rope, with excellent penetration. This Preservative is of Copper-Base and will check decay, fungi, rotting, termites and similar wood infesting insects. Has a light green color that is not permanent. Apply by brush, spray or dip treatment.

Coverage is from 250 to 450 square feet per gallon, depending upon the condition and type of surface on which it is applied.

## EXCELLENT FOR WATER PROOFING

Affords protection against mold, and rot, on unpainted surfaces as well as exteriors which are to be painted over. An added protection below water line before using copper paint.

U. S. Standard  
ONE GALLON

## DIRECTIONS

Use HANDE-COPP just as it is and DO NOT thin for any type of application. Shake well or stir thoroughly before using.

On wood, all previous paint and rotted wood should be removed and the surface cleaned of loose particles and rust. Make brush applications as liberal as necessary to obtain good penetration. Two liberal coats are ~~preferable~~ **particulate** on wood that is to contact the ground. For dip treatment soaking time depends on type of wood and its thickness. Approximately 30 minutes soaking is recommended for wood not more than 1" thick. For heavy timbers overnight soaking is recommended.

Fabrics and cordage unroll and apply sufficient compound to wet through — by dipping, time varies with material — by brush or spray flood compound onto surface.

## IMPORTANT

If the surface treated with HANDE-COPP is to be painted over allow at least 48 hours for drying before applying top coats. There might be a slight discoloration on the first coat where white and light tints are used but this will disappear after the second coat is applied provided the wood is thoroughly seasoned and dry.

HANDI PRODUCTS CO  
P. O. Box 1955  
Cleveland 6, Ohio

# Handi-Copp Copper Napthenate

Excellent Preventative for  
**TERMITES - WOOD ROT**

Also used on canvas and rope

COMPLIES WITH  
Commercial Standards CS 152 - 48

Excellent Preventative for  
**TERMITES - WOOD ROT**  
Also used on canvas and rope

Harmful If Taken Internally

ANALYSIS  
Active Ingredients:  
Copper Napthenate 12.5  
Petroleum Distillate 87.5  
(Copper as metal 1%) 100

CAUTION!

KEEP OUT OF REACH OF CHILDREN

*A Quality Product  
of the*

**handi-family**

## WARNING

Harmful if swallowed or through skin. Causes irritation! Do not breathe spray mist. Do not get on skin, or on clothing. Wash thoroughly with soap and water after handling. KEEP FROM CHILDREN. Store away from heat and open flame. Keep container closed when not in use.

## GIVES LASTING PROTECTION

On wood, Canvas and rope excellent penetration. The preservative is of Copper which will check decay, fungi, termites and similar wood eating insects. Has a blue color that is not permanent. Apply by brush, spray or flood treatment.

Coverage is from 250 to 500 feet per gallon, depending on the condition and type of surface on which it is applied.

## EXCELLENT WATER PROOFING

Affords protection against decay and rot, on unpainted wood as well as exteriors which are painted over. An added benefit is that it can be applied below water line before painting.

U. S. Standard  
ONE GALLON