

BACK PANEL

Scentoff.

PELLETS

PRECAUTIONARY STATEMENTS
Hazardous to humans and domestic animals.

CAUTION

Avoid contact with skin. Avoid contamination of food and foodstuffs or drinking water. Following contact, wash with soap and water. Do not use near fire or flame.

ENVIRONMENTAL HAZARDS

Keep out of lakes, streams and ponds.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

USE RESTRICTIONS

For application on lawns; beside trees, shrubs, and flowers; and at the edge of gardens and inanimate objects. For use against dogs and cats to reduce the frequency of their defecation, urination or walking in specific areas. Do not apply within gardens or directly on flowers and other plants. For outdoor use only.

PRE-APPLICATION DIRECTIONS

At the proposed site of application, remove any pet droppings. Wash away any remaining strong odor of urine or droppings with a garden hose.

APPLICATION DIRECTIONS

Lightly scatter SCENT-OFF Pellets at the rate of 5 or 6 per sq. ft. around areas most vulnerable to damage and nuisance by offending dogs and cats.

Some pets may require more persistent treatment and stronger applications to discourage their visits and fouling. In such cases apply 8 to 10 SCENT-OFF Pellets per square foot and repeat this application every ten days, if necessary.

STORAGE & DISPOSAL

STORAGE: Store only in original container, in a dry place inaccessible to children and pets. Do not store package at temperatures above 140° F.

DISPOSAL: Do not reuse empty container. Securely wrap in newspaper and discard in trash.

Printed and Produced in U.S.A. EPA Est. No. 5332 MD-01
Reg. No. 10,811 P.C.F. Act

BEST AVAILABLE COPY

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

S 381255 / 300
18

NOV 08 1990

P1121
File -
1990

BEST AVAILABLE COPY

Mr. Robert J. Kirkpatrick
The Gibson-Homans Company
1755 Enterprise Parkway
Twinsburg, OH 44087

Dear Mr. Kirkpatrick:

Subject: Amended Formula and Label
Lumber Gard Copper Naphthenate Wood Preserver
EPA File Symbol 7500-6
Your Application Dated August 24, 1990

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, is acceptable provided that you:

1. Make the labeling changes listed below before you release the product for shipment bearing the amended labeling:
 - a. In the ingredient statement, line up the words Inert Ingredients with declared percentage 87.5 percent, and remove Petroleum Distillate from the ingredient statement.
 - b. Place a substatement below the ingredient statement:

Contains Petroleum Distillates.

2. Submit one (1) copy of your final printed labeling before you release the product for shipment.

A stamped copy of the labeling is enclosed for your records.

The amended formula is acceptable and has been included in the files for this product.

54343:I:Stone:L21-15:KENC0:10/09/90:11/04/90:de:vo:ek:de

CONCURRENCES

SYMBOL	SURNAME	DATE						

-2-

Please note that in your Confidential Statement of Formula the upper and lower limits for Petroleum Distillates are reversed.

The amended formula and labeling supersede all previously accepted ones.

Sincerely yours,

Susan Lewis
Product Manager (21)
Fungicide-Herbicide Branch
Registration Division (H7505C)

Enclosure

BEST AVAILABLE COPY

DESCRIPTION

Gives lasting protection on exterior wood, canvas and rope, with excellent penetration. This Preservative is of copper-base and will check decay, fungi, rotting, termites and similar wood infesting insects. Has a light green color that is not permanent. Apply by brush, spray or dip treatment. Coverage is from 250 to 450 square feet per gallon, depending upon condition and type of surface on which it is applied.

Affords protection against mold, and rot, on unpainted surfaces as well as exteriors which are to be painted over. An added protection below water line before using copper paint.

PRECAUTIONARY STATEMENTS

Hazards to Humans and Domestic Animals

Eyes — Can cause irritation

Skin — Causes irritation. Prolonged or repeated use may cause dermatitis.

Inhalation — May cause irritation of respiratory tract. Can cause dizziness and or light headedness.

Ingestion — May produce nausea, vomiting, diarrhea.

STATEMENT OF PRACTICAL TREATMENT

Eyes — Flush with water. Call physician.

Skin — Wash with soap and water.

Inhalation — Remove to fresh air. If not breathing, give artificial respiration. Call physician.

Ingestion — DO NOT induce vomiting. Call physician.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to lakes, streams, or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL OR CHEMICAL HAZARDS

Keep away from heat and open flame.

VOC = 550 g/l or greater. This product contains greater than 4.6 lbs. of VOC per gal. of coating, excluding water.



LG-5876-30F

ACCEPTED
with COMMENTS
in EPA Letter Dated

NOV 08 1990

Under the Federal Insecticide, Fungicide and Rodenticide Act and the Federal Pesticide Control Act, this pesticide is registered under EPA Reg. No. 7500-6

Lumber

garco

5876

COPPER NAPHTH WOOD PRESE

Active Ingredients	
Copper Naphthenate (Copper as metal 1%)	12.5
Inert Ingredients	
Petroleum Distillate	87.5
Total Ingredients	100.0

KEEP OUT OF REACH OF CHILDREN WARNING

BEST AVAILABLE COPY MAY BE FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN. VAPORS HARMFUL.

Causes skin irritation! Do not breathe vapor or spray mist. Do not wash thoroughly with soap and warm water after handling. Keep container closed when not in use. Wear protective clothing on treated lumber. See back panel for additional precautionary statements.

E.P.A. REG. NO. 7500-6

NET CONTENTS: FIVE GALLONS

Applicable facility indicated by first digit on label.

1. OH-01

3. GA-01 4. CA-01

6. IA-01

DIRECTIONS

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Use LUMBER GARD just as it is and DO NOT thin for any type of application. Shake well or stir thoroughly before using.

On wood, all previous paint and rotted wood should be removed, and the surface cleaned of loose particles and rust. Make brush applications as liberal as necessary to obtain good penetration. Two liberal coats are required particularly on wood that is to contact the ground. For dip treatment, soaking time depends on type of wood and its thickness. Approximately 30 minutes soaking is recommended for wood not more than 1" thick. For heavy timbers, overnight soaking is recommended.

Fabrics and cordage: unroll and apply sufficient compound to wet through — by dipping, time varies with material — by brush or spray, flood compound onto surface.

IMPORTANT:

If the surface treated with LUMBER GARD is to be painted over, allow at least 48 hours for drying before applying top coats. There might be slight discoloration on the first coat where white and light tints are used but this will disappear after the second coat is applied, provided the wood is thoroughly seasoned and dry.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

STORAGE:

Keep container closed when not in use.

PESTICIDE DISPOSAL (all except household):

Pesticide, spray mixture or rinse water that cannot be used according to label instructions must be disposed of according to applicable Federal, State or local procedures under the Resource Conservation and Recovery Act.

CONTAINER DISPOSAL

Household — Do not reuse empty container. Wrap and put in trash collection.

Other — Triple rinse (or equivalent) and offer for recycling or reconditioning, or dispose of in a sanitary refill, or by other approved State and local procedures.

the GIBSON-HOMANS COMPANY
1755 Enterprise Parkway
Twinsburg, Ohio 44087

Printed in U S A

BEST AVAILABLE COPY

17500