

DESCRIPTION

Gives lasting protection on exterior wood, canvas and rope, with excellent penetration. This Preservative is of copper-base and will check decay, fungi, rotting, termites and similar wood infesting insects. Has a light green color that is not permanent. Apply by brush, spray or dip treatment. Coverage is from 250 to 450 square feet per gallon, depending upon condition and type of surface on which it is applied.

Affords protection against mold, and rot, on unpainted surfaces as well as exteriors which are to be painted over. An added protection below water line before using copper paint.

PRECAUTIONARY STATEMENTS

Hazards to Humans and Domestic Animals

Eyes — Can cause irritation.

Skin — Causes irritation. Prolonged or repeated use may cause dermatitis.

Inhalation — May cause irritation of respiratory tract. Can cause dizziness and or light headedness.

Ingestion — May produce nausea, vomiting, diarrhea.

STATEMENT OF PRACTICAL TREATMENT

Eyes — Flush with water. Call physician.

Skin — Wash with soap and water

Inhalation — Remove to fresh air. If not breathing, give artificial respiration. Call physician.

Ingestion — DO NOT induce vomiting. Call physician.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to lakes, streams, or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL OR CHEMICAL HAZARDS

Keep away from heat and open flame.

VOC = 550 g/l or greater. This product contains greater than 4.6 lbs. of VOC per gal. of coating, excluding water.



LG-5876-30F

Lumber

gard

5876

COPPER NAPHTHENATE WOOD PRESERVER

Active Ingredients	
Copper Naphthenate	12.5%
(Copper as metal 1%)	
Inert Ingredients	
Petroleum Distillate	87.5%
Total Ingredients	100.0%

KEEP OUT OF REACH OF CHILDREN WARNING

MAY BE FATAL IF SWALLOWED
OR ABSORBED THROUGH SKIN
VAPORS HARMFUL

Causes skin irritation! Do not breathe vapor or spray mist. Do not get in eyes, on skin, or on clothing. Wash thoroughly with soap and warm water after handling. Keep away from heat and open flame. Keep container closed when not in use. Wear protective clothing and gloves when handling freshly treated lumber. See back panel for additional precautionary statements.

E.P.A. REG. NO. 7500-6

NET CONTENTS: FIVE GALLONS

E.P.A. Est. No. 7500 —

Applicable facility indicated by first digit on closure

1. OH-01

3. GA-01 4. CA-01

6. IA-01

15. TX-01

DIRECTIONS

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Use LUMBER GARD just as it is and DO NOT for any type of application. Shake well or thoroughly before using.

On wood, all previous paint and rotten wood should be removed, and the surface cleaned of loose particles and rust. Make brush applications as often as necessary to obtain good penetration. Two li coats are required. Particularly on wood that contact the ground or dip treatment, soaking depends on type of wood and its thickness. Approximately 30 minutes soaking is recommended. For heavy timbers, overnight soaking is recommended.

Fabrics and cordage: unroll and apply sufficient compound to wet through — by dipping, time with material — by brush or spray, flood compound onto surface.

IMPORTANT:

If the surface treated with LUMBER GARD is painted over, allow at least 48 hours for cure before applying top coats. There might be discoloration on the first coat where white and tints are used but this will disappear after the second coat is applied, provided the wood is thoroughly seasoned and dry.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by spill or disposal.

STORAGE:

Keep container closed when not in use.

PESTICIDE DISPOSAL (all except household)

Pesticide, spray mixture or rinse water should not be used according to label instructions and disposed of according to applicable Federal, or local procedures under the Resource Conservation and Recovery Act.

CONTAINER DISPOSAL

Household — Do not reuse empty container, and put in trash collection.
Other — Triple rinse (or equivalent) and of recycling or reconditioning, or dispose of sanitary refill, or by other approved State and procedures.

the GIBSON-HOMANS COMPANY
1755 Enterprise Parkway
Twinsburg, Ohio 44087

Printed in U.S.A.