

**DIRECTIONS****NET  
CONTENTS***Ready to Use***1-GALLON****DIRECTIONS****WOOD PRESERVATION**

For protection, all wood should be prima-ry dry. All sound wood should be treated 4 feet beyond any visible signs of decay.

To best results, PENTA WOOD PRESERVATIVE should be applied so as to maximize penetration into the wood. Maximum absorption at 100% saturation. Complete immersion, either in an open tank or in an open tank is recommended for accomplishing maximum penetration. Brush application is recommended for areas where wood will be in direct contact with the ground such as in fence posts, etc. After the immersion treatment, leave for 48 hours, then excess liquid should be peeled off with a brush or scrubbed.

When treating large areas, the wind should blow from the opposite direction of the spray. Where the wood is to be in direct contact with the ground, several coats application should be given. Estimated coverage, one 1-gallon per 1000 board feet for open tank treatment; 300 square feet per gallon for brush application.

May 27, 1971

MAP # 100-281

7624-5 1/68

**← USE ACCORDING TO DIRECTIONS →**

PENTAX

Phone PL 6-4483  
CONRCE

PENTAX CO.

Highway 105 East  
TEXAS**THE SITE CONTROL**

Lean out carefully all loose wood and debris under or around infested buildings. Spray all ground under buildings at rate of 2 gallons of PENTA WOOD PRESERVATIVE per 5 cubic feet of ground. Break all wood to emoji condition, such as steps, door frames, etc., and replace with PENTA treated wood or concrete. Where construction permits, dig a trench around all foundations up to a depth of 12 to 18 inches. For buildings with deep foundations, dig 18 inches deep. Apply five gallons of PENTA WOOD PRESERVATIVE to 5 linear feet of trench up to 15 inches deep; ten gallons per 10 linear feet for deeper trenches. Trees, shrubbery or flowers should be protected from the spray by tar or heavy kraftpaper.

**WARNING**

If swallowed or absorbed through skin or eyes, seek medical attention. Do not breathe vapor or spray mist. Do not get in eyes or on skin without clothing. Wash thoroughly. Do not store near heat or open flame. Do not puncture drum. Return to drum when empty. Destroy by perforating or crushing. Buy in a safe place.

This product is toxic to fish and wildlife. Keep out of lakes, streams or ponds.

Do not contaminate water by cleaning equipment or disposal of waste and containers.

Wear protective clothing and rubber gloves when handling the treated lumber.

**PENTA****WOOD PRESERVATIVE****Preserves Wood****Stops Rot and Decay****Prevents Fungi and****Molds of Wood****Controls Termites****Controls Powder Post Beetles**

Penta Wood Preservative  
is a water-soluble preservative  
containing pentachlorophenol  
as the active ingredient.

**ACTIVE INGREDIENT**

Chlorophenol*	4.35
Other Chlorophenols & Related Compounds	65
Petroleum Solvent	95.00

\*Chlorophenol is a registered trademark of the Dow Chemical Company.

**WARNING: KEEP OUT OF REACH OF CHILDREN**

See container for other warnings.

A Division of W. M. Conroe, Inc.