UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

FEB 9 1999

FMC Lithium Division Highway 161 - P.O. Box 795 Bessemer City, NC 28016-0795

Attention: Jim T. Hill, Ph.D

Agent for FMC Corporation, Lithium Division

Subject:

Formula 2® Shock Treatment

EPA Registration Number 7675-7

Your Submission Dated December 11, 1998

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, is acceptable provide that you make the labeling change listed below before you release the product for shipment bearing the amended labeling.


- 1. Delete the "CAS No. 13840-33-0" from the "ingredient statement".
- 2. Place the signal word "Danger" underneath "Keep out of Reach of Children".
- 3. Place the heading "Directions for Use" above "It is a Violation...".
- * Me Child Besistant Packaging is Required:

A stamped copy is enclosed for your records. Submit one copy of the final printed label before you release the product for shipment bearing the amended label.

If you have any questions concerning this letter, please contact Delores Williams at (703) 308-6372.

Sincerely,

Robert S. Brennis Product Manager (32) Regulatory Management Branch II Antimicrobials Division (7510C)



7675-7 revised Formula 2 Shock Treatment

ACCEPTED with COMMENTS in EPA Letter Dated:

FEB 9 1999

Under the recoral Insecticide, Function and Rodenticide Act as amended, for the pesticide registered under LFA Beg. No.

プレフス - 7

DANGER

Keep out of reach of children
See other precautions and First Aid Statements

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

HOW TO USE FORMULA 2 SHOCK TREATMENT: The pool water should be shock treated about once each week. Utilizing your pool test kit, adjust pH of pool to 7.2-7.6 Use one pound per 6,000 gallons of water in the evening when the pool will not be used for a minimum of 12 hours. Test the chlorine residual and if above 3.0 ppm do not allow swimming until residual has decreased.

PRECAUTIONARY STATEMENTS HAZARDS TO HUMAN AND DOMESTIC ANIMALS

Corrosive: Causes irreversible eye damage or skin burns. May be fatal if swallowed. Harmful if inhaled. Do not get in eyes, on skin or on clothing. Avoid breathing dust. Wear goggles or face shield, protective clothing and rubber gloves when handling. Wash hands thoroughly with soap and water before eating, drinking, chewing gum, using tobacco or using the toilet. Remove contaminated clothing and wash clothing before reuse.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

PHYSICAL AND CHEMICAL HAZARDS

Strong oxidizing agent. Mix only with water. Use clean, dry utensils. Do not add this product to any dispensing device containing remnants of any other product. Such use may cause a violent reaction leading to fire or explosion. Contamination with moisture, organic, and matter, or other chemicals may start a chemical reaction with generation of heat, liberation of hazardous gases, and possible generation of fire and explosion. In case of contamination or decomposition, do not reseal container. If possible isolate container in open air or well-ventilated area. Flood with large volumes of water, if necessary.

ref: f7675-7

STORAGE AND DISPOSAL

Store in a cool, dry place. Do not transfer into unlabeled containers. Close container tightly after each use. Protect from moisture and heat. Completely empty liner by shaking and tapping sides and bottom to loosen clinging particles. Empty residue into application equipment. Then dispose of liner in a sanitary landfill or by incineration if allowed by State and local authorities. If drum is not be reused or is contaminated and cannot be reused, dispose of in the same manner. Do not contaminate water, food or feed by storage or disposal.

PRACTICAL TREATMENT (First Aid)

IF SWALLOWED: Immediately call a Physician or Poison Control Center. Do not induce vomiting unless instructed by Physician or Poison Control Center. If so instructed drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger, or if available by administering syrup of ipecac. If person is unconscious, do not induce vomiting or give anything by mouth. Promptly drink large quantities of water. Avoid alcohol. IF ON SKIN: Wash with plenty of soap and water. Get medical attention. IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration,

preferably mouth-to-mouth. **Get medical attention.**

IF IN EYES: Hold eyelids open and flush with a steady, gentle stream of water for 15 minutes. Get medical attention.

NOTE TO PHYSICIAN

Lithium hypochlorite is corrosive to eyes, skin and mucous membranes with chemical burns (caustic). Treatment is dilution/flushing of site with copious amounts of water with controlled removal of exposure followed by symptomatic and supportive care to maintain life functions. Consideration should be given to careful endoscopy as stomach or esophageal burns, perforations or strictures may occur. Probable mucosal damage may contraindicate the use of gastric lavage. Careful gastric lavage with an endotracheal tube in place should be considered. Observation may be warranted. Medical advice - 303 595 9048 (collect).

A Lithco product from



FMC Corporation Lithium Division
Bessemer City, North Carolina
Formula 2 and Lithco are trademarks of FMC Corporation

Emergency Telephone Numbers (24 hours)
Medical 303 595 9048 (collect)
Transportation Chemtrec 800 424 9300
Other emergency FMC Corporation Lithium Division
704 629 5361

Lithium hypochlorite, dry (UN No. 1471) Net wt 10 lbs