

# HOCUT

# CA

Nov. 20, 1973

REGISTERED TRADEMARK  
OF THE  
EPA  
EPA REG. NO. 7779-16

## HOCUT<sup>®</sup> CA

### For Use in Water Dispersible Metal Working Coolants

**ACTIVE INGREDIENTS:**

Hexahydro-1, 3, 5-tris  
(2-hydroxypropyl)-s-triazine

50.0%

**INERT INGREDIENTS:**

50.0%

## DANGER

### KEEP OUT OF REACH OF CHILDREN

#### DIRECTIONS FOR USE

Hocut CA is used industrially for controlling the growth of bacteria and fungi. Specifically, it is used to eliminate objectionable odors in water dispersible metalworking coolants. The recommended dosage level is in the range, 1000-2000 ppm., (13 to 25 oz. per 100 gallons) depending on the severity of the problem. For individual machines, add Hocut CA directly to the sump; for central systems, add material to the discharge side of the reservoir.

Hocut CA is harmful or fatal if swallowed. Corrosive. Causes eye damage and skin irritation. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling.

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse.

#### MANUFACTURED BY

### E. F. HOUGHTON & CO.

PHILADELPHIA, DETROIT, CHICAGO, CARROLLTON, MANCHESTER, S. SAN FRANCISCO  
U.S.A.

EPA Reg. No. 7779 16