

ACCEPTED

# SLIMEX<sup>®</sup> 4416

ACTIVE INGREDIENTS	22%
(Nabam) Disodium ethylene bisdithiocarbamate	18%
INERT INGREDIENTS	
Total	100%

### DIRECTIONS FOR USE

Slimex 4416 is used industrially for controlling the growth of bacteria and fungi. Specifically, it is used to eliminate objectionable odors in water dispersible metalworking coolants. The recommended dosage level is in the range, 200-500 ppm, (2.5 - 6.25 oz. per 100 gallons) depending on the severity of the problem. For individual machines, add Slimex 4416 directly to the sump; for central systems, add material to the discharge side of the reservoir. This treatment should be repeated on a weekly basis.

**CAUTION: Keep out of reach of children.** May cause skin irritation. Avoid contact with skin and eyes. In case of contact, flush with plenty of water; for eyes, get medical attention. Harmful if swallowed.

Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

Do not reuse container. Destroy when empty.

SOLD BY

### E. F. HOUGHTON & COMPANY

PHILADELPHIA    DETROIT    CHICAGO    CARROLLTON, GA.    MANCHESTER, CONN.  
SOUTH SAN FRANCISCO  
U. S. A.

NET Wt. \_\_\_\_\_ lbs.

EPA Reg. No. 7779-18

# SLIMEX<sup>®</sup>

## 4416

# slimicide