

Sep 24, 1975

REGISTERED

**SLIMEX<sup>®</sup>**  
**4420**  
**slimicide**

**SLIMEX 4420**

**SLIMICIDE**

For use in Water Dispersible  
Metal Working Coolants

ACTIVE INGREDIENT:	
Hexahydro-1,3,5-tris (2-hydroxyethyl)-s triazine	50.0%
INERT INGREDIENTS:	50.0%

**DIRECTIONS FOR USE**

Slimex 4420 is used industrially for controlling the growth of bacteria and fungi. Specifically, it is used to eliminate objectionable odors in water dispersible metal working coolants.

For best results, drain and clean the system before adding fresh cutting fluid. For individual machines, add Slimex 4420 directly to the sump; for central systems, add material to the discharge side of the reservoir. In both cases add 0.25% of Slimex 4420 to the use dilution. (2.0 pints per 100 gallons of diluted cutting fluid). 0.25% of Slimex 4420 should also be added to the use dilution of the make up fluid.

**DANGER**

**Keep out of reach of children**

Slimex 4420 is harmful or fatal if swallowed. Corrosive. Causes eye damage and skin irritation. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Avoid contamination of food.

Treated effluent should not be discharged where it will drain into lakes, streams, ponds or public water. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

Do not reuse container. Destroy when empty.

**E. F. HOUGHTON & COMPANY**

PHILADELPHIA DETROIT CHICAGO CARROLLTON, GA. MANCHESTER, CONN. S. SAN FRANCISCO  
U.S.A.

Net Wt                      lbs

EPA Reg. No. 7779-1