

"USDA Reg. No. 7836-2"

COPPER NAPHTHENATE

**CAUTION:
FLAMMABLE**

Keep away from sparks and
fire.

**This Product contains 1% Copper in the
form of 10% Copper Naphthenate**

Active Ingredients	
Copper Naphthenate	10.0%
Petroleum Solvent	90.0%
	100.0%
Copper as Metallic	1.0%

PRESERVATIVE FOR WOOD

Fence posts, poles, foundation timbers and heavy wooden members should be free of bark, dry and well-seasoned and immersed for a period of 12 to 48 hours to be an effective wood preserver and against fungal rot, decay, termites and power post beetles.

Other lumber should be dipped for 3 minutes per inch of thickness or two flowing coats applied by brush where wood will be in contact with the soil.

For use on canvas, ropes and nets. "Dip or soak until thoroughly wet." "Do not contaminate water by cleaning of equipment or disposal of wastes.

DO NOT REUSE CONTAINER.

**CAUTION
KEEP OUT OF REACH OF CHILDREN.**

HARMFUL OR FATAL IF SWALLOWED
CONTAINS PETROLEUM MINERAL SPIRITS

IF SWALLOWED, DO NOT INDUCE VOMITING. CALL PHYSICIAN.

COMBUSTIBLE. Keep away from heat and open flame. Use with adequate ventilation. Avoid breathing of vapor. Do not transfer contents to bottles or other containers. Close container after each use.

MANUFACTURED BY
GARDNER ASPHALT PRODUCTS CO.
TAMPA, FLORIDA • BIRMINGHAM, ALABAMA

FIVE GALLONS

ACCEPTED!
6/19/77
UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND HERBICIDE ACT
AS REGISTERED UNDER NO. 7836-2

Comments

ACCEPTED WITH COMMENTS

"USDA Reg. No. 7836-2"

COPPER NAPHTHENATE

**CAUTION:
FLAMMABLE**

Keep away from sparks and
fire.

This Product contains 1% Copper in the
form of 10% Copper Naphthenate

Active Ingredients	
Copper Naphthenate	10.0%
Petroleum Solvent	90.0%
Copper as Metallic	1.0%

PRESERVATIVE FOR WOOD

Fence posts, poles, foundation timbers and heavy wooden members should be free of bark, dry and well-seasoned and imersed for a period of 12 to 48 hours to be an effective wood preserver and against fungal rot, decay, termites and power post beetles.

Other lumber should be dipped for 3 minutes per inch of thickness or two flowing coats applied by brush where wood will be in contact with the soil.

For use on canvas, ropes and nets. "Dip or soak until thoroughly wet." "Do not contaminate water by cleaning of equipment or disposal of wastes.

DO NOT REUSE CONTAINER.

CAUTION

KEEP OUT OF REACH OF CHILDREN.

HARMFUL OR FATAL IF SWALLOWED
CONTAINS PETROLEUM MINERAL SPIRITS

IF SWALLOWED, DO NOT INDUCE VOMITING. CALL PHYSICIAN.

COMPOSED OF COPPER NAPHTHENATE AND PETROLEUM MINERAL SPIRITS. USE WITH CARE AND PROTECTIVE CLOTHING. AVOID CONTACT WITH EYES. DO NOT INHALE. DO NOT GET ON CLOTHING. Close container after each use.

MANUFACTURED BY

GARDNER ASPHALT PRODUCTS CO.

TAMPA, FLORIDA • BIRMINGHAM, ALABAMA

NET WEIGHT