

TESTED IN SUB-TROPICAL CLIMATE

**GARDNER**  
OF  
**FLORIDA**

EPA Reg. No. 7836-3  
GOVERNMENT SPECIFICATION: TT-W-556  
Wood Preservative

**CREOSOTE OIL**  
Grade No. 1  
Active Ingredients 100%

**WARNING - KEEP OUT OF REACH OF CHILDREN**  
MAY BE FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN.

Keep away from heat and open flame. Keep container closed when not in use.  
Do not get in eyes, on skin or on clothing. Avoid breathing of the vapor.  
Wear rubber gloves when handling freshly treated lumber.

**DESCRIPTION**  
This Coal Tar Creosote Wood Preserving Compound combines water repellent and wood preserving properties. It may be used on many types of timber to delay the onset of decay or the entry of termites. Frequent inspection and reapplication may be necessary to maintain protection against wood rot, decay, insects or other pests.

**DIRECTIONS**  
Wood should be treated prior to construction for protection from termites. Shake or stir to mix contents before using. Posts must be free of bark, clean and dry. Posts should be soaked for 12 to 24 hours, depending upon seasoning of wood. Heavy timbers should be soaked 24 to 48 hours for best results. If applied with a paint brush apply at least two flood coats. Compound dries in approximately 24 hours.

Do Not Reuse Container.

ONE GALLON

TAMPA

ACCEPTED  
9-20-71  
7836-3

comment

ACCEPTED WITH COMMENTS

Manufactured by  
**GARDNER ASPHALT PRODUCTS**  
TAMPA, FLORIDA • BIRMINGHAM, ALABAMA