

Jacket

Marine Preservative

ACCEPTED

SEP 21 1962

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under P. Reg. No. 7995-15

BEST AVAILABLE COPY

701 Green

KEEP OUT OF REACH OF CHILDREN.

CAUTION

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

ONE U.S. GALLON 3.79 LITERS

ACTIVE INGREDIENTS	
Copper Naphthenate	25.0%
(Copper as Metallic 2%)	
INERT INGREDIENTS	75.0%
TOTAL	100.0%

Contains Petroleum Distillates

PRECAUTIONARY STATEMENTS
Hazards to Humans and Domestic Animals

CAUTION

Use only with adequate ventilation. Avoid contact with skin, eyes or clothing. Remove contaminated clothing and wash before reuse. Causes eye irritation. May be fatal if swallowed or inhaled. Harmful if absorbed through skin. Do not breathe vapors or spray mist. Wash thoroughly after use and before eating or smoking. Wear protective clothing; e.g. gloves, hat, shirt and pants.

Statement of Practical Treatment:

If swallowed: Promptly drink a large quantity of water. Avoid alcohol and get medical attention.

If in eyes: Flush with plenty of water. Get medical attention.

If on skin: Wash with soap and water. Get medical attention.

If inhaled: Remove victim to fresh air. If not breathing, give mouth-to-mouth respiration. Get medical attention immediately.

ENVIRONMENTAL HAZARD

Do not contaminate water when disposing of equipment wash waters.

PHYSICAL OR CHEMICAL HAZARD

Combustible. Do not use or store near heat or open flame.

152

Gloucester® KL-990®

Marine Preservatives

These preservatives provide protection against dry rot, fungus, termites, and mildew. Boat owners apply it to boat frames, spars, planking, decking, beams, ropes, and canvas. It is also recommended for sills, fences, fence posts, porches, railings, outside steps, outside furniture, screens, doors, storm windows, blinds, docks, floats, and piers.

Directions for Use

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

This solution is ready to use as it comes from the can, and it may be applied by spray, brush or dip. In brushing or spraying, apply at least two liberal coats. In dipping, a minimum immersion of three minutes is required, and 12 to 48 hours should be allowed for posts and other large timbers.

Wood to be treated should be dry, clean, and all bark, paint, varnish or other surface films removed. Care should be taken to coat any surfaces exposed by sawing, boring or sanding after original treatment. Be sure also to treat surfaces which will be butted together. One gallon will treat 250 to 400 square feet of lumber, depending on type and condition of wood.

When treated surfaces are to be painted, a minimum of 48 hours drying time should be allowed.

This product can readily be removed from hands, brushes and containers with kerosene or mineral spirits. Keep container tightly closed to prevent evaporation.

Special Instructions for Canvas, Nets and Ropes

Unless the green color is desired, canvas tarpaulins, covers, decks and sails should be treated with the clear preservative. Apply by dipping or by spray or brush until fabric is saturated, then dry in open air. The life of rope, lines and nets is very greatly extended by similar treatment, the green preservative being recommended for this purpose.

Storage and Disposal

Do not contaminate water, food or feed storage or disposal.

Pesticide Disposal

Wastes resulting from use of this product may be disposed of on site or at an approved waste disposal facility.

Container Disposal

Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

BEST AVAILABLE COPY

E.P.A. Registration #7995-15
E.P.A. Est. #7995-MA-1

Rule Industries, Inc.
Cape Ann Industrial Park
Gloucester, Massachusetts 01930 U.S.A.

© Rule Registered Trademark