UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

11:

J/ +

Rule Industries, Inc. Cape Ann Industrial Park Gloucester, MA 01930

Attention:

Leon Abelon

Subject:

)

Glouscester Sea Jacket Anti-Fouling Bottom Paint

540 Red

EPA Registration No. 7995-19 Amendment Dated August 30, 1990

The amendment referred to above submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, is acceptable provided that you make the labeling changes below.

1. Revise your storage and disposal statement to read as follows:

STORAGE AND DISPOSAL

Do not contaminate water, food, feed by storage or disposal.

PESTICIDE DISPOSAL

Paint that cannot be used according to label instructions must be disposed of according to federal, state or local procedures under the Resources Conservation and Recovery Act.

CONTAINER DISPOSAL

Dispose of container by triple rinse and recycling or puncturing and disposing in a sanitary landfill or by other approved State and local procedures.

The heading "STORAGE AND DISPOSAL" must be of the same type size as the child hazard warning statement.

(For plastic containers include the statement "If burned, stay out of smoke").

- 2. Delete the phrase "Tin Free" from the label, this is an implied safety claim.
- 3. The child hazard warning statement on the front panel is the wrong type size. Refer to the enclosure "The Label" for labeling type size requirements. Please note that the minimum type size for labels is 6 points.

CONCURRENCES							
SYMBOL			-2-				
SUPNAME							
DATE	.)			• • • • • • • • • • • • • • • • • • • •			
FPA Form 1320-1 (12-70)		\\		<u></u>	<u> </u>	OF E1CIA	I EH E COPY

The markets build with secretable 2 me., a

🤾 Printed on Recycled Paper

OFFICIAL FILE COPY

- 4. Change the phrase "Practical Treatment" to "Statement of Practical Treatment". Also print this heading in the same bold lettering as the other headings.
- 5. Move the "Note" section so that it directly follows the Precautionary Statements section, and appears before the Statement of Practical Treatment section.
- 6. Revise the sentence "If swallowed,...quantities of water" to read "If swallowed, promptly drink large quantities of water.".

Please note that EPA does not stamp additional brand name labels; therefore, your labels for "Glouscester Sea Jacket Anti-Fouling Bottom Paint 545 Black" are being returned. If you have any questions concerning this letter please call Marshall Swind ϵ ll at (703) 305-6908.

A stamped copy of the label is included for your records.

Sincerely yours,

John H. Lee

Product Manager 31

Antimicrobial Programs Branch Registration Division (H7505C)



Sea Jacket **Anti-Fouling Bottom Paint**

540 Red

WARNING

HEFP HUT OF REACH OF CHILDREN
LEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

er ine promedient. Prome inter-Promedient

41 Sec.

ONE U.S. QUART 946 ML

Gloucester, Sea Jacket

s is wertig a journit, mit, is the sit time.
The time is a life existent to expend the same of the site of the same of the sam an ellers also i them marine matters; since also also statistics in the second is a second also statistics and is negli-amortiants statistics in the good is negli-color categories and second also second and also and effective the first campoint and also second effective the campoint and also second effective and also second eff

Directions for Use It is a visuation of Federal law to use this product in a minuter inconsistent with

Fiberglass: New fiberglass bottoms must be rewaxed using #551 Epoxy *hinner or s sustable court therear or determent weeks I suitable paint flavorer or delengent week-sand with 80 to 100 grit paper and prime with rB370 or #375 Epoxy Primer. On sur-faces already planted and in good condi-tion, send to delened smoothness. Surfaces in poor condition should be stripped ed and of many purfoces.

Wood: This paint can be applied directly to new wood bottoms after sending smarth. Previously painted bofforts on which the old plant is in good condition ha his problem with belacion of yer cose durt. Where did paint is linese and axing in large a axis strip 4 off end proeed as for new unpainted work

Metal: Bring new metal to bright finish and prime with two costs of #8374 Epinity Ped Lead primer. On previously painted Haces loose or flaking spots in the risk ling should be resented down to bright renaility wire triusting, power sanding. Sanifelating and immediately spot med. At least one additional first of
 mer should be applied to these spate.

Application Information

The relative Allow at east 100 mounts with which required a tief the results after the sure fine of the sure of the mest results. are the princendage for mest results for ining is necessary use send-und the area and its state as well as equilibries and egy princin as well as a contage as 350 400 sq. ft. gail. Apple area may be thy brush. I aller in spray. Everywheature should be 40 ft or after e. Sur princendage. tuce should be of and clean with crose or fusing paint completely removed. Apply under good drythig conditions

Note: White spraying and/or sanding host surface, wear a mask or a respirator longly approved by the Mining Emorcement and Salety Administration and the National Institute for Occupational Salety and Health

Muintenance

Since man-made and netural pollution can reduce the effectiveness of all anti-foulant paint, it is recommended that the bottom paint be checked from time to and lightly scrubbed with a tolk."

Storage and Disposal

Do not contaminize water food or feed by storage or deposed. Paint that cannot be used according to laber instructions must used according to laber instructions must be disposed of according to featural state or icea procedures under the Retources. Crinservetion and Recovery Act. Dispose of contener by triple ness and recycling. niner approved State and incal procedures

PRECAUTIONARY STATEMENTS

WARNING

See only with adequate vent aftern femed on agent with such expensive withing themose contaminated softling and wish remove untaminated sominal and either of the fatal if walkneed in chared infamilial di absorbed through suin Do not breath lapus or spray man Wash thoroughly after use and before sating or smoking shet and pants

promptly dnnk a large quantity of milk egg whites, geletin solution or if not aveil able drivin large duantities of water Avoid alcohol. Gel medical attention

If in eyes, flush eyes such water cust medical aftertion II on sun, wash with soep and water. Get medical attention. If rehaled, remove victim to freeh air. If not treature, give mouth-to-mouth returns ton. Get medical attention.

This product is toxic to turn. Do not apply directly to water by cleaning of arturpment or disposal of waters. Do not allow chips and dust generated during plant removal to enter water. Dispose of print debris in an approved sendfel

PHYSICAL OF CHEMICAL HAZARD

Computable: Do not use or store near heat or open flame

ACCEPTO. with CottMitters in EPA Lover Lated:

· 2 2 1992

Under in dietral barreich Fund to serve

BEST AVAILABLE COPY