

rule
GLOUCESTER
★ Marine Paints ★

Sea Jacket
Anti-Fouling Bottom Paint

540 Red

KEEP OUT OF REACH OF CHILDREN

WARNING

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

ONE U.S. GALLON 3.79 LITERS

BEST AVAILABLE COPY

Gloucester Sea Jacket

Sea Jacket is a premium quality anti-fouling protective paint, resistant to algae, barnacles and other marine fouling. Effective in both salt and fresh water. It is a semi-hard, smooth finish, and its high copper content provides remarkable anti-fouling properties. It is easy to apply and gives long effective life. This paint provides excellent performance on high or low speed boats in tropical or temperate waters.

Directions for Use

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Fiberglass: New fiberglass bottoms must be dewaxed using #702 Dewaxer or a suitable paint thinner or detergent wash. Sand with 80 to 100 grit paper and prime with #B370 or #375 Epoxy Primer. On surfaces already painted and in good condition, sand to desired smoothness. Surfaces in poor condition should be stripped and treated as if new surface.

Wood: This paint can be applied directly to new wood bottoms after sanding smooth. Previously painted bottoms on which the old paint is in good condition may be recoated after sanding off all loose dirt. Where old paint is loose and flaking in large areas, strip it off and proceed as for new unpainted work.

Metal: Bring new metal to bright finish and prime with two coats of #B374 Epoxy Red Lead primer. On previously painted surfaces, loose or flaking spots in the old coating should be cleaned down to bright metal by wire brushing, power sanding or sandblasting and immediately spot-primed. At least one additional coat of primer should be applied to these spots before finish-coating.

Application Information

Stir thoroughly. Allow at least four hours between coats and before launching. Two coats are recommended for best results. If thinning is necessary, use #773 Brushing Thinner. Use #551 Thinner & Cleaner for cleaning brushes and equipment. Average coverage is 350-400 sq. ft./gal.

Application may be by brush, roller or spray. Temperatures should be 40° or above. Surface should be dry and clean with loose or flaking paint completely removed. Apply under good drying conditions.

Maintenance

Since man-made and natural pollution can reduce the effectiveness of all anti-fouling paint, it is recommended that the bottom paint be checked from time to time, and lightly scrubbed with a soft material.

Storage and Disposal

Do not contaminate water, food or feed by storage or disposal.

Pesticide Disposal

Paint that cannot be used according to label instructions must be disposed of according to federal, state or local procedures under the Resources Conservation and Recovery Act.

Container Disposal

Dispose of container by triple rinse and recycling or puncturing and disposing in a sanitary landfill or by other approved state and local procedures.

Rule Industries, Inc.
Cape Ann Industrial Park
Gloucester, Massachusetts 01930 U.S.A.

E.P.A. Registration #7995-19
E.P.A. Est. #7995-MA-1

PRECAUTIONARY STATEMENTS

Hazardous to Fish and Domestic Animals

WARNING

Use only with adequate ventilation. Avoid contact with skin, eyes or clothing. Remove contaminated clothing and wash before reuse. Causes eye irritation. May be fatal if swallowed or inhaled. Harmful if absorbed through skin. Do not breathe vapors or spray mist. Wash thoroughly after use and before eating or smoking. Wear protective clothing, e.g. gloves, hat, shirt and pants.

Note: When sanding and/or sanding boat surfaces, wear a mask or a respirator, jointly approved by the Mine Safety and Health Administration and the National Institute for Occupational Safety and Health.

Statement of Practical Treatment

If swallowed, do not induce vomiting. Drink a large quantity of water. Avoid alcohol and get medical attention.

If in eyes, flush with plenty of water. Get medical attention.

If on skin, wash with soap and water. Get medical attention.

If inhaled, remove victim to fresh air. If not breathing, give mouth-to-mouth respiration. Get medical attention immediately.

ENVIRONMENTAL HAZARD

This product is very flammable. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARD

Combustible. Do not use or store near heat or open flame.