

 rule

**SUPER
KLTTM
F**

**ACCEPTED
SEP 23 1992**
Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
registered under 7995-27
EPA Reg. No.

BEST

KL-990
ANTI-FOULING COATING

RED

WARNING
KEEP OUT OF REACH OF CHILDREN
SEE BACK PANEL FOR ALL INFORMATION
AND CAUTIONARY STATEMENT

**ONE U.S. GALLON
3.79 LITERS**

CONTAINS 11

Super KL-TF™

Super KL-TF is a premium anti-fouling coating that provides effective protection for boats that are used in high fouling waters or remain in the water for prolonged periods between haul outs. It forms a smooth surface and can be applied over most hard and soft bottom paints.

Directions for Use

It is a violation of federal law to use or dispose of this product in a manner inconsistent with its labeling:

New Fiberglass — No Sanding:

Thoroughly clean with 551 Hi-Solvency Thinner & Cleaner, lifting the solvent wax and contaminants off the surface with clean rags.

Apply one thin coat of 179 No Sanding Primer, allow to dry a minimum of one hour and a maximum of four hours, then apply two coats of Super KL-TF by brush, roller or spray.

New Fiberglass — Epoxy Barrier Coat:

Thoroughly clean with 551 Hi-Solvency Thinner & Cleaner, lifting the solvent wax and contaminants off the surface with clean rags.

Abrade with 80 grit sandpaper, then seal with two coats of B370 Two-Part Epoxy Primer.

Sand between coats and before applying the anti-fouling coating to improve adhesion. Apply two coats of KL-TF by brush, roller or spray.

New Wood: Sand with 80 grit sandpaper, clean thoroughly and apply two coats of Super KL-TF by brush, roller or spray.

Metal: Super KL-TF contains cuprous oxide and is not recommended for aluminum surfaces. Iron and steel should be cleaned to bright metal and then sealed with two coats of an anti-corrosive primer such as B374 Red Lead Epoxy. Apply two coats of Super KL-TF by brush, roller or spray.

Previously Painted Surfaces: Super KL-TF can be applied over most hard and soft bottom paints so long as they are clean and in good condition.

Coatings that are cracked, damaged or peeling should be completely removed before painting.

Application Information

Mix thoroughly. Allow to dry at least six hours between coats and before launching. For best results, apply at least two coats. Apply by spray, short-nap roller or brush. Use mineral spirits for thinning and cleaning equipment.

Recommended application temperature range is 65°-80°F. Expected coverage is 350 to 400 square feet per gallon.

Maintenance

Physical damage, fuel spills and pollution can reduce the effectiveness of anti-fouling coatings. Therefore, it is recommended that the bottom be inspected periodically. If necessary, clean with a soft towel. Never use a stiff brush, scrub pad or abrasives.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Store antifouling coatings in their original, tightly sealed containers.

PESTICIDE DISPOSAL

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

PRECAUTIONARY STATEMENTS
Hazardous to Humans and Domestic Animals.

WARNING

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray mist. Wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

STATEMENT OF Practical Treatment

If swallowed: Promptly drink a large quantity of water. Avoid alcohol and get medical attention.

If in eyes: Flush with plenty of water. Get medical attention.

If on skin: Wash with soap and water. Get medical attention.

If inhaled: Remove victim to fresh air. If not breathing, give mouth-to-mouth respiration. Get medical attention immediately.

ENVIRONMENTAL HAZARD

This product is toxic to fish. Do not apply directly into the water during cleaning or disposal of wastes. Do not allow chips or dust generated during paint removal to enter the water. Dispose of debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARD

COMBUSTIBLE. Do not use or store near heat or open flame.

E.P.A. Registration #7995-27

E.P.A. Est. #7995-MA-1

Rule Industries, Inc.
Cape Ann Industrial Park
Gloucester, Massachusetts 01930

* Rule Registered Trademark

COPIE