

Super KL™

Super KL is a premium anti-fouling coating that provides effective protection for boats that are used in high fouling waters or remain in the water for prolonged periods between haul outs. It forms a smooth surface and can be applied over most hard and soft bottom paints.

Directions for Use

It is a violation of federal law to use or dispose of this product in a manner inconsistent with its labeling:

New Fiberglass—No Sanding: Thoroughly clean with 702 Dewaxer, lifting the solvent, wax and contaminants off the surface with clean rags.

Apply one thin coat of 179 No Sanding Primer, allowing to dry a minimum of one hour and a maximum of four hours, then apply two coats of Super KL by brush, roller or spray.

New Fiberglass—Epoxy Barrier Coat: Thoroughly clean with 702 Dewaxer, lifting the solvent, wax and contaminants off the surface with clean rags.

Abrade with 80 grit sandpaper, then seal with two coats of B370 Two-part Epoxy Primer. Sand between coats and before applying the anti-fouling coating to improve adhesion. Apply two coats of Super KL by brush roller or spray.

New Wood: Sand with 80 grit sandpaper, clean thoroughly and apply two coats of Super KL by brush, roller or spray.

Metal: Super KL contains cuprous oxide and is not recommended for aluminum surfaces.

Iron and steel should be cleaned to bright metal and then sealed with two coats of an anticorrosive primer such as B374 Red Lead Epoxy. Apply two coats of Super KL by brush, roller or spray.

Previously Coated Surfaces: Super KL can be applied over most other hard and soft bottom paints so long as they are clean and in good condition. Coatings that are cracked, damaged or peeling should be completely removed before painting.

Application Information

Mix thoroughly. Allow to dry at least overnight between coats and before launching. For best results apply at least two coats. Apply by spray, short-nap roller or brush. Use mineral spirits for thinning and cleaning equipment. Recommended application temperature range is 65°F – 80°F. Expected coverage is 350-400 square feet per gallon.

Maintenance

Physical damage, fuel spills and pollution can reduce the effectiveness of anti-fouling coatings. Therefore, it is recommended that the bottom be inspected periodically. If necessary, clean with a soft towel. Never use a stiff brush, scrub pad or abrasives.

Storage and Disposal

Do not contaminate water, food or feed by storage or disposal. Store anti-fouling coatings in their original tightly-sealed containers.

Pesticide Disposal

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Container Disposal

Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

© Rule Registered Trademark
™ Property of Rule Industries, Inc.

PRECAUTIONARY STATEMENTS

Hazards to Humans and Domestic Animals.

WARNING

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor, or spray mist. Wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

Statement of Practical Treatment

If swallowed. Promptly drink a large quantity of water. Avoid alcohol and get medical attention.

If in eyes. Flush with plenty of water. Get medical attention.

If on skin. Wash with soap and water. Get medical attention.

If inhaled. Remove victim to fresh air. If not breathing, give mouth-to-mouth respiration. Get medical attention immediately.

ENVIRONMENTAL HAZARD

This product is toxic to fish and other marine life. Do not apply directly to the water during cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter the water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARD

COMBUSTIBLE. Do not use or store near heat or open flame.

E.P.A. Registration #7995-27

E.P.A. Est. #7995-MA-1

Rule Industries, Inc.

Cape Ann Industrial Park

Gloucester, Massachusetts 01930 U.S.A.

7995-27
Acceptance Stamp on 78. 2 of 2
12/5/95
Page 1 of 2



SUPER KTML

ACCEPTED
 DEC 5 1995
 Under the Federal Insecticide,
 Fungicide, and Rodenticide Act,
 as amended, for the pesticide
 registered under 7995-217

KL-9900 ANTI-FOULING COATING

RED K90

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of Ruie Industries, Inc. including surface preparation, proper application and environmental conditions. Therefore, Ruie Industries, Inc. cannot guarantee the suitability of this product for your particular application. Implied warranties of fitness for a particular purpose and of merchantability are excluded. Ruie Industries, Inc. shall not under any circumstances be liable for incidental or consequential damages. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at the option of Ruie Industries, Inc.

KEEP OUT OF REACH OF CHILDREN.

WARNING

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

ONE U.S. GALLON
 3.79 LITERS

ACTIVE INGREDIENTS
 CASUS OVER 1000
 INERT INGREDIENTS 2000
 TOTAL WEIGHT 3000
 CONTAINS PETROLEUM DISTILLATES