

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

JAN 22 1992

Rule Industries, Inc.  
Cape Ann Industrial Park  
Westchester, MA 01930

Attention: Leon Abelon

Subject: Sea Jacket Anti-Fouling Bottom Paint  
541 Green  
EPA Registration No. 7995-28  
Amendment Dated August 30, 1990

The amendment referred to above submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, is acceptable provided that you make the labeling changes below.

1. Revise your storage and disposal statement to read as follows:

STORAGE AND DISPOSAL

Do not contaminate water, food, feed by storage or disposal.

PESTICIDE DISPOSAL

Paint that cannot be used according to label instructions must be disposed of according to federal, state or local procedures under the Resources Conservation and Recovery Act.

CONTAINER DISPOSAL

Dispose of container by triple rinse and recycling or puncturing and disposing in a sanitary landfill or by other approved State and local procedures.

The heading "STORAGE AND DISPOSAL" must be of the same type size as the child hazard warning statement.

(For plastic containers include the statement "If burned, stay out of smoke").

2. Delete the phrase "Tin Free" from the label, this is an implied safety claim.

3. The child hazard warning statement on the front panel is the wrong type size. Refer to the enclosure "The Label" for labeling type size requirements. Please note that the minimum type size for labels is 6 POINTS

SYMBOL							
SURNAME							
DATE							

4. Change the phrase "Practical Treatment" to "Statement of Practical Treatment". Also print this heading in the same bold lettering as the other headings.

5. Move the "Note" section so that it directly follows the Precautionary Statements section, and appears before the Statement of Practical Treatment section.

6. Revise the sentence "If swallowed, ...quantities of water" to read "If swallowed, promptly drink large quantities of water."

If you have any questions concerning this letter please call Marshall Swindell at (703) 305-6908.

A stamped copy of the label is included for your records.

Sincerely yours,



John H. Lee  
Product Manager 31  
Antimicrobial Programs Branch  
Registration Division (H7505C)

# Sea Jacket Anti-Fouling Bottom Paint

## 541 Green

### WARNING

KEEP OUT OF REACH OF CHILDREN  
SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

ACTIVE INGREDIENTS	WT. %
Cuprous Oxide*	27.00
WEIGHT ADJUSTERS	6.00
	100.00
*Total Cuprous Oxide	2.70

ONE U.S. QUART 946 ML

#### Gloucester Sea Jacket

Sea Jacket is a premium quality anti-fouling protective paint resistant to algae, barnacles and other marine fouling. Effective in both salt and fresh water, it is a semi-hard, smooth finish and its high copper content provides remarkable anti-fouling properties. It is easy to apply and gives long effective life. This paint provides excellent performance on high or low speed boats in tropical or temperate waters.

#### Directions for Use

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

**Fiberglass:** New fiberglass bottoms must be deaired using #551 Epoxy Thinner or a suitable paint thinner or detergent wash. Sand with 80 to 100 grit paper and prime with #B370 or #B375 Epoxy Primer. On surfaces already painted and in good condition, sand to desired smoothness. Surfaces in poor condition should be stripped and treated as if new surface.

**Wood:** This paint can be applied directly to new wood bottoms after sanding smooth. Previously painted bottoms on which the old paint is in good condition may be recoated after sanding off all loose dirt. Where old paint is loose and flaking in large areas, strip it off and proceed as for new unpainted work.

**Metal:** Bring new metal to bright finish and prime with two coats of #B374 Epoxy Red Lead primer. On previously painted surfaces, loose or flaking spots in the old coating should be cleaned down to bright metal by wire brushing, power sanding or sandblasting and immediately reprimed. At least one additional coat of primer should be applied to these spots before fresh coating.

#### Application Information

Stir thoroughly. Allow at least four hours between coats and before launching. Two coats are recommended for best results. If thinning is necessary, use denatured alcohol only. It should be used for cleaning brushes and equipment as well. Average coverage is 350-400 sq. ft./gal. Application may be by brush, roller or spray. Surface temperature should be 40° or above. Surface should be dry and clean with loose or flaking paint completely removed. Apply under good drying conditions.

**Water:** While spraying and/or tending boat surface, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health.

#### Maintenance

Since man-made and natural pollution can reduce the effectiveness of all anti-fouling paint, it is recommended that the bottom paint be checked from time to time, and lightly scrubbed with a soft material.

#### Storage and Disposal

Do not contaminate water, food or feed by storage or disposal. Paint that cannot be used according to label instructions must be disposed of according to federal, state or local procedures under the Resource Conservation and Recovery Act. Dispose of container by triple rinse and recycling or disposing in a sanitary landfill or by other approved state and local procedures.

#### PRECAUTIONARY STATEMENTS

Hazards to Humans and Domestic Animals

#### WARNING

Use only with adequate ventilation. Avoid contact with skin, eyes or clothing. Remove contaminated clothing and wash before reuse. Causes eye irritation. May be fatal if swallowed or inhaled. Harmful if absorbed through skin. Do not breathe vapors or spray mist. Wash thoroughly after use and before eating or smoking. Wear protective clothing, e.g. gloves, hat, shirt and pants.

**Practical Treatment:** If swallowed, promptly drink a large quantity of milk, egg whites, gelatin solution, or if not available, drink large quantities of water. Avoid alcohol. Get medical attention if in eyes, flush eyes with water. Get medical attention if on skin, wash with soap and water. Get medical attention, if inhaled, remove victim to fresh air. If not breathing, give mouth-to-mouth respiration. Get medical attention.

#### ENVIRONMENTAL HAZARD

This product is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

#### PHYSICAL OR CHEMICAL HAZARD

Combustible. Do not use or store near heat or open flame.

EPA Registration #7885-28  
EPA Est. #7885-MA-1

Paints & Chemical, Inc.  
Gloucester, Massachusetts 01930 U.S.A.  
©1980 Registered trademark

ACCEPTED  
with COMMENTS  
in EPA Label 1-82

REV 4 2 88

Under the provisions of the  
Federal Insecticide, Fungicide,  
and Rodenticide Act, this  
product is registered under the  
Registration No. 7995-28

BEST AVAILABLE COPY