

BEST AVAILABLE COPY

# GLOUCESTER

## MARINE PAINTS

ACCEPTED  
FEB 12 1981

ACTIVE INGREDIENTS  
Cadmium Oxide 37.5  
Manganese Dioxide 10.0  
NET WEIGHT 47.5  
Other Metals 0.0



# SEA JACKET EPOXY-552 GREEN ANTI-FOULING PAINT

Excellent adhesion and anti-fouling qualities are characteristics of this epoxy based paint. For use on fiberglass, wood and metal boats. Durable, hard and smooth, the ideal choice for all types of high, medium or low speed boats in any water temperature for lasting and effective anti-fouling performance. May be applied over vinyls or other hard type anti-fouling paints.

## GENERAL INFORMATION

Stir thoroughly. Allow at least 4 hours between coats and before launching. Two coats are recommended for best results. Use only # 551 Epoxy Thinner, if thinning is necessary. Clean brushes and equipment with # 551 also. Recommended application temperature is 65-85°F. Application in temperature below 60° will unduly extend cure time.

## PRECAUTIONARY STATEMENTS

### HAZARDS TO HUMANS AND DOMESTIC ANIMALS. CAUTION!

Contains copper. May be fatal if swallowed. Avoid breathing vapor, dust or spray mist. Do not get in eyes, on skin or clothing. In case of contact, flush eyes immediately with plenty of water and wash skin with soap and water. Avoid contamination of food and feed products.

Note: When product is used in confined areas, wear a pesticide respirator jointly approved by the Mining Enforcement and Safety Administration (formerly the U.S. Bureau of Mines) and the National Institute for Occupational Safety and Health under the provisions of 30 CFR 11.

## ENVIRONMENTAL HAZARDS

Do not contaminate water by cleaning of equipment or disposal of wastes.

## PHYSICAL HAZARDS

Combustible. Keep away from heat and flame.

## DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

**Fiberglass** — New fiberglass must be dewaxed. Epoxy Thinner # 551 is recommended for this purpose. Other suitable solvent or detergent wash may be used. Apply this paint directly as its own primer or apply over # B370 or # 375 Epoxy Fiberglass Primer. On previously painted bottoms, apply to smooth clean surface.

**Wood** — New wood, and previously painted bottoms need only be properly sanded. Apply directly to the clean, dry surface.

**Metal** — Surfaces should be brought to bright metal and degreased with Epoxy Thinner # 551. Immediately apply two coats of # B374 Epoxy Red Lead in accordance with label instructions. Apply to primed surface.

## STORAGE AND DISPOSAL

Close container after each use. Do not reuse container. Destroy when empty.