U.S. ENVIRONMENTAL PROTECTION AGENCY
OFFICE OF PESTICIDES PROGRAMS
REGISTRATION DIVISION (WH-567)
WASHINGTON, D.C. 20460

NOTICE OF PESTICIDE: ☒ REGISTRATION ☐ REREGISTRATION

(Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended)

EPA REGISTRATION NO.: 7995-52

DATE OF ISSUANCE: JUL 29 1985

TERM OF ISSUANCE:

NAME OF PESTICIDE PRODUCT: Alumajacket 518 Black

NAME AND ADDRESS OF REGISTRANT *(Include ZIP code)*

Pure Paint & Chemical Co.
Cape Ann Industrial Park
Gloucester, MA 01930

NOTE: Changes in labeling [illegible] in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

[illegible] in accordance with FIFRA [illegible]

[illegible] [illegible] [illegible] [illegible]

[illegible] [illegible] [illegible] [illegible]

[illegible] [illegible] [illegible] [illegible]

[illegible] [illegible] [illegible] [illegible]

[illegible] [illegible] [illegible] [illegible]

[illegible] [illegible] [illegible] [illegible]

[illegible] "May be [illegible] sensitizer," or submit data [illegible] that [illegible] cause [illegible] reaction.

[illegible] "Wear [illegible] clothing, e.g., gloves, [illegible] "Wear protective clothing such as [illegible] and gloves."

[illegible] "Wash thoroughly after use and before eating or smoking." [illegible] "Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse."

☒ ATTACHMENT IS APPLICABLE

BEST AVAILABLE COPY

SIGNATURE OF APPROVING OFFICIAL | DATE

EPA Form 8570-6 (Rev. 5-76) PREVIOUS EDITION MAY BE USED UNTIL SUPPLY IS EXHAUSTED.

Add the phrase "Do not get in eyes or on clothing" after the words "Corrosive, causes skin burns."

c. The words "Active Ingredients and Inert Ingredients" must be given equal prominence and they must be of the same type size. Use the words "Inert Ingredients" for "Inert."

d. The preferred declaration for the first active ingredient should be: "Tributyltin fluoride," note the spelling of word "fluoride."

e. The substatement to the second active ingredient should be enclosed in parenthesis: (As part of a polymer). Replace the word "copolymer" with "polymer."

f. The label should bear a statement below the ingredient statement "Contains petroleum distillates."

3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 Enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

John H. Lee
Product Manager (31)
Disinfectants Branch
Registration Division (TS-767c)

Enclosure

RD/DIS:JOL:91178:Lee:RD:85/34:Kendrick&Co:898-1270:6/10/85:Del:6/18/85:DKD

Rule®

Gloucester®

Marine Paints

Alumajacket 518 Black

ACCEPTED
with COMMENTS
in EPA Letter Dated:

JUL 29 1985

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 7995-52

518 Black
ONE U.S. QUART
946 ML

ACTIVE INGREDIENTS

Tri-n-butyltin Flouride	2.33%
Tributyltin Methacrylate as part of a Copolymer	11.10
Inert	86.57
Total	100.00%

DANGER
Keep out of reach of children.
See back panel for additional precautionary statements.

Gloucester® Aluminum Boat and Outdrive Anti-Fouling Bottom Paint
This product is an anti-fouling protective paint, resistant to algae, barnacles and other marine fouling.

It is a one-part epoxy-based Tri-n-butyltin Flouride paint designed specifically to solve the problems of electrolysis between copper ingredients and aluminum. While formulated for aluminum boats and outdrives, it is fully as effective and useful on fiberglass and wood.

Directions for Use
It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Aluminum: Bare aluminum should be cleaned and degreased with Gloucester #551 Epoxy Thinner & Cleaner, lacquer thinner, or other suitable product. Wipe dry. Sand with 80-grit sandpaper. Immediately apply Gloucester #414 Wash Primer mixed with Activator per label instructions.

On previously painted surfaces, may be applied over itself or most hard anti-fouling paints. Test a small area for compatibility. Before application sand old finish lightly with 80-grit paper.

Aluminum Outdrives: Follow directions above. May be applied over most factory finishes.

Fiberglass: New fiberglass must be dewaxed. Gloucester #551 Thinner & Cleaner is recommended for this purpose. Lacquer Thinner or other suitable solvent may be used. Sand with 80-grit sandpaper and prime with Gloucester B370 Epoxy Primer.

On previously painted surfaces, check for compatibility. Sand with 80-grit sandpaper. Old paints in poor condition should be stripped. Proceed as for new fiberglass.

Wood: New wood and previously painted bottoms need only be properly sanded. Apply three coats. The first coat may be reduced with no more than 10% Gloucester #551 Thinner & Cleaner.

Application Information
Stir thoroughly. Allow overnight drying between coats and before launching. Two coats are recommended for best results. Apply with short-nap roller or brush. Use only Gloucester #551 Thinner & Cleaner if thinning is necessary. Also use for cleaning brushes and equipment. Recommended application temperature is 65°-85°F. Application in temperatures below 60°F will unduly extend cure time. Average coverage is 250 sq. ft./gal.

Maintenance
Since man-made and natural pollution can reduce the effectiveness of all anti-foulant paint, it is recommended that the bottom paint be checked from time to time, and lightly scrubbed with a soft material.

STORAGE AND DISPOSAL
Do not contaminate water, food, or feed by storage in disposal. Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rerisate is a violation of Federal law. If these wastes cannot be disposed of according to label instructions, contact your State Pesticide or Environmental Control Agency, or the hazardous waste representative at the nearest EPA regional office for guidance. Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedure approved by state and local authorities. Store in original tightly sealed container.

ACCEPTED
WITH COMMENTS
In EPA Letter Dated:
JUL 29 1985
Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 7995-52

PRECAUTIONARY STATEMENTS
Hazards to Humans and Domestic Animals.

DANGER
Use only with adequate ventilation. Corrosive; causes skin burns. May be dermal sensitizer. Wear protective clothing, e.g., gloves, hat, shirt, and pants. Causes irreversible eye damage and burns. May be fatal if swallowed or inhaled. Harmful if absorbed through skin. Do not breath vapors or spray mist. Wash thoroughly after use and before eating or smoking. When used in enclosed areas while spraying and/or sanding boat surface, wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Wear goggles, face shield, or safety glasses.

Practical Treatment. If swallowed, promptly drink a large quantity of milk, egg whites, gelatin solution, or if not availabel, drink large quantities of water. Avoid alcohol. Get medical attention. Note to M.D.: probable mucosal damage may contraindicate the use of gastric lavage. If in eyes, flush eyes with water. Get medical attention. If on skin, wash with soap and water. Get medical attention. If inhaled, remove victim to fresh air. If not breathing, give mouth-to-mouth respiration. Get medical attention.

ENVIRONMENTAL HAZARD
This product is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL
HAZARD
FLAMMABLE. Do not use or store near heat or open flame.

E.P.A. Registration #7995-
E.P.A. Est. #7995-MA-1

Rule Paint and Chemical, Inc.
Gloucester, Massachusetts 01930 U.S.A.

®Rule Registered Trademark

ACCEPTED
with COMMENTS
in EPA Letter Dated:

JUL 29 1985

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 7995-52

U.S. ENVIRONMENTAL PROTECTION AGENCY
OFFICE OF PESTICIDES PROGRAMS
REGISTRATION DIVISION (WH-567)
WASHINGTON, D.C. 20460

NOTICE OF PESTICIDE: ☒ REGISTRATION ☐ REREGISTRATION

(Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended)

EPA REGISTRATION NO.: [illegible]-52

DATE OF ISSUANCE: JUL 29 1985

TERM OF ISSUANCE:

NAME OF PESTICIDE PRODUCT: [illegible]

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

[illegible]

NOTE: Changes in labeling [illegible] in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

[illegible]

☒ ATTACHMENT IS APPLICABLE

BEST AVAILABLE COPY

SIGNATURE OF APPROVING OFFICIAL

DATE

EPA Form 8570-6 (Rev. 5-76) PREVIOUS EDITION MAY BE USED UNTIL SUPPLY IS EXHAUSTED.

Add the phrase "Do not get in eyes or on clothing" after the words "Corrosive, causes skin burns."

c. The words "Active Ingredients and Inert Ingredients" must be given equal prominence and they must be of the same type si: . Use the words "Inert Ingredients" for "Inert."

d. The preferred declaration for the first active ingredient should be: "Tributyltin fluoride," note the spelling of word "fluoride."

e. The substatement to the second active ingredient should be enclosed in parenthesis: (As part of a polymer). Replace the word "copolymer" with "polymer."

f. The label should bear a statement below the ingredient statement "Contains petroleum distillates."

3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 Enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

John H. Lee
Product Manager (31)
Disinfectants Branch
Registration Division (TS-767c)

Enclosure

RD/DIS:JOB:91178:Lee:RD:85/34:Kendrick&Co:898-1270:6/10/85:Del:6/18/85:DKD

Rule®

Gloucester®

Marine Paints

Alumajacket 518 Black

ACCEPTED
with COMMENTS
in EPA Letter Dated

JUL 29 1985

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 7995-52

518 Black
ONE U.S. QUART
946 ML

ACTIVE INGREDIENTS	
Tri-n-butyltin Flouride	2.33%
Tributyltin Methacrylate as part of a Copolymer	11.10
Inert	86.57
Total	100.00%

DANGER
Keep out of reach of children.
See back panel for additional precautionary statements.

Gloucester® Aluminum Boat and Outdrive Anti-Fouling Bottom Paint
This product is an anti-fouling protective paint, resistant to algae, barnacles and other marine fouling.

It is a one-part epoxy-based Tri-n-butyltin Flouride paint designed specifically to solve the problems of electrolysis between copper ingredients and aluminum. While formulated for aluminum boats and outdrives, it is fully as effective and useful on fiberglass and wood.

Directions for Use
It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Aluminum: Bare aluminum should be cleaned and degreased with Gloucester #551 Epoxy Thinner & Cleaner, lacquer thinner, or other suitable product. Wipe dry. Sand with 80-grit sandpaper. Immediately apply Gloucester #414 Wash Primer mixed with Activator per label instructions.

On previously painted surfaces, may be applied over itself or most hard anti-fouling paints. Test a small area for compatibility. Before application and old finish lightly with 80-grit paper.

Aluminum Outdrives: Follow directions above. May be applied over most factory finishes.

Fiberglass: New fiberglass must be dewaxed. Gloucester #551 Thinner & Cleaner is recommended for this purpose. Lacquer Thinner or other suitable solvent may be used. Sand with 80-grit sandpaper and prime with Gloucester B370 Epoxy Primer.

On previously painted surfaces, check for compatibility. Sand with 80-grit sandpaper. Old paints in poor condition should be stripped. Proceed as for new fiberglass.

Wood: New wood and previously painted bottoms need only be properly sanded. Apply three coats. The first coat may be reduced with no more than 10% Gloucester #551 Thinner & Cleaner.

Application Information
Stir thoroughly. Allow overnight drying between coats and before launching. Two coats are recommended for best results. Apply with short-nap roller or brush. Use only Gloucester #551 Thinner & Cleaner if thinning is necessary. Also use for cleaning brushes and equipment. Recommended application temperature is 65°-85°F. Application in temperatures below 60°F will unduly extend cure time. Average coverage is 250 sq. ft./gal.

Maintenance
Since man-made and natural pollution can reduce the effectiveness of all anti-foulant paint, it is recommended that the bottom paint be checked from time to time, and lightly scrubbed with a soft material.

STORAGE AND DISPOSAL
Do not contaminate water, food, or feed by storage in disposal. Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rerisate is a violation of Federal law. If these wastes cannot be disposed of according to label instructions, contact your State Pesticide or Environmental Control Agency, or the hazardous waste representative at the nearest EPA regional office for guidance. Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedure approved by state and local authorities. Store in original tightly sealed container.

ACCEPTED
WITH COMMENTS
In EPA Letter Dated:
JUL 29 1985
Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 7995-52

PRECAUTIONARY STATEMENTS
Hazards to Humans and Domestic Animals.

DANGER
Use only with adequate ventilation. Corrosive; causes skin burns. May be dermal sensitizer. Wear protective clothing, e.g., gloves, hat, shirt, and pants. Causes irreversible eye damage and burns. May be fatal if swallowed or inhaled. Harmful if absorbed through skin. Do not breath vapors or spray mist. Wash thoroughly after use and before eating or smoking. When used in enclosed areas while spraying and/or sanding boat surface, wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Wear goggles, face shield, or safety glasses.

Practical Treatment. If swallowed, promptly drink a large quantity of milk, egg whites, gelatin solution, or if not availabel, drink large quantities of water. Avoid alcohol. Get medical attention. Note to M.D.: probable mucosal damage may contraindicate the use of gastric lavage. If in eyes, flush eyes with water. Get medical attention. If on skin, wash with soap and water. Get medical attention. If inhaled, remove victim to fresh air. If not breathing, give mouth-to-mouth respiration. Get medical attention.

ENVIRONMENTAL HAZARD
This product is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL
HAZARD
FLAMMABLE. Do not use or store near heat or open flame.

E.P.A. Registration #7995-
E.P.A. Est. #7995-MA-1

Rule Paint and Chemical, Inc.
Gloucester, Massachusetts 01930 U.S.A.

®Rule Registered Trademark

ACCEPTED
with COMMENTS
In EPA Letter Dated:
JUL 29 1985
Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 7995-52