


U.S. ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (WH-567) WASHINGTON, D.C. 20460	EPA REGISTRATION NO. 7995-53	DATE OF ISSUANCE JUL 29 1985
	TERM OF ISSUANCE	
NOTICE OF PESTICIDE: <input checked="" type="checkbox"/> REGISTRATION <input type="checkbox"/> REREGISTRATION (Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended)	NAME OF PESTICIDE PRODUCT Alumajacket 515 White	
	NAME AND ADDRESS OF REGISTRANT (Include ZIP code)	
P. O. Box 1000 & Chemical Co. Cape Ann Industrial Park Gloucester, MA 01930		
NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.		
On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.		
A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.		
Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.		
The registrant is advised that the following information is required by the Act:		
1. To submit analytical and other data required for registration/reregistration of your product under FIFRA Sec. 261(5) when the Agency requires registrants of similar products to submit such data.		
2. Make the following labeling changes, insofar as they apply to the product for shipment:		
a. Add the phrase "EPA Registration No. 7995-53."		
b. In the "Precautionary Statements"		
Delete the phrase, "May be harmful to sensitive persons" or similar data which indicate that the product causes this reaction.		
Expand the sentence "Wear protective clothing, e.g., gloves, hat, shirt, pants" to: "Wear protective clothing such as long-sleeved shirt, long pants, hat and gloves."		
Expand the sentence "Wash thoroughly after use and before eating or smoking" to: "Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse."		
<input checked="" type="checkbox"/> ATTACHMENT IS APPLICABLE		
SIGNATURE OF APPROVING OFFICIAL		DATE
BEST AVAILABLE COPY		

Add the phrase "Do not get in eyes or on clothing" after the words "Corrosive, causes skin burns."

- c. The words "Active Ingredients and Inert Ingredients" must be given equal prominence and they must be of the same type size. Use the words "Inert Ingredients" for "Inert."
 - d. The preferred declaration for the first active ingredient should be: "Tributyltin fluoride," note the spelling of word "fluoride."
 - e. The substatement to the second active ingredient should be enclosed in parenthesis: (As part of a polymer). Replace the word "copolymer" with "polymer."
 - f. The label should bear a statement below the ingredient statement "Contains petroleum distillates."
3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 Enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

John H. Lee 
Product Manager (31)
Disinfectants Branch
Registration Division (TS-767c)

Enclosure

RD/DIS: JOB: 91178: Lee: RD: 85/34: Kendrick & Co: 898-1270: 6/10/85: Del: 6/18/85: DKD

Rule

Gloucester

Marine Paints

Alumajacket 519 White

ACCEPTED
with COMMENTS
in EPA Letter Dated

JUL 29 1985

519 White
ONE U.S. QUART
946 ML

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
as amended, this pesticide
registered under EPA Reg. No.
7995-53

ACTIVE INGREDIENTS

Tri-n-butyltin Flouride	2.39%
Tributyltin Methacrylate as part of a Copolymer	11.40
Inert	86.21
Total	<u>100.00%</u>

DANGER

Keep out of reach of children.
See back panel for additional precautionary statements.

Gloucester Aluminum Boat and Outdrive Anti-Fouling Bottom Paint
This product is an anti-fouling protective paint, resistant to
algae, barnacles and other marine fouling.

It is a one-part epoxy-based Tri-n-butyltin Flouride paint designed
specifically to solve the problems of electrolysis between copper
ingredients and aluminum. While formulated for aluminum boats and
outdrives, it is fully as effective and useful on fiberglass and wood.

Directions for Use

It is a violation of Federal law to use this product in a manner
inconsistent with its labeling.

Aluminum: Bare aluminum should be cleaned and degreased with
Gloucester #551 Epoxy Thinner & Cleaner, lacquer thinner, or other
suitable product. Wipe dry. Sand with 80-grit sandpaper.
Immediately apply Gloucester #414 Wash Primer mixed with Activator
per label instructions.

On previously painted surfaces, may be applied over itself or most
hard anti-fouling paints. Test a small area for compatibility.
Before application sand old finish lightly with 90-grit paper.

Aluminum Outdrives: Follow directions above. May be applied over
most factory finishes.

BEST AVAILABLE COPY

Gloucester^R Anti-Fouling Bottom Paint

Fiberglass: New fiberglass must be dewaxed. Gloucester #551 Thinner & Cleaner is recommended for this purpose. Lacquer Thinner or other suitable solvent may be used. Sand with 80-grit sandpaper and prime with Gloucester B370 Epoxy Primer.

On previously painted surfaces, check for compatibility. Sand with 80-grit sandpaper. Old paints in poor condition should be stripped. Proceed as for new fiberglass.

Wood: New wood and previously painted bottoms need only be properly sanded. Apply three coats. The first coat may be reduced with no more than 10% Gloucester #551 Thinner & Cleaner.

Application Information

Stir thoroughly. Allow overnight drying between coats and before launching. Two coats are recommended for best results. Apply with short-nap roller or brush. Use only Gloucester #551 Thinner & Cleaner if thinning is necessary. Also use for cleaning brushes and equipment. Recommended application temperature is 65°-85°F. Application in temperatures below 60°F will unduly extend cure time. Average coverage is 250 sq. ft./gal.

Maintenance

Since man-made and natural pollution can reduce the effectiveness of all anti-foulant paint, it is recommended that the bottom paint be checked from time to time, and lightly scrubbed with a soft material.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage in disposal. Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or residue is a violation of Federal law. If these wastes cannot be disposed of according to label instructions, contact your State Pesticide or Environmental Control Agency, or the hazardous waste representative at the nearest EPA regional office for guidance. Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedure approved of by state and local authorities. Store in original tightly sealed container.

ACCEPTED
with COMMENTS
EPA Approved
Enter Date:

JUL 29 1985

PRECAUTIONARY STATEMENTS

Hazards to Humans and Domestic Animals.

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No.

DANGER

Use only with adequate ventilation. Corrosive; causes skin burns. May be dermal sensitizer. Wear protective clothing, e.g., gloves, hat, shirt, and pants. Causes irreversible eye damage and burns. May be fatal if swallowed or inhaled. Harmful if absorbed through skin. Do not breath vapors or spray mist. Wash thoroughly after use and before eating or smoking. When used in enclosed areas while spraying and/or sanding boat surface, wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Wear goggles, face shield, or safety glasses.

7985-53

Practical Treatment. If swallowed, promptly drink a large quantity of milk, egg whites, gelatin solution, or if not available, drink large quantities of water. Avoid alcohol. Get medical attention. Note to M.D.: probable mucosal damage may contraindicate the use of gastric lavage. If in eyes, flush eyes with water. Get medical attention. If on skin, wash with soap and water. Get medical attention. If inhaled, remove victim to fresh air. If not breathing, give mouth-to-mouth respiration. Get medical attention.

ENVIRONMENTAL HAZARD

This product is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARD

FLAMMABLE. Do not use or store near heat or open flame.

E.P.A. Registration #7995-
E.P.A. Est. #7995-MA-1

Rule Paint and Chemical, Inc.
Gloucester, Massachusetts 01930 U.S.A.

[®]Rule Registered Trademark

ACCEPTED
with COMMENTS
in EPA Letter Dated

JUL 29 1985

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
as amended, for the pesticide
registered under EPA Reg. No.

7995-53