

ACCEPTED
SEP 23 1992

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under EPA Reg. No. **7995-S3**

rule

SUPER HARD, SMOOTH
EPOXYCOP-TF

KL-990
ANTI-FOULING COATING

KEEP OUT OF REACH OF CHILDREN
WARNING


SEE BACK PANEL FOR ADDITIONAL PRECAUTIONS & DIRECTIONS

ONE U.S. GALLON
3.79 LITERS

BLUE K61TF

ACTIVE INGREDIENTS	58.80%
INERT INGREDIENTS	41.20%
TOTAL	100.00%

CONTAINS PETROLEUM DISTILLATES



KL-990[®] Super Epoxycop-TF

A high-performance, anti-fouling coating with excellent resistance to algae, barnacles and other marine fouling. Super Epoxycop-TF uses high levels of cuprous oxide in a tough epoxy coating to provide superior anti-fouling protection for all types of boats in fresh and salt water.

Directions for Use:

It is a violation of federal law to use or dispose of this product in a manner inconsistent with its labeling:

New Fiberglass—No Sanding: Thoroughly clean with 702 Dewaxer, lifting the solvent, wax and contaminants off the surface with clean rags.

Apply one thin coat of 179 No Sanding Primer, allow to dry a minimum of one hour and a maximum of four hours, then apply two coats of KL-990 Super Epoxycop-TF by brush, roller or spray.

New Fiberglass—Epoxy Barrier Coat: Thoroughly clean with 702 Dewaxer, lifting the solvent, wax and contaminants off the surface with clean rags.

Abrade with 80 grit sandpaper, then seal with two coats of B370 Two-part Epoxy Primer. Sand between coats and before applying the anti-fouling coating (to improve adhesion). Apply two coats of KL-990 Super Epoxycop-TF by brush, roller or spray.

New Wood: Sand with 80 grit sandpaper, clean thoroughly and apply two coats of KL-990 Super Epoxycop-TF by brush, roller or spray.

Metal: Super Epoxycop-TF contains cuprous oxide and is not recommended for aluminum surfaces.

Iron and steel should be cleaned to bright metal and then sealed with two coats of anticorrosive primer such as B374 Red Lead Epoxy. Apply two coats of Super Epoxycop-TF by brush, roller or spray.

Previously Painted Surfaces: Hard epoxy and vinyl bottom paints that are in good condition can be abraded with 80 grit sandpaper and then over-coated with KL-990 Super Epoxycop-TF. Soft bottom paints and coatings that are cracked, damaged or peeling should be completely removed and the surface treated as if new.

Application Information

Mix thoroughly. Allow to dry at least overnight between coats and before launching. For best results, apply at least two coats. Apply by spray, short-nap roller or brush. Use 551 Hi-Solvency Thinner & Cleaner for brushing and to clean equipment. Use 716 Spray Thinner to spray. Recommended application temperature range is 65°-80°F. Expected coverage is 350 to 400 square feet per gallon.

Maintenance

Physical damage, fuel spills and pollution can reduce the effectiveness of anti-fouling coatings. Therefore, it is recommended that the bottom be inspected periodically. Regular use or light scrubbing with a soft brush will help maintain a clean bottom.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Store antifouling coatings in their original, tightly sealed containers.

PESTICIDE DISPOSAL

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or residue is a violation of federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

PRECAUTIONARY STATEMENTS

Hazardous to Humans and Domestic Animals

WARNING

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes, or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray mist. Wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

Statement of Practical Treatment

- If Swallowed:** Drink promptly a large quantity of water. Avoid alcohol. Get medical attention.
- If In Eyes:** Flush with plenty of water. Get medical attention.
- If On Skin:** Wash with plenty of soap and water. Get medical attention.
- If Inhaled:** Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

ENVIRONMENTAL HAZARD

This product is toxic to fish and other marine life. Do not apply directly to the water during cleaning or disposal of wastes. Do not allow chips or dust generated during paint removal to enter the water. Dispose of debris in an approved landfill.

Physical or Chemical Hazard COMBUSTIBLE

Do not use or store near heat or open flame
E.P.A. Registration #7995-55
E.P.A. Est. #7995-MA-1

Rule Industries, Inc.
Cape Ann Industrial Park
Gloucester, MA 01930. U S A

*Rule Registered Trademark

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of Rule Industries, Inc. including surface preparation, proper application and environmental conditions. Therefore, Rule Industries, Inc. cannot guarantee the suitability of this product for your particular application. Limited warranties of fitness for a particular purpose and of merchantability are excluded. Rule Industries, Inc. shall not under any circumstances be liable for incidental or consequential damages. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at the option of Rule Industries, Inc.

