

U.S. ENVIRONMENTAL PROTECTION AGENCY  
OFFICE OF PESTICIDES PROGRAMS  
REGISTRATION DIVISION (TS-767)  
WASHINGTON, DC 20460

**NOTICE OF PESTICIDE:**

☒ REGISTRATION  
☐ REREGISTRATION

(Under the Federal Insecticide, Fungicide,  
and Rodenticide Act, as amended)

EPA REGISTRATION NO.

7995-66

DATE OF ISSUANCE

TERM OF ISSUANCE

SEP 10 1990

NAME OF PESTICIDE PRODUCT

KL-990 Polycon TF Blue

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

Kalo Industries, Inc.  
One Ann Industrial Park  
Ann Arbor, MI 48106

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

1. Submit to all States required for registration/reregistration of your product under FIFRA section 3(c)(5) when the Agency requires all registrants of similar products to submit data.

2. Make the labeling changes listed below before you release the product for shipment:

3. Please refer to the labeling changes to the label of the product under the label movement program Notice dated May 11, 1986 enclosed.

4. The submitter must submit storage and stability data for the product for 12 months at 25°C acceptable on an interim basis. The results of the 12-month storage stability test must be received by the Agency within 12 months of the date of this Registration Notice.

5. Submit five copies of your final printed labeling before you release the product for shipment. Refer to the A-79 enclosure for a full description of final printed labeling.


☒ ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL

DATE

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

John H. Lee   
Product Manager (31)  
Antimicrobial Program Branch  
Registration Division (H7505C)

Enclosures

PM 31 77

 rule

**EXTRA POTENT**  
**POLYCC**  
**KL-990**  
**ANTI-FOULING COATING**

A Unique Formulation  
For Superior Performance  
In Waters Everywhere

**WARNING**  
KEEP OUT OF REACH OF CHILDREN  
SEE BACK PANEL FOR ADDITIONAL  
PRECAUTIONARY STATEMENTS

ONE U.S. GALLON  
(3.79 LITERS)

F<sup>TM</sup>**KL-990® Polycop-TF™**

A unique tin-free anti-fouling coating that inhibits the attachment of algae, barnacles and other marine fouling. KL-990 Polycop-TF provides effective anti-fouling protection for fiberglass, wood and steel hulls, in fresh and salt water.

This unique ablating coating is designed to be self-polishing, and becomes smoother and more efficient with use. There is no build up of old material and residual coating can be removed during haul out with a high pressure hose.

**Directions for Use**

It is a violation of federal law to use or dispose of this product in a manner inconsistent with its labeling.

**New Fiberglass - No Sanding:**

Thoroughly clean with 551 Hi-Solvency Thinner & Cleaner, lifting the solvent, wax and contaminants off the surface with clean rags.

Apply one thin coat of 179 No Sanding Primer, allow to dry a minimum of one hour and a maximum of four hours. Apply two coats of KL-990 Polycop-TF by brush, roller or spray.

**New Fiberglass - Epoxy Barrier Coat:**

Thoroughly clean with 551 Hi-Solvency Thinner & Cleaner, lifting the solvent, wax and contaminants off the surface with clean rags.

Abrade with 80 grit sandpaper, then seal with two coats of 8370 Epoxy Primer.

Sand between coats and before applying the anti-fouling coating to improve adhesion. Apply two coats of KL-990 Polycop-TF by brush, roller or spray.

**New Wood:** Sand with 80 grit sandpaper, clean thoroughly and apply two coats of KL-990 Polycop-TF by brush, roller or spray.

**Metal:** Iron and steel should be cleaned to bright metal and then sealed with two coats of an anticorrosive primer such as 8374 Red Lead Epoxy. Apply two coats of Polycop-TF by brush, roller or spray.

Polycop-TF contains cuprous oxide and is not recommended for aluminum surfaces unless they are fully protected by a barrier coat.

**Previously Painted Surfaces:** KL-990 Polycop-TF can be applied over most other hard and soft coatings so long as they are clean and in good condition. Coatings that are cracked, damaged or peeling should be completely removed before painting.

**Application Information**

Mix thoroughly. Allow to dry at least six hours between coats and before launching. For best results, apply at least two coats by spray, short-nap roller or brush. If necessary, thin with up to 10% mineral spirits. Use mineral spirits for cleanup. Paint only when the surface temperature is 50° or above. Expected coverage is 350 to 400 square feet per gallon.

**Maintenance**

Physical damage, fuel spills and pollution can reduce the effectiveness of anti-fouling coatings. Therefore, it is recommended that the bottom be inspected periodically. If necessary, clean with a soft towel. Never use a stiff brush, scrub pad or abrasive cleaning tools to maintain KL-990 Polycop-TF anti-fouling coatings.

KL-990 Polycop-TF can be applied over most other bottom paints so long as they are sound and undamaged.

**Storage and Disposal**

Do not contaminate water, food or feed by storage or disposal. Store anti-fouling coatings in their original tightly-sealed containers.

**Pesticide Disposal**

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

**Container Disposal**

Do not reuse empty container. Rinse empty container thoroughly and discard in trash, or by other procedures approved by State or local authorities.

**PRECAUTIONARY STATEMENTS**

Hazardous to Humans and Domestic Animals.

**WARNING**

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled.

Do not breathe dust, vapor or spray mist. Wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

**Practical Treatment**

If swallowed: prompt drink a large quantity of milk, egg-white or gelatin solution. If not available, drink large quantities of water. Avoid alcohol and get medical attention.

If in eyes: Flush with large amount of water. Get medical attention.

If on skin: Wash with soap and water. Get medical attention.

If inhaled: Remove victim to fresh air. If not breathing, give mouth-to-mouth respiration. Get medical attention immediately.

**ENVIRONMENTAL HAZARD**

This product is toxic to fish and other marine life. Do not apply directly to the water during cleaning or disposal of wastes. Do not allow chips and dust generate during paint removal to enter the water. Dispose of paint debris in an approved landfill.

**PHYSICAL OR CHEMICAL****HAZARD**

Combustible. Do not use or store near heat or open flame.

E.P.A. Registration #795-1A

E.P.A. Est. #7995-MA

Rule Industries, Inc.

Cape Ann Industrial Park  
Gloucester, Massachusetts 01930 U.S.A.

\* Rule Registered Trademark

© Property of Rule Industries, Inc.

4074