PM 31 7995-68 PT 174

US ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (75-767)
WASHINGTON OC 20460

7995-68

PA REGISTRATION NO.

TERM OF ISSUANCE

NOV 0 1 1994

Komposition II

NAME AND ADDRESS OF REGISTRANT (Include 21P code)

1

Rule Industries, Inc Cape Ann Industrial Park Gloucester, MA 01930

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance With FIFRA sec. 3(c)(7)(A) provided that you:

- 1. Submit/cite all data required for registration/ reregistration of your product under FIFRA section 3(c)(5) When the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4.
- 2. Make the labeling changes listed below before you release the product for shipment:
  - a. Add the phrase "EPA Registration No. 7995-68".
  - b. Add the letter "s" to the heading: Environmental Hazard.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

ATTACHMENT IS APPLICABLE	
SIGNATURE OF APPROVING OFFICIAL	DATE

A stamped copy of the label is enclosed for your records.

Sincerely,

Marshall Swindell

Acting Product Manager (31)

Antimicrobial Program Branch

Registration Division (H7505C)

CONCURRENCES SYMBOL SURNAME DATE

EPA Form 1320- A (1/90)

Printed on Recycled Paper

OFFICIAL FILE COPY



## KOMPOSITION



II Komposition is water-based modified acrylic copolymer. This ablative coating inhibits the attachment algae, barnacles and Zebra mussels. Komposition II provides effective antifouling protection for wood and steel hulls in fiberglass, fresh and salt water. Komposition II is easy to apply and dries quickly. It used over old antifouling coatings in good condition.

For commercial and non-commercial use. For use on boats and vessels only.

DIRECTIONS FOR USE

The second secon

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

Mixing: Mix thoroughly, preferably with a shaker of drill.

Thinning: Apply Komposition II without thinning to assure proper film thickness.

Coverage: Theoretical coverage is 400 sq. ft. per gallon. For maximum protection, apply 2 coats.

Overcoat and dry times:

Allow 1 hour dry time between coats. Allow 12 hours before launching.

Clean-up: Fresh water

APPLICATION INFORMATION

New Fiberglass-No Sanding:

Thoroughly clean with 702 Dewaxer, lifting the solvent, wax and contaminants of the surfaces with clean rags. Apply one thin coat of 179 No Sanding Primer and allow to dry a minimum of 1 hour and a maximum of 4 hours. Then apply 2 coats of Komposition II by brush roller or spray

Fiberglass- Epoxy Barrier Coat:

moroughly clean with 702 Dewaxer, lifting the solvent, Wax and contaminants of the surface with clean Abrade with 80 grit sandpaper, dewax again, then seal with 4 coats of Two-Part Epoxy Primer. Sand between coats and before applying the antifouling coating improve adhesion. Apply 2 coats of Komposition II by brush roller or spray.

Steel:

clean to bright metal and then seal with 2 coats of anti-corrosive primer such as B374 Epoxy. Apply 2 coats of Komposition II by brush, roller or spray. Komposition II contains cuprous oxide and is not recommended for aluminum surfaces unless they are fully protected by a barrier coat.

Previously Painted Surfaces:

If the previous coating is in good condition, abrade with 80 grit sandpaper, apply 2 coats of Komposition II by brush, roller or spray. Coatings that are cracked, damaged or peeling should be completely removed before painting.

Storage and Disposal

Do not contaminate water, food or feed by storage or disposal. Store anti-fouling coatings in their original tightly-sealed containers.

Pesticide Disposal

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**Container Disposal** 

Do not reuse empty container. Rinse empty container thoroughly and discard in trash, or by other procedures approved by State or local authorities.

PRECAUTIONARY STATEMENTS

Hazards to Humans and Domestic Animals.

WARNING

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, tong-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor, or spray mist.

While spraying paint

and/or sanding boat surfaces, Wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

Statement of Practical Treatment

If swallowed. Promptly drink a large quantity of water. Avoid alcohol and get medical attention.

If In eyes. Flush with plenty of water. Get medical attention.

If on skin. Wash with soap and water. Get medical attention.

If inhaled. Remove victim to fresh air. If not breathing, give mouth-to-mouth respiration. Get medical attention immediately.

## ENVIRONMENTAL HAZARD

This product is toxic to fish Do not apply directly to the water during cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter the water. Dispose of paint debris in an approved landfill.

E.P.A. Registration #7995-E.P.A. Est. #7995-MA-1 Rule Industries, Inc. Cape Ann Industrial Park Gloucester, Massachusetts 01930 U.S.A.

Rule Registered Trademark

BEST AVAILABLE COPY