

NOTICE OF PESTICIDE: ☒ REGISTRATION
☐ REREISTRATION
(Under the Federal Insecticide, Fungicide
and Rodenticide Act, as amended)

NAME OF PESTICIDE PRODUCT

Super KL II

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

Rule Industries
Cape Ann Industrial Park
L Gloucester, MA 01930

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit/cite all data required for registration/reregistration of your product under FIFRA section 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4.

2. Make the labeling changes listed below before you release the product for shipment:

a. Add the phrase "EPA Registration No. 7995-69."

Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

☐ ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL

A stamped copy of the label is enclosed for your records.

Sincerely,



Walter Francis
Acting Product Manager (31)
Antimicrobial Program Branch
Registration Division (7505)

Enclosures

rule®

SUPER

KL-II

ACCEPTED
WITH COMMENTS
IN EPA LETTER 12824

JAN 30 1995

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
as amended, for the pesticide
registered under EPA Reg. No.

1995-69

KL-990
ANTI-FOULING COATING

KEEP OUT OF REACH OF CHILDREN!
WARNING

SEE BACK PANEL FOR ADDITIONAL
PRECAUTIONARY STATEMENTS

NET CONTENTS

ONE U.S. GALLON
3.79 LITERS

ACTIVE INGREDIENT

Cuprous Oxide

INERT INGREDIENT

TOTAL

Total Copper Mo

BEST AVAILABLE COPY

BEST AVAILABLE COPY

SUPER KL II is a water-based modified acrylic copolymer. This ablative coating inhibits the attachment of algae, barnacles and Zebra mussels. Super KL II provides effective antifouling protection for fiberglass, wood and steel hulls in fresh and salt water. Super KL II is easy to apply and dries quickly. It can be used over old antifouling coatings in good condition.

For commercial and non-commercial use. For use on boats and vessels only.

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

- Mixing: Mix thoroughly, preferably with a shaker of drill.
- Thinning: Apply Super KL II without thinning to assure proper film thickness.
- Coverage: Theoretical coverage is 400 sq. ft. per gallon. For maximum protection, apply 2 coats.
- Overcoat and dry times: Allow 1 hour dry time between coats. Allow 12 hours before launching.
- Clean-up: Fresh water.

APPLICATION INFORMATION

New Fiberglass-No Sanding:

Thoroughly clean with 702 Dewaxer, lifting the solvent, wax and contaminants of the surfaces with clean rags. Apply one thin coat of 179 No Sanding Primer and allow to dry a minimum of 1 hour and a maximum of 4 hours. Then apply 2 coats of Super KL II by brush roller or spray.

New Fiberglass-Epoxy Barrier Coat:

Thoroughly clean with 702 Dewaxer, lifting the solvent, wax and contaminants of the surface with clean rags. Abrade with 80 grit sandpaper, dewax again, then seal with 4 coats of B370 Two-Part Epoxy Primer. Sand between coats and before applying the antifouling coating to improve adhesion. Apply 2 coats of Super KL II by brush roller or spray.

Steel:

Clean to bright metal and then seal with 2 coats of anti-corrosive primer such as B374 Epoxy. Apply 2 coats of Super KL II by brush, roller or spray. Super KL II contains cuprous oxide and is not recommended for aluminum surfaces unless they are fully protected by a barrier coat.

Previously Painted Surfaces:

If the previous coating is in good condition, abrade with 80 grit sandpaper, apply 2 coats of Super KL II by brush, roller or spray. Coatings that are cracked, damaged or peeling should be completely removed before painting.

Storage and Disposal

Do not contaminate water, food or feed by storage or disposal. Store anti-fouling coatings in their original tightly-sealed containers.

Pesticide Disposal

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinse is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

Do not reuse empty container. Rinse empty container thoroughly and discard in trash or by other procedures approved by state or local authorities.

PRECAUTIONARY STATEMENTS

Hazards to Humans and Domestic Animals.

WARNING

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor, or spray mist.

While spraying paint and/or sanding boat surfaces. Wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

Statement of Practical Treatment

If swallowed. Promptly drink a large quantity of water. Avoid alcohol and get medical attention.

If in eyes. Flush with plenty of water. Get medical attention.

If on skin. Wash with soap and water. Get medical attention.

If inhaled. Remove victim to fresh air. If not breathing, give mouth-to-mouth respiration. Get medical attention immediately.

ENVIRONMENTAL HAZARD

This product is toxic to fish.

Do not apply directly to the water during cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter the water. Dispose of paint debris in an approved landfill.

E.P.A. Registration #7995-

E.P.A. Est. #7995-MA-1

Rule Industries, Inc.

Cape Ann Industrial Park

Gloucester, Massachusetts 01930 U.S.A.

DISCLAIMER: The performance of any marine paint or coating depends on many factors, outside the control of Rule Industries, Inc. including surface preparation, proper application and environmental conditions. Therefore, Rule Industries, Inc. cannot guarantee the suitability of this product for your particular application. Implied warranties of fitness for a particular purpose and of merchantability are excluded. Rule Industries, Inc. shall not be liable for incidental or consequential damages by purchase or use of this product. Buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at the option of Rule Industries, Inc.

JAN 30 1985

7995-69

4-1