

DO NOT RE-USE CONTAINER. DESTROY WHEN EMPTY. DO NOT USE, POUR, SPILL OR STORE NEAR HEAT OR OPEN FLAME

*(Amur)*

UNDER THE FEDERAL INSECTICIDE  
FUNGICIDE AND RODENTICIDE ACT  
FOR ECONOMIC  
POISON REGISTRATION  
E. 7818

*Recorded as 1972*

# AMERCOAT

# 67

ACCEPTED

## PROTECTIVE COATINGS

## ANTI-FOULING

ACCEPTED WITH COMMENTS

### APPLICATION INSTRUCTIONS

**WOODEN HULLS:** All marine growth and loose paint must be removed by scraping and washing with fresh water. Allow hull to dry.

Stir thoroughly before use. Thin only if necessary, using Amercoat No. 65 Thinner. Do not use more than one pint of No. 65 Thinner for each gallon of Anti-Fouling.

Apply two coats of No. 67 Anti-Fouling by brush or spray, at a coverage not to exceed 300 square feet per gallon for each coat. Apply as heavily as possible. Allow to dry for at least one hour between coats, and for one or more hours before placing vessel in water. However, the Anti-Fouling will not be harmed if it is necessary for the vessel to be left out of the water for several weeks.

**STEEL HULLS:** No. 67 Anti-Fouling must be applied over a high quality anti-corrosive primer when used on steel hulls. No. 67 is not an anticorrosive in itself. Otherwise, application procedure for steel hulls is the same as for wooden hulls.

This product is intended to protect against marine growth such as algae, barnacles, Bryozoa, Pholads and teredos.

EPA Reg. No. 8120-3-AA

R4/72



### CAUTION: HARMFUL IF SWALLOWED. KEEP OUT OF REACH OF CHILDREN


**CAUTION:** This product is combustible and may cause skin and eye irritation. Keep away from heat and open flame. Keep container closed. Use with adequate ventilation. Avoid prolonged breathing of vapor. Avoid contact with skin or eyes. Do not take internally. In case of contact, immediately flush skin with plenty of water; for eyes, flush with plenty of water for at least 15 minutes and get medical attention. If used in confined areas, observe the following precautions to prevent hazards of fire or explosion or damage to the health: (1) circulate adequate fresh air continuously during application and drying, (2) use fresh air masks and explosion-proof equipment, (3) prohibit all flames, sparks, welding and smoking. See application instructions included with shipment for equipment and methods recommended for safe application procedure.

**WARRANTY:** We guarantee the standard quality of this material and its adherence to our published specifications, if any. However, as the use of the product is beyond our control, we expressly disclaim responsibility for its handling, use, storage, the results obtained or any injury or special indirect or consequential damage of any nature whatsoever, however caused.

No. 67 ACTIVE INGREDIENTS: Metallic Copper, Flaked. 15.0%  
INERT INGREDIENTS ..... 85.0%

100.0%

Flash Point ..... 85°F Tag Open Cup



CORROSION CONTROL DIVISION

Home Office: FREA, CALIFORNIA 92621

CONTENTS:  
1 U.S. GALLON  
(3.785 LITERS)