8120-26

7-18-2006

1þ

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, D.C. 20460

JUL 18 2006

SEPA United States Environmental Protection Office of Pesticide Programs

Ameron Coatings 1200 Bluegrass Lakes Parkway, Suite 100 Alpharetta, GA 30004

Attention: Mark Clements

Subject: Amercoat 275E EPA Registration No. 8120-26 Amendment Dated April 24, 2006

The amendment, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, is acceptable.

- Revised Product Labeling per PR Notice 2001-1

A stamped copy of the "accepted" product labeling is enclosed for your records.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely

11

Marshall Swindell Product Manager 33 Regulatory Management Branch 1 Antimicrobials Division (7510P)

Enclosure

Precautionary Statements – HAZARDS TO HUMANS (and Domestic Animals): Warning! Vapor and spray mist can be harmful; imitating to eyes, skin, mucous membranes and respiratory system. Can cause headache, nausea, dizziness, asphyxiation or lung injury. Can be harmful if inhaled or swallowed. Possible eye and skin burns or injury. Overexposure to spray mist can damage kidneys, liver and blood. FIRST AID - If inhaled:

- Move person to fresh air.
- If person is breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth to mouth, if possible.

If on skin or clothing:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.

If in eyes:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.

If swallowed:

- Call poison control center or doctor immediately for treatment advice.
- Have person sip a glass of water if able to swallow,
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give anything by mouth to an unconscious person.

Hygienic practices – Wash thoroughly after use and before eating, smoking or using washroom. Keep away from feed or food products. Launder contaminated clothing before use.

Physical or Chemical Hazards: Flammable. Keep away from heat, sparks, arc and open flame. Avoid breathing vapor, dust, spray mist or contact with eyes and skin. Use adequate ventilation during mixing, application and drying. Reports associate repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Wear protective equipment such as goggles,

> Ameron Coatings 11805 Vimy Ridge Road Little Rock, AR 72209 USA

Form 277E-05 (R9/97) Manufactured in U.S.A.

AMERON

AMERCOAT[®]

277E BLACK Antifouling

FOR USE IN COMMERCIAL SHIPYARDS ONLY

Made in accordance with formula 129 Active Ingredient: Cuprous oxide 55.2%

| 0001000 01100 | | ~~ | |
|-------------------|--|----|--------------|
| Inert Ingredient: | | | <u>44.8%</u> |
| - | | | 100.0% |
| _ | | | |

Copper as metallic: 60.5%

NOTE: This product contains a chemical/s known to the State of California to cause cancer, birth defects or other reproductive harm



KEEP OUT OF REACH OF CHILDREN. WARNING!

EPA Est. No.: 8120 AR-1 EPA Registration No.: 8120-26



111900 1910 999 119 *05*

BATCH: LR2005040349

5.00 GL

face protection, gloves, full protective clothing and properly positive-pressure, air-supplied respirator (TC 19C NIOSH/M during mixing, spraying and until all vapors and mists are go confined, poorly ventilated areas, use airline, hood-type resp and explosion- and spark-proof equipment. Welding and cuttir produce hazardous fumes and gases; follow the American Na Standard Z49.1, "Safety in Welding and Cutting."

Fire – Blanket flames with foam, CO_2 , dry chemical. NIOSH/MSHA certified, self-contained air-supplied respirators

Spillage – Eliminate all sources of ignition or sparks. Use absorbanup materials; place in separate, closed, metal container ar pose of in accordance with all applicable regulations.

Environmental Hazards – This material is toxic to fish. Do not directly to water by cleaning equipment, disposal of wastes. I allow chips and dust generated during paint removal to enter Dispose of paint debris in an approved landfill.

Directions for Use – It is a violation of Federal Law to use this uct in a manner inconsistent with its labeling. See Product Sheet for further use instructions.

Storage and Disposal: Store in cool, dry, well-ventilated area container closed and upright when not in use. Do not conta water, food or feed by storage or disposal.

Pesticide Disposal: Pesticide wastes are toxic. Improper disp this product or its rinsate is a violation of Federal Laws. If this uct cannot be disposed of by use according to label instru contact your State Pesticide or Environmental Control Age Regional EPA Office, Hazardous Waste.

Container Disposal: Triple rinse or equivalent. Then offer fo cling, reconditioning or puncture and dispose of in a landfill other approved state and local procedures.

WARRANTY - Refer to Ameron's product data sheet for Am warranty and application instructions for this product.

NONPHOTOCHEMICALLY REACTIVE

DOT: Paint UN: 1263 VOC: 324 g/L, 2.7 lbs/gal VOC/Thinned, 10E (1pt/gal) 384 g/L, 3.2 lbs/g HMIS: H3 F3 R0

Commodity No. 277ES90000 Net Contents: 5 U.S. Gallons (18.93 Liters)

| See other cautions on side panel and MSDS. Use only in accordance with instructions a | ccompanying shipment. Emergency (in case of spills or leaks) CHEMITHEC | (800) 424-93 |
|---|---|--------------|
| <u> </u> | ACCEPTED | |
| a se | JUL 18 2006 | |
| | Under The Reduced Anacesticide, Fungicide and Rodeshticide Act, as anancial, for the pesticide registered under FI20-2C | |