

1

C. D. Stevens
Aercon Protective Coatings Division
201 North Berry Street
Brea, CA 92621

Dear Mr. Stevens:

Subject: Antifouling Paint Label
Improvement Program
Aercoat 2439 Red, Antifouling
EPA Registration No. 8120-48
Your Application Dated October 27, 1982

The amendment referred to above, submitted in connection with registration under FIFRA sec. 3(c)(7)(A), is acceptable, provided that you:

1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data.

2. Make the labeling changes listed below before you release the product for shipment bearing the amended labeling:

a. Place active ingredient on the same line as tributyltin.

b. After ... methacrylate add:

(as part of a polymer)

3. Submit five (5) copies of your final printed labeling before you release the product for shipment.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product bearing the amended labeling constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely yours,

Richard F. Mountfort *RFM*
Product Manager (23)
Fungicide-Herbicide Branch
Registration Division (TS-767)

Enclosure

TS-767:Mountfort:DCR-04141:MANJ-1071C:hk:Raven:479-2013:11/8/82

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS
(& DOMESTIC ANIMALS)

DANGER

Corrosive. Causes irreversible eye damage and burns. Do not get in eyes, on skin, or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray mist. Wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

STATEMENT OF PRACTICAL TREATMENT

If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

If in eyes: Flush with plenty of water. Get medical attention.

If on skin: Wash with plenty of soap and water. Get medical attention.

FOR USE IN COMMERCIAL SHIPYARDS ONLY

AMERCOAT®

2438
Antifouling
Red

with comment

8120 48

Active Ingredients:	Tributyltin Methacrylate	9.32%
Inert Ingredients:	Cuprous Oxide	16.70%
Copper as Metallic:		73.98%
Total Tin as Metallic:		100.00%

KEEP OUT OF REACH OF CHILDREN
DANGER

STATEMENT OF PRACTICAL TREATMENT

If swallowed: Get medical attention.

If inhaled: Remove to fresh air. If breathing is labored, give artificial respiration.

If on skin: Wash with plenty of water.

If in eyes: Flush with plenty of water.

See Side Panel for Additional Precautionary Statements

EPA Est. No.: 8120 CA-1
EPA Registration No.: 8120-48
Net Contents: 5 U.S. GALLONS
18.9 LITERS

MANUFACTURED BY:

Ameron
Protective Coatings
Division

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS

Flammable. Keep away from heat and open flame. In case of spillage, eliminate all sources of ignition.

DIRECTIONS FOR USE - It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. See Product Data Sheet for further use instructions.

STORAGE AND DISPOSAL - Pesticide, spray mixture, or rinse water that cannot be used according to label instructions must be disposed of according to Federal or approved state procedures under Subtitle C of the Resource Conservation and Recovery Act.

Container - Triple rinse or equivalent. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

WARRANTY - Refer to Ameron's Product Data Sheet for Ameron's Warranty and Application Instructions on this product.

DOT: Paint, Liquid