

Received Oct 11, 88  
per PR-88-6  
Not reviewed.

8120-49  
PM 31  
1051

#### Precautionary Statements

**HAZARDS TO HUMANS (and Domestic Animals):** **Danger!**—Corrosive Causes irreversible eye damage and burns. Harmful if absorbed through skin, swallowed, or inhaled. Do not get in eyes, on skin, or clothing. Wear protective clothing such as goggles, gloves, long-sleeved cotton shirt, long pants, and hat. Wear a NIOSH/MSHA certified mask or respirator. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling. Do not breathe vapors, spray mist, or sanding dust. Use with adequate ventilation.

**STATEMENT OF PRACTICAL TREATMENT:** In case of contact immediately flush eyes or skin with plenty of water for at least 15 minutes. Get medical attention. For over-exposure to vapor, provide fresh air. If breathing is labored, give artificial respiration. Get medical attention. If swallowed, drink promptly a large quantity of milk, egg white, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

**NOTE TO PHYSICIAN:** Probable mucosal damage may contraindicate the use of gastric lavage.

**ENVIRONMENTAL HAZARDS**—This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

# AMERCOAT. 635

## Antifoulant

Active ingredients:	Tributyltin methacrylate (as part of polymer)	9.8%
	Tributyltin fluoride	1.1%
Inert Ingredients:		89.1%
		100.0%

Total Tin as metallic: 3.6%

Contains: Petroleum distillates

**KEEP OUT OF REACH OF CHILDREN**

## DANGER

See other cautions of side panels and Material Safety Data Sheet. Use only in accordance with instructions accompanying shipment.

EPA Est. No: 8120 AR-1

EPA Registration No: 8120-49

**FOR USE IN COMMERCIAL SHIPYARDS ONLY**

#### PHYSICAL OR CHEMICAL HAZARDS

**Flammable** Keep away from heat, sparks, arc and open flame. Use only with adequate ventilation during mixing, application and drying. Use absorbent cleanup material if spilled. For fires, blanket flames with foam CO<sub>2</sub>, dry chemical. Wear NIOSH/MSHA certified respirator.

**DIRECTIONS FOR USE**—See application instructions. It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

**STORAGE AND DISPOSAL**—Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Pesticide, spray mixture, or rinseate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State or local disposal authorities.

**Container**—Triple rinse (or equivalent) and dispose of in an approved landfill. Consult Federal, State, or local disposal authorities for approved alternate procedures.

**WARRANTY**—Refer to Ameron's product data sheet and application instructions for this product for Ameron's warranty.

**Photochemically Reactive**  
**DOT - Paint UN 1263**

VOC Amercoat 635	532 g/L
thinned	584 g/L

Commodity No.

# Ameron

Net Contents:

Form 5873-P (R9/88)  
Manufactured in U.S.A.

Protective Coatings Division • Home Office: 201 N. Berry Street, Brea, California 92621  
• J.F. Kennedylaan 7, 4191 MZ Geldermalsen, The Netherlands