

Reg # 8120-49

PM-311

193

MAY 18 1989

Ameron Protective Coatings Division
201 North Berry Street
P.O. Box 1020
Brea, CA 92621

Attention: Mr. Kevin F. Brown

BEST AVAILABLE COPY

Gentlemen:

Subject: Amercoat 635 Antifouling
EPA Registration No. 8120-49
Your Application Dated November 11, 1988
EPA Received Date April 1, 1989

The amendment referred to above, submitted in connection with registration under section 3(c)(7)(A) of the Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA), is acceptable provided that you:

1. Submit/cite all data required for registration/reregistration of your product under FIFRA section 3(c)(5) when the agency requires all registrants of similar products to submit such data.
2. Before you release the product for shipment bearing the amended labeling submit an amended Confidential Statement of Formula for your product which demonstrates that your product is within certified limits for TBT release rate which places it within the release rate limit imposed by the Organotin Antifouling Paint Control Act of 1988. Your product was certified as being within the OAPCA limit by the Agency in its letter dated May 11, 1989.
3. Submit acceptable prototype specifications and materials for a certification and training program for the use/disposal and removal of TBT antifouling paints and paint wastes within 180 days from the date of your application to amend this registration. Your application was dated November 11, 1988. The prototype specifications and materials must be submitted by May 11, 1989. The minimum elements to be addressed in the certification and training program are identified in the Agency's Notice at 53 FR 39038.

54743:I:Lee:LL-19:KENCO:5/16/89:5/24/89:rw:gj:vo:rw

CONCURRENCES

SYMBOL							
SURNAME							
DATE							

4. Make the labeling changes listed below before you release the product for shipment bearing the amended labeling:
 - a. In the right panel:
 - 1) The sentence "It is a violation . . . labeling" should be immediately followed by the sentence "It is unlawful . . . surf vessel."
 - 2) This above second sentence should be immediately followed by the sentence "Users must comply"
 - 3) The paragraph "Putting . . . sanitary landfill" would follow next, ending with the sentence "See Application."
 - b. Place the restricted use paragraph at the top center of the front panel, see item (9a) of "The Label."
5. Submit one (1) copy of your final printed labeling before you release the product for shipment bearing the amended labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product bearing the amended labeling constitutes acceptance of these conditions. Any existing stock within your possession or control must be restrickered to bear labeling approved as part of your conditional registration; all new production must also bear such a label.

A stamped copy of the label is enclosed for your records. In order to be acceptable, your label must bear the changes listed at item 4 above.

Sincerely yours,

John H. Lee
 Product Manager (31)
 Antimicrobial Program Branch
 Registration Division (H7505C)

Enclosure

BEST AVAILABLE COPY

393

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS (and DOMESTIC ANIMALS): Danger! - Corrosive. Causes irreversible eye damage and burns. Harmful if absorbed through skin, swallowed, or inhaled. Do not get in eyes, on skin, or clothing. Wear protective clothing such as goggles, gloves, long-sleeved cotton shirt, long pants, and hat. Wear a MSHA/NIOSH certified mask or respirator. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling. Do not breathe vapors, spray mist, or sanding dust. Use with adequate ventilation.

STATEMENT OF PRACTICAL TREATMENT: In case of contact immediately flush eyes or skin with plenty of water for at least 15 minutes. Get medical attention. For overexposure to vapor, provide fresh air. If breathing is labored, give artificial respiration. Get medical attention. If swallowed, drink promptly a large quantity of milk, egg white, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

ENVIRONMENTAL HAZARDS - This material is toxic to fish. Do not apply directly to water by cleaning of equipment, or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

COMMODITY NO.

Form 5873 (R2/88)
Manufactured in USA

NET CONTENTS:

**AMERCOAT®
635
ANTIFOULING**

Active Ingredients: Tributyltin methacrylate (as part of polymer) 9.8%
Tributyltin fluoride 1.1%
Inert Ingredients: 89.1%
100.0%

Total Tin as metallic: 3.6%
Contains Petroleum Distillates

KEEP OUT OF REACH OF CHILDREN

DANGER

See other cautions on side panels. Use only in accordance with instructions accompanying shipment.

Restricted Use Pesticide due to toxicity to Aquatic Organisms including shellfish: For sale only to certified commercial applicators and for use only by persons under the direct supervision of an on-site (at the work site) certified commercial applicator. These restrictions become effective on March 1, 1990.

During and after paint removal and/or application of new TBT paint, methods must be employed which are designed to prevent release of TBT paints into the aquatic environment. Following removal of old TBT paint and/or application of new TBT paint, all paint chips and spent abrasives, paint containers, unused paint, and any other waste products from paint removal or application must be disposed of in a sanitary landfill.

EPA Est. No: 8120 CA-1
EPA Registration No: 8120-49

FOR USE IN COMMERCIAL SHIPYARDS ONLY

AMERON®
Protective Coatings Division
Home Office: 201 N. Berry Street,
Anaheim, California 92621

PHYSICAL OR CHEMICAL HAZARDS: Flammable. Keep away from open flame, arc and open flame. Use with adequate ventilation. Upon application and cleanup material may ignite. Blanket flame resistant chemical. Wear respirator.

DIRECTIONS FOR USE: See instructions. Federal Law to be observed in manner inconsistent with this label.

STORAGE AND DISPOSAL: Store closed when not in use. Store in a dry, well-ventilated area. Do not contaminate water. Storage or disposal of this product must conform with applicable regulations. Disposal: See instructions. Improper disposal of this product may result in environmental contamination. If this product is used according to instructions, contact your local Environmental Regional EPA Office for Container Disposal instructions. Dispose of in accordance with applicable regulations.

WARRANTY - See data sheet for application instructions. Product.

It is unlawful to use this product on non-aluminum hulls less than 25 feet (7.6 meters) in length except for the drive unit of a motorboat.

Users must comply with OSHA requirements.

DOT-Paint UN 1993
PHOTOCHEMICAL RISK

BEST AVAILABLE

ACCEPTED
WITH COMMENTS
BY EPA LABORATORY

MAY 18 1989

For information only
Do not use for labeling

8120-49