

pm 3  
8120-54  
U.S. ENVIRONMENTAL PROTECTION AGENCY  
OFFICE OF PESTICIDES PROGRAMS  
REGISTRATION DIVISION (TS-767)  
WASHINGTON, DC 20460

EPA REGISTRATION NO.  
8120-54

DATE OF ISSUANCE  
JAN 28 1992

TERM OF ISSUANCE

NOTICE OF PESTICIDE:  REGISTRATION  
 REREGISTRATION  
(Under the Federal Insecticide, Fungicide,  
and Rodenticide Act, as amended)

NAME OF PESTICIDE PRODUCT  
Amercoat 3224 Aerosol  
Antifoulant

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

Ameron  
Protective Coatings Division  
201 N. Berry Street  
Brea, CA 92622-1020

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others. This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit/cite all data required for registration/reregistration of your product under FIFRA section 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4.

At present, the data requirements specified in the following documents are among the data requirements applicable to your registration and for which you are required to select satisfactory methods of compliance and to inform the Agency of such selection and to comply with all deadlines on a schedule consistent with that required of other registrants of similar products as required by FIFRA section 3(c)(7)(A).

This registration is subject to the Data Call-In requirements including, but not limited to, those specified in the January 31, 1985 Data Call-In Notice on Tributyltin, the July 29, 1986 Data Call-In Notice on Tributyltin, August 13, 1987 Data Call-In Notice on Tributyltin, the August 26, 1987 Data Call-In Notice, the March 26, 1989 Data Call-In Notice for TBT Monitoring and Product Efficacy Data, and the Reregistration Data Requirements Packages for products containing TBT issued 1990 and 1991.

ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL

DATE

2. Make the labeling changes listed below before you release the product for shipment:

- a. Add the phrase "EPA Registration No. 8120-54".
- b. Revise the "If Swallowed" statement to read "If swallowed, drink promptly a large quantity of water. Avoid Alcohol. Get medical attention."
- c. Include the following statement immediately after the heading "Directions For Use" and before the misuse statement (i.e., It is unlawful to. . . its labeling.):  
"This product may only lawfully be used on aluminum outdrives and outboards."
- d. Change "Bare Aluminum" to "Bare Aluminum Outdrives and Outboards".
- e. Revise your Container Disposal statement to read "Do not puncture or incinerate. Wrap and discard in trash."

3. Before you release the product for shipment bearing the EPA registered labeling, you must submit an amended Confidential Statement of Formula for your product which demonstrates that your product is within the certified limits for TBT release rate which places it within the release rate limit imposed by the Organotin Antifouling Paint Control Act of 1988. Your product was certified as being within the OAPCA limit by the Agency in its letter dated February 26, 1991.


The release rate data submitted is accepted for certification purposes. Amercoat 3224 Aerosol Antifoulant has a certified average release rate of 3.55  $\mu\text{g}/\text{cm}^2/\text{day}$ .

4. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,



John H. Lee  
Product Manager (31)  
Antimicrobial Program Branch  
Registration Division (H7505C)

Enclosures

**Precautionary Statement**

**HAZARDS TO HUMANS (and Domestic Animals):**

**DANGER! - Corrosive.** Causes irreversible eye damage and burns. Harmful if absorbed through skin, swallowed, or inhaled. Do not get in eyes, on skin or clothing. Wear protective clothing such as goggles, gloves, long-sleeved cotton shirts, long pants, and hat. Wear a NIOSH/MSHA certified mask or respirator. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling. Do not breathe vapors, spray mist, or sanding dust. Use with adequate ventilation.

**STATEMENT OF PRACTICAL TREATMENT:** In case of contact: immediately flush eyes or skin with plenty of water for at least 15 minutes. Get medical attention. For overexposure to vapor, spray mist, provide fresh air. If breathing is labored, give artificial respiration. Get medical attention. If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

**NOTE TO PHYSICIAN:** Probable mucosal damage may contraindicate the use of gastric lavage.

**ENVIRONMENTAL HAZARDS:** This pesticide is toxic to aquatic organisms including fish and shellfish.

**PHYSICAL OR CHEMICAL HAZARDS:** Extremely flammable. Contents under pressure. Keep away from heat, sparks, arc and open flame. Do not puncture or incinerate container. Exposure to temperatures above 130°F may cause bursting. Use only with adequate ventilation during mixing, application and drying. Use absorbent cleanup material if spilled. For fires, blanket flames with foam, CO<sub>2</sub>, dry chemical. Wear NIOSH/MSHA certified air-supplied respirator.

**DIRECTIONS FOR USE:** It is unlawful to use this product on non-aluminum hulled vessels less than 82 feet (25 meters) in length (on deck) except for the outboard motor or lower drive unit of such vessel. Users must comply with all applicable OSHA requirements.

**NEW OUTDRIVE UNIT:** Lightly sand the factory paint to dull the surface, clean with thinner and apply two coats of Amercoat 3224 allowing four hours dry time between coats.

# AMERCOAT® 3224 Aerosol Antifoulant For Aluminum Outdrives and Outboards

Active ingredients: Tributyltin methacrylate (as part of polymer)	4.7%
Inert Ingredients:	95.3%
	100.0%

Total Tin as metallic: 1.5%  
Contains Petroleum Distillates

**DANGER  
EXTREMELY FLAMMABLE  
CONTENTS UNDER PRESSURE**

EPA Est. No.: 8120 CA-1  
EPA Registration No.: 8120

**KEEP OUT OF REACH OF CHILDREN  
NOT FOR RESIDENTIAL USE.**

**OUTDRIVES PREVIOUSLY ANTIFOULING PAINT:** Lightly sand the surface, clean with thinner and apply two coats of Amercoat 3224 allowing four hours dry time between coats.  
**BARE ALUMINUM:** If the old paint is not removed, the bare metal, it must be primed with a zinc-rich primer. A one square inch can be spot primed with Amercoat 3224.  
**LAUNCH TIME:** Any time after Amercoat 3224.

**APPLICATION:** Shake can for 30 seconds before use. Spray begins to rattle. Hold can 10-12 inches from surface. Depress nozzle and spray with short bursts.

**STORAGE AND DISPOSAL:** Keep out of reach of children. Do not use. Store in cool, dry, well-ventilated area. Do not contaminate water, food or feed. Dispose of in a sanitary landfill. Follow State or local regulations, handling and disposal instructions. Manage other waste materials from reapplication in accordance with State or local regulations, handling and disposal instructions. Manage other application wastes in accordance with State, and local requirements. Consult your State or Environmental Control Agency, the RCRA/ Superfund Office, or the RCRA/ Superfund Office for waste disposal guidance. Do not reuse container if intended for other use. Empty paint containers with residue must be disposed of in accordance with Federal, State or local regulations (a hazardous waste).

**PHOTOCHEMICALLY CURABLE  
DOT - Paint  
VOC: 770 g/L, 6.4 lbs/gal**

Commodity No.



Form 6229 (9/91)  
Manufactured in U.S.A.

Protective Coatings Division • Home Office: 201 N. Berry Street, Brea, California  
• J.F. Kennedylaan 7, 4191 MZ Geldermalsen, The Netherlands