

Reg # 8120-54

PM-31

1/9/

Precautionary Statement

HAZARDS TO HUMANS (and Domestic Animals):

DANGER! - Corrosive. Causes irreversible eye damage and burns. Harmful if absorbed through skin, swallowed, or inhaled. Do not get in eyes, on skin or clothing. May be a dermal sensitizer. Wear protective clothing such as goggles, gloves, long-sleeved cotton shirts, long pants, and hat. Wear a NIOSH/MSHA certified mask or respirator. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling. Do not breathe vapors, spray mist, or sanding dust. Use with adequate ventilation.

STATEMENT OF PRACTICAL TREATMENT: In case of contact: immediately flush eyes or skin with plenty of water for at least 15 minutes. Get medical attention. For overexposure to vapor, spray mist, provide fresh air. If breathing is labored, give artificial respiration. Get medical attention. If swallowed, drink promptly a large quantity of water. Avoid alcohol. Get medical attention.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to aquatic organisms including fish and shellfish.

PHYSICAL OR CHEMICAL HAZARDS: Extremely flammable. Contents under pressure. Keep away from heat, sparks, arc and open flame. Do not puncture or incinerate container. Exposure to temperatures above 100 F may cause bursting. Use only with adequate ventilation during application and drying. Use absorbent cleanup material if spilled. For fires, blanket flames with foam, CO2, dry chemical. Wear NIOSH/MSHA certified air-supplied respirator.

DIRECTIONS FOR USE: This product may only lawfully be used on aluminum outdrives and outboards. It is unlawful to use this product on non-aluminum hulls (unless less than 52 feet (25 meters) in length (on deck) except for the outboard motor or lower drive unit of such vessel). Users must comply with all applicable OSHA requirements.

AMERCOAT® 3224 WHITE Aerosol Antifoulant For Aluminum Outdrives and Outboards

Active ingredients: Tributyltin methacrylate (as part of polymer) 4.7%
Inert ingredients: 95.3%
100.0%

Total Tin as metallic 1.5%
Contains Petroleum Distillates

DANGER EXTREMELY FLAMMABLE CONTENTS UNDER PRESSURE

EPA Est. No.: 8120 CA-1
EPA Registration No.: 8120-54

**KEEP OUT OF REACH OF CHILDREN
NOT FOR RESIDENTIAL USE.**

NEW OUTDRIVE UNIT: Lightly sand the factory paint to dull the surface, clean with thinner and apply two coats of Amercoat 3224 allowing four hours dry time between coats.

OUTDRIVES PREVIOUSLY PAINTED WITH ANTIFOULING PAINT: Lightly sand the old antifouling paint, clean with thinner and apply two coats of Amercoat 3224 allowing four hours dry time between coats.

BARE ALUMINUM OUTDRIVES AND OUTBOARDS: If the old paint has been chipped to bare metal, it must be primed. Smaller areas than one square inch can be spot primed.

LAUNCH TIME: Any time after overnight dry of last coat of Amercoat 3224.

APPLICATION: Shake can for one minute after mixing ball begins to rattle. Hold can 10-12 inches from surface. Depress nozzle and spray with smooth, even strokes.

STORAGE AND DISPOSAL: Keep container closed when not in use. Store in cool, dry, well-ventilated area. Do not contaminate water, food or feed by storage or disposal.

Pesticide Disposal: Paint chips, spent abrasives, and any other waste materials from removal of old paint must be disposed of in a sanitary landfill (or, if required by Federal, State or local regulations, handled as a hazardous waste).

If possible, use all of the contents by application according to label instructions. Manage excess paint, rinseate, and other application wastes in accordance with Federal, State, and local requirements. Consult your State pesticide or Environmental control agency, nearest EPA Regional Office, or the RCRA/Superfund Hotline (800-424-9346) for waste disposal guidance. **Container Disposal:** Do not puncture or incinerate. Wrap and discard in trash.

PHOTOCHEMICALLY REACTIVE
DOT - Paint UN - 1263
VOC: 770 g/L, 6.4 lbs/gal

Commodity No.



Net Contents:

Protective Coatings Division • Home Office: 201 N. Berry Street, Brea, California 92622-1020
• J.F. Kromm, Jan. 7, 1991 MZ Geldermalsen, The Netherlands

ACCEPTED
FEB 03 1994