

PM-33

Reg # 8120-56

9/4/97

193

## UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

SEP - 4 1997

Ameron International Corp.  
Protective Coatings Group  
201 North Berry Street  
Brea, California 92821

Attention: Marilyn Lindquist  
Consultant

Subject: Formula 121  
Marine Antifouling Paint Vinyl Red  
EPA Registration No. 8120-56  
Your Amendment Dated August 16, 1997

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, to reflect the new company name and product name changes, is acceptable. A stamped copy is enclosed for your records.

If you have any questions regarding this letter, please contact Pam Hasty at (703) 308-7933.

Sincerely,



Marshall Swindell  
Acting Product Manager 33  
Regulatory Management Branch I  
Antimicrobial Division (7510W)

CONCURRENCES							
SYMBOL	7510W						
SURNAME	P. Hasty						
DATE	9/4/97					SEP 4 1997	

273

Precautionary Statements  
**WARNING**

**Hazard to Humans and Domestic Animals**

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear a face shield and rubber gloves when handling. Use in a well ventilated area. When used in confined areas or applied by spraying, wear protective clothing and a pesticide respirator jointly approved by the Mining Enforcement and Safety Administration (formerly the U.S. Bureau of Mines) and by the National Institute for Occupational Safety and Health under the provisions of 30 CFR 11. May be fatal if swallowed or inhaled. Do not breathe vapors or spray mist.

**Practical Treatment**

In case of skin contact, remove contaminated clothing and immediately wash skin with soap and water. Get medical attention. Wash contaminated clothing before reuse. If swallowed, promptly drink a large quantity of milk or water. Avoid alcohol. Get medical attention. If in eyes, immediately flush with plenty of water. Get medical attention. If inhaled, remove to fresh air. Use artificial respiration if breathing has stopped. Get medical attention.

**Environmental Hazards**

This product is toxic to fish. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

**Chemical and Physical Hazards**

Do not use or store near heat or open flame.

MAF-3113

# DEVORE Formula 121

## Marine Antifouling Paint

Manufactured by **AMERON INTERNATIONAL CORPORATION**

FOR USE IN COMMERCIAL SHIPYARDS ONLY

# VINYL RED

Keep Out Of Reach Of Children

### WARNING

See side panel for precautionary statements

**Active Ingredients\***

Cuprous Oxide	68.97%
Inert Ingredients	31.03%
	100.00%

\*Equivalent to 61.24% Metallic Copper

VOC-275 GPL

Do not thin inconsistent with local VOC regulations  
**PAINT UN1263 5 U.S. Gallons (18.925 Liters)**  
EPA Reg. No. 8120-56 EPA Est. No. 8120-AP-4

**Directions f**  
It is a violation inconsistent wit

Devore Antifou steel, aluminur barnacles, alg Surface to be moisture. Do not coat should be is recommended brush or roller When sprayin approved resp goggles should should be lau Solvent. Launc dry, or later if c

**Storage an**  
Do not contam

**Pesticide Disp**  
of excess pes Federal Law. according to l Environment representative

**Container Dis**  
recycling of re by other appr

For U

Unde  
Fung  
amer  
regis



273

DEVOL

# Formula 121

## Marine Antifouling Paint

Manufactured by AMERON INTERNATIONAL CORPORATION

FOR USE IN COMMERCIAL SHIPYARDS ONLY

# VINYL RED

Keep Out Of Reach Of Children

### WARNING

See side panel for precautionary statements

VOC-275 GPL

Do not thin inconsistent with local VOC regulations  
PAINT UN1263 5 U.S. Gallons (18.925 Liters)  
EPA Reg. No. 8120-56, EPA Est. No. 8120-AR-1

Active Ingredients\*

Cuprous Oxide	68.97%
Inert Ingredients	31.03%
	100.00%

\*Equivalent to 61.24% Metallic Copper

### Directions for Use

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Devool Antifouling Paint—for application to underwater areas of steel, aluminum, fiberglass or wood vessels subject to fouling by barnacles, algae, tube worms and other fouling organisms. Surface to be coated should be clean of grease, oil, dirt and moisture. Do not apply directly to metal surfaces. A suitable barrier coat should be applied to steel and aluminum surfaces; a primer is recommended for fiberglass and wood surfaces. Apply by spray, brush or roller. For spray, airless spray is strongly recommended. When spraying, applicators must use appropriate NIOSH approved respirators. Protective clothing, rubber gloves and goggles should be worn by applicators. Contaminated clothing should be laundered before reuse. Clean up with Devool T-10 Solvent. Launching may be accomplished as soon as coating is dry, or later if desired.

### Storage and Disposal

Do not contaminate water, food or feed by storage or disposal.

Pesticide Disposal—Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Container Disposal—Triple rinse (or equivalent) and offer for recycling of reconditioning, or dispose of in a sanitary landfill, or by other approved State and local procedures.

For Use in Commercial Shipyards Only

ACCEPTED  
with COMMENTS  
in EPA Letter Dated:

SEP - 4 1997

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No. 8120-56



Emergency: In case of leaks or spills,  
call CHEMTREC: 800-424-9300.

**Ameron Protective Coatings Group**

201 N. Berry Street, Brea, California 92622-1020 U.S.A.  
J.F. Kennedylaan 7, 4191 MZ Geldermalsen, The Netherlands