

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

SEP - 4 1997

Ameron International Corp.
Protective Coatings Group
201 North Berry Street
Brea, California 92821

Attention: Marilyn Lindquist
Consultant

Subject: Super Tropical 280-S-2771
Marine Antifouling Paint 280
EPA Registration No. 8120-60
Your Amendment Dated August 16, 1997

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, to reflect the new company name and product name changes, is acceptable. A stamped copy is enclosed for your records.

If you have any questions regarding this letter, please contact Pam Hasty at (703) 308-7933.

Sincerely,

Marshall Swindell
Acting Product Manager 33
Regulatory Management Branch I
Antimicrobial Division (7510W)

CONCURRENCES

SYMBOL	7510W						
SURNAME	P. Hasty						
DATE	9/4/97						

Precautionary Statements

DANGER

Hazard to Humans and Domestic Animals

Corrosive. Causes skin burns and eye irritation. Harmful if absorbed through skin or inhaled. Do not get on skin, clothing or in eyes. May be a dermal sensitizer. Wear a face shield and rubber gloves when handling. Wear protective clothing, such as long sleeved cotton shirt, long pants and hat. Use in a well ventilated area. When used in confined areas or applied by spraying, wear protective clothing and a pesticide respirator jointly approved by the Mining Enforcement and Safety Administration (formerly the U.S. Bureau of Mines) and by the National Institute for Occupational Safety and Health under the provisions of 30 CFR 11. May be fatal if swallowed. If swallowed, promptly drink a large quantity of egg whites, gelatin solution or water. Avoid alcohol. Do not induce vomiting. Do not breathe vapors or spray mist.

Practical Treatment

In case of skin contact, remove contaminated clothing and immediately wash skin with soap and water. Get medical attention. Wash contaminated clothing before reuse. If inhaled, remove to fresh air. Use artificial respiration if breathing has stopped. Get medical attention. If swallowed, do not induce vomiting. This product contains petroleum distillates. Get medical attention. If in eyes, immediately flush with plenty of water. Get medical attention.

WARNING! This product contains a chemical known to the State of California to cause cancer.

Environmental Hazards

This pesticide is toxic to aquatic organisms including fish and shellfish. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

Chemical and Physical Hazards

Do not use or store near heat or open flame.

MAF-2771

For Use in Commercial Shipyards Only

DEVÖE

RESTRICTED USE PESTICIDE:

Due to Toxicity to Aquatic Organisms including Shellfish: For retail sale to and use only by Certified Applicators or persons under their direct supervision and only for those uses covered by the Certified Applicator's certification.

Super Tropical

280-S-2771

Manufactured by AMERON INTERNATIONAL Marine Antifouling Paint

280

Keep Out Of Reach Of Children

DANGER

See side panel for precautionary statements

VOC—315 GPL (2.63 Lb/Gal)

Do not thin inconsistent with local VOC regulations
PAINT UN1263 5 U.S. Gallons (18.925 Liters)

EPA Reg. No. 8120-60

EPA Est. No. 8120-AR-1

ACCEPTED
with COMMENTS
in EPA Letter Dated:

SEP - 4 1997

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No. 8120-60
Active Ingredients*

Cuprous Oxide	24.59%
Bis(tributyltin) Oxide	1.86%
Inert Ingredients	73.55%
	100.00%

*Equivalent to 21.83% Metallic
Copper and 0.74% Metallic Tin

Contains
Petroleum Distillates

Directions for Use
It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Do not use this product on aluminum hulls (on deck) except for the removal of old paint.

Users must comply with the following instructions:

During and after painting, methods must be employed to prevent the migration of TBT paints into the water. Do not use old TBT paint and/or spent abrasives in paint containers, unused paint removal or application.

Devöe Antifouling Paint is applied to steel, aluminum, fiberglass, and other surfaces. Surface to be coated must be clean and free of moisture. Do not apply in high humidity. A primer coat should be applied. This product is recommended for application by brush or roller. For spraying, an approved respirator and goggles should be worn. The paint should be laundered with water. Solvent. Launching should be done dry, or later if desired.

Storage and Disposal
Do not contaminate water.

Paint chips, spent abrasives, and removal of old paint are considered hazardous waste if required by Federal or State regulations.

If possible, use all of the instructions. Manage wastes in accordance with local, State, or Federal regulations. Consult your State or nearest EPA Region (800-424-9346) for waste disposal instructions.

Triple rinse containers. Empty paint containers should be disposed of in a safe manner in accordance with local or State regulations, if applicable.



AMERON INTERNATIONAL
2011
J.F.K.