UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

9/4/97

8120 -66

SEP - 4 1997

Ameron International Corp. Protective Coatings Group 201 North Berry Street Brea, California 92821

33

Attention: Marilyn Lindquist Consultant

Subject: ABC #2 2882-S-4754 Marine Antifouling Paint #2 Red EPA Registration No. 8120-66 Your Amendment Dated August 16, 1997

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, to reflect the new company name and product name changes, is acceptable. A stamped copy is enclosed for your records.

If you have any questions regarding this letter, please contact Pam Hasty at (703) 308-7933.

Sincerely,

Pam Hos & Por

Marshall Swindell Acting Product Manager 33 Regulatory Management Branch I Antimicrobial Divsion (7510W)

	CONCURRENCES	
SYMBOL 7510W		CED - 4 307
SURNAME P. A. GATA		
DATE 9/4/9		
EPA Form 1320-1A (1/90)	Printed on Recycled Paper	OFFICIAL FILE COPY

Precautionary Statements

DANGER

Hazard to Humans and Domestic Animals

Corrosive. Causes skin burns and eye irritation. Harmful if absorbed through skin or inhaled. Do not get on skin, clothing or in eyes. May be a dermal sensitizer. Wear a face shield and rubber gloves when handling. Wear protective clothing, such as long sleeved cotton shirt, long pants and hat. Use in a well ventilated area. When used in confined areas or applied by spraying, wear protective clothing and a pesticide respirator jointly approved by the Mining Enforcement and Safety Administration (formerly the U.S. Bureau of Mines) and by the National Institute for Occupational Safety and Health under the provisions of 30 CFR 11. May be fatal if swallowed. If swallowed, promptly drink a large quantity of egg whites, gelatin solution or water. Avoid alcohol. Do not induce vomiting. Do not breathe vapors or spray mist.

Practical Treatment

In case of skin contact, remove contaminated clothing and immediately wash skin with soap and water. Get medical attention. Wash contaminated clothing before reuse. If inhaled, remove to fresh air. Use artificial respiration if breathing has stopped. Get medical attention. If swallowed, do not induce vomiting. This product contains petroleum distillates. Get medical attention. If in eyes, immediately flush with plenty of water. Get medical attention.

WARNINGI This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Environmental Hazards

This pesticide is toxic to aquatic organisms including fish and shellfish. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

Chemical and Physical Hazards

Do not use or store near heat or open flame. MAF-4754



For Use in Commercial Shipyards Only



RESTRICTED USE PESTICIDE:

Due to Toxicity to Aquatic Organisms including Shellfish: For retail sale to and use only by Certified Applicators or persons under their direct supervision and only for those uses covered by the Certified Applicator's certification.

282-S-4754 Manufactured by AMEBON INTERNATIONAL Marine Antifoulting Paint

#2 RED

ACCEPTED with COMMENTS in EPA Letter Dated:

SEP - 4 1997

Under the Federal Insecticide, Fingicide, and Rodenticide Act as and, for the pesticide, ed under EPA Reg. No. Active Ingredients* Cuprous Oxide 37.92% Bis(tributyltin) Oxide 2.21% Inert Ingredients 59.87% 100.00% *Equivalent to 33.6% Metallic

Copper and 0.88% Metallic Tin

Contains Petroleum Distillates Directions for it is a violation of inconsistent with i nonaluminum hulled (on deck) except for vessel.

Users must compl

During and after pai methods must be e of TBT paints into old TBT paint and and spent abrasiv containers, unused removal or applic:

Devoe Antifouling steel, aluminum, i barnacles, algae, Surface to be co moisture. Do not ap coat should be ap is recommended for brush or roller. Fo When spraying, approved respirad goggles should be should be launde Solvent. Launchin dry, or later if desir

Storage and D Do not contaminat

Paint chips, spent removal of old pai if required by Fed hazardous waste).

If possible, use all o instructions. Mana wastes in accordan Consult your State nearest EPA Regi (800-424-9346) for

Triple rinse contai Empty paint conta be disposed of in a s or local regulations



VOC-375 GPL (3.13 Lb/Gal) Do not thin inconsistent with local VOC regulations PAINT UN1263 18.925 Liters (5 U.S. Gallons) EPA Reg. No. 8120-66 EPA Est. No. 8120-AR-1

Keep Out Of Reach Of Children

DANGER

See side panel for precautionary statements