

PRECAUTIONARY STATEMENTS **DANGÉR**

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

Keep Out of Reach of Children
Corrosive. Causes severe eye damage and skin damage.
Do not get in eyes, on skin, or on clothing. Wear goggles or
face shield and rubber gloves when handling. Harmful or
fatal if swallowed. Avoid contact with skin. Avoid contamnation of food.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not apply in marine and/or estuarine oil fields. Do not discharge into lakes, streams, ponds or public waters unless in accordance with NPDES permit. For guidance contact your local Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARDS

Do not use or store near heat or open flame

Directions for Use
It is a violation of Federal Law to use this
product in a manner inconsistent with its labeling

To control algae and bacterial slimes, use BACTRON KM-12 as directed. For best results, slug feed. The frequency of addition of microbiocide needed depends on many factors. To optimize your use of BACTRON KM-12 use the following procedure.

Recirculating Cooling Towers

- Initially use 16-24 fluid ounces per 1000 gallons of water to be treated (20-30 ppm active quaternary). Repeat the initial dose every seven days or increase the frequency, if needed
- When the above treatment level is successful, use 14-18 fluid ounces per 1000 gallons of water to maximize efficiency. Repeat weekly as needed.

(Continued on right side panel)

BACTRON KM-12

WATER TREATMENT MICROBIOCIDE FOR BUILDING AND INDUSTRIAL COOLING TOWERS AND OIL FIELD WATER FLOODS OR SALT WATER DISPOSAL SYSTEMS

Active Ingredient

Alkyl* dimethyl benzyl amonium chloride *alkyl (50% C., 40% C., 10% C.) 16%

Inert Ingredients

84% 100%

....

DANGER

Statement of Practical Treatment

In case of CONTACT, Immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before re-use.

If SWALLOWED, Drink promptly a large quantity of milk, egg whites, or gelatin solution. If these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

NOTE TO PHYSICIAN Probable mucosal damage inay contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression, and convulsion may be needed.

SEE LEFT PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

Champion Chemicals, Inc.

PO Box 450499 • Houston, Texas 77245 manufacturing address 115 Proctor, Odessa, Texas 79762

EPA Establishment No EPA Registration No 457 fbs. Net W 09133-TX-01 8133-19

55 U.S. gals Net Volume

(Continued from left side panel)

Cooling tower waters that are inherently low in algae growth and bacteria count may be adequately controlled by the lower range of these dosages. Stug feed every seven days

Oil Field Water Flood or Salt Water Disposal Systems:

- For the control of slime forming and sulfate reducing bacteria
 in oil field water flood or salt water disposal systems, add 2030 ppm (active) BACTRON KM-12 (7-10.3 gallons per 1000
 barrels of water) continuously. Levels for effective control will
 vary depending on conditions at the site.
- For intermittent use, dose at a rate of 6.25-7.5 gallons BACTRON KM-12 per 1000 barrels of water for four to eight hours per day, one to four times a week as needed to maintain control.

Add BACTRON KM-12 directly from the drum with the proper type of metering equipment.

STORAGE AND DISPOSAL

- 1 PROHIBITIONS—Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited. Do not reuse empty container.
- 2 PESTICIDE DISPOSAL—Pesticide, spray mixture, or rinsate that cannot be used or chemically processed should be disposed of in a landfill approved for pesticides
- 3 CONTAINER DISPOSAL—(a) Reseal container and offer for reconditioning, or (b) Triple rinse (or equivalent) and offer for recycling, reconditioning, or disposal in approved landfill
- 4 GENERAL—Consult Federal, State, or local disposal authorities for approved alternative procedures