

## PRECAUTIONARY STATEMENTS DANGER

### HAZARDS TO HUMANS AND DOMESTIC ANIMALS

Corrosive. Causes severe eye and skin damage. Harmful or fatal if swallowed. Do not get in eyes, on skin, or on clothing. Wear chemical goggles and rubber gloves when handling. Wash thoroughly with soap and water after handling. Avoid contamination of food.

### ENVIRONMENTAL HAZARDS

DO NOT discharge effluent containing this active ingredient into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. DO NOT discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

### PHYSICAL OR CHEMICAL HAZARDS

Do not use or store near heat or open flame.

## STORAGE AND DISPOSAL

**STORAGE** - Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited. Do not reuse empty container.

**PESTICIDE DISPOSAL** - Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**CONTAINER DISPOSAL** - Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or if allowed by state and local authorities, by burning. If burned, stay out of smoke.

# BACTRON K-24 MICROBIOCIDES

WATER TREATMENT MICROBIOCIDES  
FOR BUILDING AND INDUSTRIAL COOLING TOWERS  
AND OIL FIELD WATER FLOODS  
OR SALT WATER DISPOSAL SYSTEMS

#### Active Ingredients:

Alkyl\* dimethyl benzyl ammonium chloride 50%  
\*alkyl (50% C<sub>14</sub>, 40% C<sub>12</sub>, 10% C<sub>16</sub>)

#### Inert Ingredients:

CAS No: Mixture 50%  
100%

## KEEP OUT OF REACH OF CHILDREN DANGER

### STATEMENT OF PRACTICAL TREATMENT

In case of CONTACT, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician immediately. Remove and wash contaminated clothing before reuse.

If SWALLOWED, immediately give 3-4 glasses of milk; if unavailable, give water. Do not induce vomiting. Call a physician.

**NOTE TO PHYSICIAN:** Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression, and convulsion may be needed.

SEE LEFT PANEL FOR  
ADDITIONAL PRECAUTIONARY STATEMENTS

Manufactured By

 **Champion  
Technologies, Inc.**

3355 W. Alabama St. 4101  
Houston, TX 77098

EPA Establishment No.  
EPA Registration No.  
440 lbs. Net Weight

8133-TX-01  
8133-22  
55 U.S. gals Net Volume

## DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

To control algae and bacterial slimes use BACTRON K-24 MICROBIOCIDES as directed. For best results, slug feed. The frequency of addition of microbiocide needed depends on many factors. To optimize your use of BACTRON K-24 MICROBIOCIDES follow this procedure.

### RECIRCULATING COOLING TOWERS:

Initially use 5 1/2-8 fluid ounces per 1000 gallons of water to be treated (20-30 ppm active quaternary). Repeat the initial dose every seven days or increase the frequency, if needed.

When the above treatment level is successful, use 2-3 fluid ounces per 1000 gallons of water to maximize efficiency. Repeat weekly as needed.

Cooling tower waters that are inherently low in algae growth and bacteria count may be adequately controlled by the lower range of these dosages. Slug feed every seven days.

### OIL FIELD WATER FLOOD OR SALT WATER DISPOSAL SYSTEMS:

For the control of slime forming and sulfate reducing bacteria in oil field water flood or salt water disposal systems, add 5-10 ppm (active) BACTRON K-24 MICROBIOCIDES (1 1/2-3 gallons per 1000 barrels of water) continuously. Levels for effective control will vary depending on conditions at the site.

For intermittent use, dose at a rate of 1/2-2 gallons BACTRON K-24 MICROBIOCIDES per 1000 barrels of water for four to eight hours per day, one to four times a week as needed to maintain control.

Add BACTRON K-24 MICROBIOCIDES directly from the drum with the proper type of metering equipment.

CHEMICAL EMERGENCY CALL CHAMPION TECHNOLOGIES  
AT 713-431-2561 OR CHEMTREC AT 1-800-424-9300  
BEFORE USING, CONSULT MATERIAL SAFETY DATA SHEET

To request a Material Safety Data Sheet, please call (713) 431-2561 or write Champion Technologies, Inc., P.O. Box 450499, Houston, TX 77245-0499.

|                     |   |
|---------------------|---|
| HEALTH              | 3 |
| FIRE                | 2 |
| REACTIVITY          | 0 |
| PERSONAL PROTECTION |   |