

ACCEPTED

NOV - 8 1986

Under the
Registration Act as amended, for the
pesticide registered under
EPA Reg. No. 76

PREMIER #131 MICROBIOCIDES

ACTIVE INGREDIENT:

Potassium dimethyldithiocarbamate 20.0 %

INERT INGREDIENTS 80.0 %

This product contains 1.81 lb. of active ingredient per gallon and weighs 9.05 lb. per gallon.

KEEP OUT OF REACH OF CHILDREN
DANGER

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Irritant to eyes, nose and skin. Irritant to fish. Avoid contact with eyes, nose and skin. Wash thoroughly with soap and water after handling.

STATEMENT OF PRACTICAL TREATMENT: In case of contact with eyes, flush with water for 15 minutes. In case of contact with skin, wash with soap and water. In case of contact with clothing, remove clothing and wash separately.

Water pollution: Do not allow to be discharged into water.

ENVIRONMENTAL HAZARDS: Do not apply directly to fish, streams, ponds, lakes, or other aquatic environments. Do not apply to crops or plants. Do not apply to lawns or ornamental plants.

Manufactured by

EPA Reg. No.

EPA Est. No.

Net Contents

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

PREMIER #131 MICROBIOCIDES is used in industrial and/or commercial recirculating cooling tower systems and industrial air washing systems to control microbial slime. Prior to the use of PREMIER #131 MICROBIOCIDES in industrial and/or commercial recirculating cooling tower systems, systems should be cleaned to remove algal growth, microbiological slime, and other deposits. Then make an initial slug addition of 2.7 to 3.6 fl oz of PREMIER #131 MICROBIOCIDES per 1000 gal. of water to provide 50 to 75 ppm of PREMIER #131 MICROBIOCIDES based on total weight of water in the system. Repeat initial dosage until control is evident. Make subsequent slug addition of 2.9 to 3.6 fl oz of PREMIER #131 MICROBIOCIDES per 1000 gal. of water (25 to 75 ppm PREMIER #131 MICROBIOCIDES) every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of recirculating cooling tower systems.

PREMIER #131 MICROBIOCIDES is used in industrial air washing systems which maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 13.5 to 17.2 fl oz. of PREMIER #131 MICROBIOCIDES per 1000 gal. of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 13.5 to 17.2 fl oz. of PREMIER #131 MICROBIOCIDES per 1000 gallons of water should be employed every 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or the water collection trays of the airwash system.

STORAGE AND DISPOSAL

Do not store in plastic water tank or feed by storage or disposal. Do not store in plastic water tank or feed by storage or disposal. Do not store in plastic water tank or feed by storage or disposal.

ENVIRONMENTAL DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray material, or empty containers may cause pollution. Do not discharge into water. Do not discharge into air. Do not discharge into land. Do not discharge into water.

CONTAINER DISPOSAL: PLASTIC (Type III or equivalent): Offer for recycling or reconditioning, or store and dispose of as secondary waste, by incineration, or if allowed by state and local authorities, by burning, if burned, away from public areas. METAL (Type III or equivalent): Offer for recycling or reconditioning, or store and dispose of as secondary waste, or by other procedures approved by state and local authorities.