



Valspar

VINYL ANTI-FOULING BOTTOM PAINT

*Active Ingredient
 Tributyltin
 chloride 11.7%
 inert ingredients 88.3%
 100.0%
 (Net Wt. 4.25%)

CONTAINS
 PETROLEUM
 DISTILLATES
 KEEP OUT OF
 REACH OF CHILDREN

DANGER!

SEE BACK PANEL FOR
 ADDITIONAL PRECAUTIONARY STATEMENTS

E.P.A. REG. NO. 8177-19
 E.P.A. EST. NO. 8177-11-1

NET 32 FL. OZ.
 (ONE QUART)

3537 COHO BLUE

0.916 LITERS

ACCEPTED
 with comments
 OCT 13 1982
 EPA REG. NO. 8177-19

VINYL ANTI-FOULING BO

Apply directly to fiberglass or "Dry" before under storage. Provides protection and fresh water, such as barnacles.

PRECAUTIONARY STATEMENTS

DANGER TO HUMANS
 IS IRRITANT TO SKIN
 Corrosive. Causes irreparable eye damage and burns. Harmful if absorbed through skin, inhaled, or ingested. Do not get on skin. In case of eye contact, flush eyes with water for safety glasses. Wear protective clothing when in low-visibility outdoor work. Long pants, hat and gloves. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse. Avoid breathing vapors. Spray mist. Get on ships from handling. While spraying, wear a hooding mask. Wash face and hands after handling. See Material Safety Data Sheet for more information. See Material Safety Data Sheet and Safety Administration and the National Institute for Occupational Safety and Health.

STATEMENT OF PRACTICAL VERACITY
 IF MANAGED: Promptly drink a large quantity of milk, soy milk, or water solution if these are not available. Drink large quantities of water. Avoid alcohol. Get medical attention.
 IF IN EYES: Flush with plenty of water. Get medical attention.
 IF ON SKIN: Wash with plenty of soap and water. Get medical attention.
 IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration. Preferably mouth-to-mouth. Get medical attention.

ENVIRONMENTAL HAZARD
 This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of waste. Do not allow strips and dust generated during paint removal to enter water. Stripping of paint should be on approved land fill.

HARMFUL TO AQUATIC LIFE
 Keep away from water. Do not dump or spill.

It is a violation of Federal law to apply this product to a motor vehicle. This product may contain lead and other substances that are regulated by the Federal Government. See the label for more information.

DISPOSAL
 Vinyl anti-fouling paint is a hazardous waste. Do not dump or dispose of in a shallow body of water. See Material Safety Data Sheet for more information. See Material Safety Data Sheet and Safety Administration and the National Institute for Occupational Safety and Health.

PREPARATION
 Prepare the surface to be painted. Remove all old paint and fouling. Clean the surface with a brush or sandpaper. Rinse with water. Dry the surface.

APPLICATION
 Apply the paint with a brush or spray. Apply in a thin, even coat. Allow the paint to dry for 24 hours before use.

REMOVAL
 Remove the paint with a scraper or sandpaper. Rinse the surface with water. Dry the surface.

The Valspar
 MINNEAPOLIS

BEST DOCUMENT AVAILABLE



VINYL ANTI-FOULING BOTTOM PAINT

Applied directly to fiberglass or "Dry" formolite — can be applied before water storage. — Provides protection from marine growth, in salt or fresh water, such as barnacles, Torpedos and Algae.

PRECAUTIONARY STATEMENTS

HAZARD TO HUMANS
 In Summary: IRRITANT.
 Avoid contact with eyes, nose and mouth. If absorbed through skin, wash with soap and water. Do not get in eyes, on clothing, hair, or in mouth. Wear protective clothing such as long-sleeved cotton shirt, long pants, hat and gloves. Wash thoroughly with soap and water after handling. Remove contaminated clothing and keep before reuse. Avoid breathing vapors or spray mist. Do not inhale fumes. Wear a mask or respirator if heavily exposed by the fumes. Follow all instructions on the label for safe use and disposal. See the Material Safety Data Sheet for occupational safety and health.

STATEMENT OF PRACTICAL USES
 IF RECOMMENDED: Apply with a large quantity of water, by brush, sprayer or roller. If these are not available, brush large quantities of water. Wash hands. See medical literature.
 USE TO REMOVE: Stubborn stains. Remove by scrubbing with a stiff brush. Wash with plenty of water. See medical literature.
 IF IN EYES: Wash with plenty of soap and water. See medical literature.
 IF IN MOUTH: Spit out. Do not swallow. Give artificial respiration, preferably mouth-to-mouth. See medical literature.

ENVIRONMENTAL HAZARD:
 This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of water. Do not allow drift and fast currents during paint removal in water areas. Dispose of paint debris in an approved land fill.

PURICAL OR MEDICAL AIDANCE
 (FURNISH)
 Keep away from heat, open flame or sparks.

DIRECTIONS FOR USE

In the Regulation of Federal law or not this product is a normal commercial with a labeling. This product and/or those of special use must be used according to label instructions and be disposed of according to Federal or approved state regulations under article 2 of the Hazardous Conservation and Recovery Act.

DISPENSAL INSTRUCTIONS

Triple check containers. They offer the possibility of contamination by puncture and disposal of in a secondary container. It is by water approved ways and local procedures.
SAFETY NOTE: If previous finish is of vinyl or epoxy composition and is good condition, sand and apply over by three coats. If old paint is not in good condition, sand and apply over by three coats. If old paint is not in good condition, sand and apply over by three coats. If old paint is not in good condition, sand and apply over by three coats.

PREPARATION: Scrub surface with medium grade sand paper and allow to dry. Sand vinyl surface thoroughly to remove gloss. Wash with water and allow to dry. Let dry. Do not apply any primer. Vinyl bottom paint must be applied directly to fiberglass.
APPLICATION: Scrub surface with medium grade sand paper and allow to dry. Sand with 220 sand paper and remove dust with vacuum. Apply primer and allow to dry. Apply two coats of vinyl bottom paint. Allow to dry for 24 hours. Then apply two coats of Valspar Vinyl Fine Chrysolite Primer (1000) allowing at least three hours dry time between coats. If better appearance.

SAFETY: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of water. Do not allow drift and fast currents during paint removal in water areas. Dispose of paint debris in an approved land fill.
KEEP AWAY FROM HEAT, OPEN FLAME OR SPARKS.

ANALYSIS

Epoxy-20%	75%
Phthalic Anhydride	6%
Zinc Oxide	6%
Lead Oxide	7%
Barium	27%
White-71%	
Red Oxide	1%
Lead Oxide	1%
Iron Oxide	1%
Carbon	1%
Hydrocarbon	1%
	100%

ANALYSIS BY THE NATIONAL BUREAU OF STANDARDS, U.S. DEPARTMENT OF COMMERCE, NIST, 4330 RILEY AVE., GAITHERSBURG, MD 20899.

COLORED BROWN ON DRY. APPROXIMATELY 20% IN CASE OF: IS NOT A GUARANTEE OF AN EXACT COLOR MATCH.

The Valspar Corporation
 ANN ARBOR, MICHIGAN 48106

RECEIVED
 with comments
 CT 13 1982
 Federal Inspect
 1 enclosure
 No. 8199-19

File copy

OCT 13 1982

Brian C. Neeth
The Valpar Corporation
1181 Third Street South
P.O. Box 1461
Minneapolis, MN 55440

Dear Mr. Neeth:

Subject: Antifouling Paint Label Improvement Program,
Vinyl Antifouling Bottom Paint
3537 Cobalt Blue
EPA Registration No. 8177-19
Vinyl Antifouling Bottom Paint
3505 White
EPA Registration No. 8177-20
Your Submission of September 27, 1982

The amendment referred to above, submitted in connection with registration under FIFRA sec. 3(c)(7)(A), is acceptable, provided that you:

1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data.
2. Make the labeling changes listed below before you release the product for shipment bearing the amended labeling:
 - a. Add the Signal Word DANGER below Hazards to Humans (A Domestic Animals) on the side panel.
 - b. Delete "or fresh." This is inconsistent with the claim "protection from marine growth."
 - c. Move the heading DISPOSAL to above the paragraph beginning with "This product and/or rinse material...."
 - d. Delete "Formulated without mercury and conforms to all lead...." This statement is misleading and is an implied safety claim. Refer to 40 Code of Federal Regulations §162.10 (a)(5)--False or misleading statements.

We have forwarded the application for "Ace Vinyl Anti-Fouling Bottom Paint Blue 8177-19" to Process Coordinator Branch, Registration Division.

BEST DOCUMENT AVAILABLE

-2- 8177-19

We have no objection to using the existing label stock until June 1, 1981.

1. Submit five (5) copies of your final printed labeling before you release the product for shipment.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product bearing the amended labeling constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely yours,

Richard F. Mountfort *RFM*
Product Manager (23)
Fungicide-Herbicide Branch
Registration Division (78-767)

Enclosure

78-767:Mountfort:DCR-24196:WANG-0382C:ert:Ravent:679-2013:10/7/82

BEST DOCUMENT AVAILABLE