

DR.
FOLING
PAINT

STATEMENTS
0
-1

0.94 LITERS

ACCEPTED
with comments
OCT 13 1982
The Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the purposes registered under
EPA Reg. No. **8177-20**

VINYL ANTI-FOLING BOTTOM PAINT

Applies directly to fiberglass or "dry" laminations — can be applied before underplating. Provides protection from marine growth, in salt or fresh water, such as barnacles, porozoans and algae.

PRECAUTIONARY STATEMENTS

HARMFUL TO HUMANS
IS IRRITANT TO EYES
Corrosive. Causes irreversible eye damage and burns. Harmful if absorbed through skin. Swallowing, or inhaling, or getting on skin, is very, very irritating. Wear protective clothing such as long-sleeved button shirt, long pants, hat and gloves. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse. Avoid breathing vapors; spray part; shut up traps from handling. Avoid spraying paint or coating hot surfaces. Wear a mask or respirator partially approved by the Health, Education and Safety Administration and the National Institute for Occupational Safety and Health.

STATEMENT OF PRACTICAL TREATMENT
IF SWALLOWED: Promptly drink a large quantity of milk, egg whites, or water. Do not induce vomiting. If unable to get water, drink large quantities of water. Avoid alcohol. Get medical attention.
IF ON SKIN: Wash with plenty of soap and water. Get medical attention.
IF IN EYES: Flush with plenty of water. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

ENVIRONMENTAL HAZARD
This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of excess. Do not allow traps and bait containers during paint removal to enter water. Dispose of paint debris in an approved land fill.

PHYSICAL OR CHEMICAL HAZARD
FLAMMABLE:
Keep away from heat.
Open flame or sparks.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. This product and/or these materials that cannot be used according to label instructions may be disposed of according to Federal or approved state procedures under Subtitle C of the Resource Conservation and Recovery Act.

DISPOSAL INSTRUCTIONS

Triple clean containers. Then either for recycling or incineration, or puncture and dispose of in a quantity landfill, or by some approved state and local procedures.
REPAINT WORK: If previous finish is of similar vinyl composition and is good condition, clean, sand and apply one or more coats. **REPAIR:** Always test vinyl bottom paint over the old paint to see if it will lift the old finish off. If previous finish is in questionable condition or is not of a vinyl composition, remove to bare surface. Make any necessary surface repairs and proceed as for new work.
NEW WORK: Prepare surface as recommended for vinyl substrate type of new work.
NOTE: Apply one coat of Valspar Vinyl Bottom Paint (100) with Valspar Vinyl Thinner (100), then apply finish coats as desired. Vinyl bottom paint must be applied directly to wood.

REPAIRS: Scrub surface with fine sandpaper, sand well and allow to dry. Sand fiber-glass thoroughly to remove gloss. Wash with Valspar Vinyl Thinner (100). Let dry. Do not apply any primers. Vinyl bottom paint must be applied directly to fiberglass.
REPAIRS: Scrub surface with fine sandpaper, sand well and allow to dry. Sand fiber-glass thoroughly to remove gloss. Wash with Valspar Vinyl Thinner (100). Let dry. Apply one coat of Valspar Vinyl Wash Primer (100) reduced equally by volume with Valspar Primer (100). Allow primer to dry one hour, but not more than six hours. Then apply two coats of Valspar Vinyl Fine Chromate Primer (100) reduced one at least three hours dry time between coats and before topcoating.

NOTE: For maximum anti-fouling action, freshly underplated is suggested.
NOTE: For maximum anti-fouling action, freshly underplated is suggested.

ANALYSIS

Fiberglass-100%	
Titanium	100%
Barium Hydroxide	87%
Barium	11%
Vinyl-100%	
Vinyl Resin	87%
Barium	11%
Chromate	14%
Hydroxy	81%
Triethylamine	11%
	100%

accumulated without mercury and cadmium in all lead and air pollution regulations 40 C.F.R. 101.10.

COLOR SHOWS BY THE APPEARANCE OF THE CAN AND IS NOT A GUARANTEE OF AN EXACT COLOR MATCH.

The Valspar Corporation
MINNEAPOLIS, MINNESOTA 55416

BEST DOCUMENT AVAILABLE

10
Brian C. Neath
The Valpar Corporation
1101 Third Street South
P.O. Box 1461
Minneapolis, MN 55440

OCT 13 1982

Dear Mr. Neath:

Subject: Antifouling Paint Label Improvement Program,
Vinyl Antifouling Bottom Paint
3537 Cobalt Blue
EPA Registration No. 8177-19
Vinyl Antifouling Bottom Paint
3505 White
EPA Registration No. 8177-20
Your submission of September 27, 1982

The amendment referred to above, submitted in connection with registration under FIFRA sec. 3(a)(7)(B), is acceptable, provided that you:

1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(a)(5) when the Agency requires all registrants of similar products to submit such data.
2. Make the labeling changes listed below before you release the product for shipment bearing the amended labeling:
 - a. Add the Signal Word DANGER below Hazards to Humans (& Domestic Animals) on the side panel.
 - b. Delete "or fresh." This is inconsistent with the claim "protection from marine growth."
 - c. Move the heading DISPOSAL to above the paragraph beginning with "This product and/or rinse material...."
 - d. Delete "Formulated without mercury and conforms to all lead...." This statement is misleading and is an implied safety claim. Refer to 40 Code of Federal Regulations §162.10 (a)(5)--False or misleading statements.

We have forwarded the application for "Ace Vinyl Anti-Fouling Bottom Paint Blue #121-141" to Process Coordinator Branch, Registration Division.

BEST DOCUMENT AVAILABLE

877-30

We have no objection to using the existing label stock until June 1, 1981.

- 1. Submit five (5) copies of your final labeled labeling before you release the product for shipment.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product bearing the amended labeling constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely yours,

Richard F. Mountfort *RFM*
 Product Manager (21)
 Fungicide-Herbicide Branch
 Registration Division (TS-767)

Enclosure

TS-767:Mountfort;DCH-24196;MANG-0502C;ext:Haven;479-2013;10/7/82