



vinyl  
anti-fouling  
for fiberglass,  
wood, metal

ANTI-FOULING CHEMICALS

TOUGH, PROTECTIVE VINYL BASE

NO PRIMER REQUIRED

MAXIMUM RESISTANCE TO ABRASION,

DRIES FAST;

FOR SALT OR FRESH WATER  
APPLIES DIRECTLY TO  
"DRY" FORMULATION—

PREVIOUSLY PAINTED SURFACES  
in good condition; clean surface  
face film is not a vinyl coating  
work.

NEW WORK: Apply 2 or 3 coats  
preparation.

Wood:

1. Fill cracks and striations
2. Do not use a primer.
3. Apply a coat of Foulgard. Allow to dry one gallon of Foulgard.

Fiberglass:

1. Wash surface with a fine sandpaper.
2. Wet sand with medium wet sand, and dry.
3. Wash surface with medium wet sand, and dry.
4. Do not use a primer before sanding.
5. Recoat with one or more coats.

Aluminum:

1. Wash surface with a fine sandpaper.
2. Treat surface with Alum.
3. Follow immediately with Foulgard.
4. Do not sand. Apply a coat of Foulgard. Allow to dry 18 hours.
5. Top coat with this Foulgard.
6. Recoat with one or more coats.

DRYING TIME: To sand and  
NOT FOR USE OR STORAGE  
DO NOT RE-USE CONTAINER  
DO NOT CONTAMINATE WATER

NET CONTENTS ONE GALLON

EPA REGISTRATION NO. 100-075  
distributed by MONTROVIA

**DANGER! FLAMMABLE!**  
**KEEP AWAY FROM HEAT!**  
fatal if swallowed. If swallowed,  
in eyes, on skin or on clothing,  
with plenty of water for at least 15  
through skin. In case of contact  
with soap and water. Wash clothes  
apply on window sills, toys, furniture  
tainer after each use.

ANALYSIS

Pigment - 20922	7.2%
Benzoic Acid - Pyroton Red	13.2%
Silicate	
Vinyl Resin - 75156	34.1%
Vinyl Resin	5.1%
Tributyltin Fluoride	1.1%
Inert Ingredients	38.3%
Ketones	1.2%
Esters	1.8%
Ammonium Hydroxide	1.1%
	100.0%

# VINYL FOULGARD


bottom paint 1 QT. 75-3068  
RED

**DANGER!** HARMFUL OR FATAL IF SWALLOWED. FLAMMABLE. VAPOR HARMFUL.  
KEEP OUT OF REACH OF CHILDREN.  
See other cautions on back panel

\*Active Ingredients  
Tributyltin Fluoride  
Inert Ingredients  
(Tin as Metal 4.8%)

12 335  
87 777  
100 075  
Feb. 28, 1973

8177-28



**ANTI-FOULING CHEMICALS**

**TOUGH, PROTECTIVE VINYL BASE**

**NO PRIMER REQUIRED**

**MAXIMUM RESISTANCE TO ABRASION.**

**DRIES FAST;**

vinyl  
anti-fouling  
for fiberglass,  
wood, metal

# FOULGARD

\*Active Ingredients  
Tributyltin Fluoride  
Inert Ingredients

(Tin as Metal 4.93%)

12.3%  
87.7%  
100.0%

*Feb. 28, 1973*

*8177-28*

75-3068  
RED

HARMFUL OR FATAL IF SWALLOWED. FLAMMABLE. VAPOR HARMFUL.  
KEEP OUT OF REACH OF CHILDREN.  
other cautions on back panel

**FOR SALT OR FRESH WATER.**

APPLIES DIRECTLY TO FIBERGLASS—no primer should be used.  
"DRY" FORMULATION—can be applied before winter storage.

**PREVIOUSLY PAINTED SURFACES:** if previous coating is of similar vinyl composition and in good condition; clean and apply 2 or 3 coats of Montgomery Ward Foulgard. Where surface film is not a vinyl composition, remove coating to bare surface and proceed as for new work.

**NEW WORK:** Apply 2 or more coats of Foulgard Anti-Fouling after the following specific preparation.

**Wood:**

1. Fill cracks and strokes. Sand smooth. Clean and dry the surface.
2. Do not use a primer. Apply this paint directly to clean dry surface.
3. Apply a coat of Foulgard thinned down one pint of Montgomery Ward Vinyl Thinner to one gallon of Foulgard. Allow to dry.

**Fiberglass:**

1. Wash surface with a foaming cleanser.
2. Wet sand with medium grit "Wet-Or-Dry" sandpaper to completely remove gloss. Rinse well, and dry.
3. Wash surface with Montgomery Ward Vinyl Thinner. Dry.
4. Do not use a primer but apply this paint directly to clean, dry surface. Allow to dry. Do not sand.
5. Recoat with one or more coats as desired.

**Aluminum:**

1. Wash surface with a foaming cleanser; rinse well and dry.
2. Treat surface with Aluminum Clean & Etch.
3. Follow immediately with a coat of Alodine. Allow to dry by evaporation.
4. Do not sand. Apply a coat of Montgomery Ward Zinc Chromate Primer. Allow primer to dry 18 hours.
5. Top coat with this Foulgard paint. Do not sand.
6. Recoat with one or more coats as desired.

**DRYING TIME:** To sand and recoat—8 hours; To Launch—48 hours

NOT FOR USE OR STORAGE IN OR AROUND HOUSE

DO NOT RE-USE CONTAINER. DESTROY WHEN EMPTY.

DO NOT CONTAMINATE WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES.

NET CONTENTS ONE QUART    COVERS UP TO 100 SQ. FT.    75P-174P

EPA REGISTRATION NO. 8177-28

**distributed by MONTGOMERY WARD & CO., INC. Chicago, Illinois 60607**

**DANGER! FLAMMABLE! CONTAINS TRIBUTYLTIN FLUORIDE TOLUOL AND KETONES. KEEP AWAY FROM HEAT, OPEN FLAME OR SPARKS.** Causes severe eye damage. Harmful or fatal if swallowed. If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. Do not get in eyes, on skin or on clothing. Wear goggles or face shield when handling. In case of contact flush eyes with plenty of water for at least 15 minutes and CALL PHYSICIAN IMMEDIATELY. May be absorbed through skin. In case of contact with clothing or skin, remove contaminated clothing and wash skin with soap and water. Wash clothing before re-use. Avoid storage near feed and food products. Do not apply on window sills, toys, furniture or interior surfaces which may be used by children. Close container after each use.

Use with adequate ventilation.  
KEEP OUT OF REACH OF CHILDREN.